



Earth leakage add-on block 4P 63A 30mA AC Class

Reference: BD464
 EAN Code: 3250611344643
 Pack quantity: 1 Part
 Product price list: To be defined

Description

Technical information	Values
Connection cross-sect. flexible cable	16mm ²
Connection cross-sect. rigid cable	25 mm ²
Depth of installed product	9 cm
Device family	BD
Electric endurance in number of cycles	2000
Frequency	50 Hz
Hager installation time	230 s
Hager wiring time	120 s
Height of installed product	7 cm
I _{dn} / drop-out	30 mA
Installation time	230 s
Net weight of the product	171.07 g
Neutral position	left
Number of half-modules for the labelling field	0 ½ Mod
Number of mechanical operations	2000
Number of modules	3
Number of poles	4 P
Number of products in the packaging	1
Power loss per pole at I _n	10.7 W
Product group number for calculating the heating processes	1
Protection index IP	IP20
Quantity of half modules of 17,7mm	6 ½ Mod
Rated current	63 A

BD464

Technical information	Values
Rated insulation voltage	500 V
Rated operational voltage Ue	230 V; 400 V
Rated residual operating current	30 mA
Rating current 40°C	63 A
Residual current type	AC
Tightening torque	2,8Nm
Total power loss under IN	35.5 W
Type of pole	4 P
Width of installed product	4 cm
Wiring time	120 s