



3-pole, 63A Modular Switch

Reference: SBN363
 EAN Code: 3250615510228
 Pack quantity: 1 Part
 Product price list: To be defined

Description

Technical information	Values
Acceptable current rating with AC22 category A	63 A
Connection cross-sect. flexible cable	2,5 / 16mm ²
Connection cross-sect. rigid cable	2,5 / 25mm ²
Connection type (text)	With screw
Copper weight of the product	0.06 kg
Depth of installed product	68 mm
Device family	SBN
Frequency	50/60 Hz
Hager installation time	90 s
Hager wiring time	896 s
Height of installed product	83 mm
Installation time	90 s
Net weight of the product	210 g
Number of changeover switch contacts	0
Number of half-modules for the labelling field	6 ½ Mod
Number of mechanical operations	60000
Number of modules	3
Number of NC contacts	0
Number of NO contacts	3
Number of poles	3 P
Number of products in the packaging	1
Product group number for calculating the heating processes	1
Protection index IP	IP20

SBN363

Technical information	Values
Quantity of half modules of 17,7mm	6 ½ Mod
Rated current	63 A
Rated impulse withstand voltage	6000 V
Rated insulation voltage	440 V
Rated operating current, AC22	63 A
Rated operational voltage Ue	400 V
Rated short-circuit making capacity Icm (kA peak) at 400V following IEC 60947-2	1332 A
Short-circuit current with gl-gG fuses	945 A
Tightening torque	2,8Nm
Total power loss under IN	6.9 W
Type of order	Load switch
Type of pole	3 P
Width of installed product	53 mm
Wiring time	896 s