



### Timer

Reference: EZN004  
 EAN Code: 3250612469963  
 Pack quantity: 1 Part  
 Product price list: To be defined

### Description

Technical information	Values
Breaking capacity	AC1
Coil voltage	12-230V AC/12-48V DC
Connection cross-sect. flexible cable	1 / 6mm <sup>2</sup>
Connection cross-sect. rigid cable	1,5 / 10mm <sup>2</sup>
Connection type (text)	With screw
Contact type	1 changeover
Control circuit AC voltage	195 V; 230 V; 253 V
Depth of installed product	58 mm
Device family	EZN004
Fixing mode	Din-Rail
Fixing type	Din-Rail
Frequency	50/60 Hz
Frequency of the control voltage 2	50/60 Hz
Hager installation time	130 s
Hager wiring time	390 s
Height of installed product	85 mm
In contact	8 A - 250 V AC
In, AC1	8 A
Installation time	130 s
Max. current for cos phi 0.6	10 A
Max. power with incandescent lamps	450 W
Max. power with non-offset fluo. tubes	500 VA
Net weight of the product	110 g

## EZN004

Technical information	Values
Number of changeover switch contacts	1
Number of contacts	1
Number of half-modules for the labelling field	2 ½ Mod
Number of modules	1
Number of NC contacts	0
Number of NO contacts	0
Number of products in the packaging	1
Operating temperature	-20 °C to 50 °C
Product group number for calculating the heating processes	2
Protection index IP	IP40
Puissance dissipée par la commande	0.5 W
Quantity of half modules of 17,7mm	2 ½ Mod
Rated current	8 A
Rated operational voltage in DC	12 V; 48 V
Rated operational voltage Ue	12 V; 230 V
Supply voltage	12, 24, 48, or 230V
Time delayed range	0,1s / 10h
Tolerance of the rated DC voltage	-15 % to 10 %
Total power loss under IN	2 W
Width of installed product	18 mm
Wiring time	390 s