



Earth leakage add-on-block 3P 125A 30mA type AC

Reference: BDC380E
 EAN Code: 3250611340010
 Pack quantity: 1 Part
 Product price list: To be defined

Description

Technical information	Values
Connection cross-sect. flexible cable	10 / 50 mm ²
Connection cross-sect. rigid cable	10 / 70 mm ²
Connection type (text)	With screw
Copper weight of the product	0.225 kg
Degree of pollution according to IEC 60664 / IEC 60947-2	3
Depth of installed product	69 mm
Device family	BDC
Electric endurance in number of cycles	1000
Frequency	50 Hz
Hager installation time	200 s
Hager wiring time	0 s
Height of installed product	103 mm
I _{dn} / drop-out	30 mA
Installation time	200 s
Net weight of the product	700 g
Neutral position	Left or right
Number of half-modules for the labelling field	0 ½ Mod
Number of mechanical operations	7000
Number of modules	6
Number of poles	3 P
Number of products in the packaging	1
Power loss per pole at I _n	3.75 W
Product group number for calculating the heating processes	1

BDC380E

Technical information	Values
Protection index IP	2X
Quantity of half modules of 17,7mm	12 ½ Mod
Rated current	125 A
Rated impulse withstand voltage	6000 V
Rated insulation voltage	500 V
Rated operational voltage Ue	230 V; 400 V
Rated residual operating current	30 mA
Rating current 30°C	125 A
Rating current 40°C	118.9 A
Rating current 50°C	112.4 A
Rating current 60°C	105.6 A
Rating current 70°C	99.4 A
Residual current type	AC
Tightening torque	3,5Nm
Total power loss under IN	11.25 W
Type of pole	3 P
Width of installed product	187 mm
Wiring time	0 s