



Air Circuit Breaker Fr A 3P DO 65kA 1250A

Reference: HWAN312ED
 EAN Code: 3250613137540
 Pack quantity: 1 Part
 Product price list: To be defined

Description

Technical information	Values
Breaking capacity	65 kA
Device family	HWAN312ED
Frequency	50 / 60 Hz
Group number of the product for the heating calculation	1
Hager installation time	5730 s
Installation time	5730 s
Instantaneous protection (li)	2500 A
Magnetic protection nob setting xIN	0; 1; 1.5; 2; 2.5; 3; 4; 6; 8; 10
No. of protected poles	3 P - 3d
Number of poles	3 P
Number of products in the packaging	1
Range of the thermal adjustment	1250 A; 1187.5 A; 1125 A; 1062.5 A; 1000 A
Rated current	1250 A
Rated operational voltage Ue	415 V; 690 V
Rated primary current	1250 A
Rated service breaking capacity Ics AC according IEC 60947-2	100 %
Rated ultimate short-circuit breaking capacity Icu under 230V AC IEC 60947-2	65 kA
Rated ultimate short-circuit breaking capacity Icu under 400V AC IEC 60947-2	65 kA
Setting type In or Ith	IN
Short-time short-circuit protection (STD)	1250 A
Total power loss under IN	141 W
Type of pole	3 P
Virtual weight	63000 g

Technical information	Values
Wiring time	9270 s
Wiring time - Hager made	9270 s