

Data sheet

Art.No.: 76.352.0736.1

Hood MIN GOT GB 7 M20 25 Z1

revos MINI size 3 hood with threaded collar M20, top cable entry, single locking lever, metal housing

1011011010001010010101101
0100110110010110100101010
101001101100111001010010
10101001010101010101010
1101010011011001011010010
10101010010101101010011

DIGITALIZATION IN PROGRESS

Art.No.	76.352.0736.1
EAN	4015573651142
Order Unit	10

Technical data

General

Housing material	Die-cast zinc
Color	Grey
Surface	With powder coating
Degree of protection (IP)	Other
UV resistant	Yes
Inflammability class of insulation material acc. with UL94	Other
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

Model

Construction	3
Model	male
Locking mechanism	Single locking lever
Cable entry	Above
Type of cable	Thread
With cable screw gland	No
Thread size M	20
Thread size PG	
Hinged lid	No
EMC-version	No
Length	26.8 mm
Width	33.5 mm
Height	50 mm

Classification

ECLASS 8.1	27440202
ETIM 7.0	EC000437
ETIM 6.0	EC000437
ETIM 5.0	EC000437
ETIM 4.0	EC000437

ETIM 3.0	EC000437
----------	----------