

Data sheet

Art.No.: 46.050.1253.1

Distributor RST16I5V 2P1 TGVG SW

RST16i5 distribution block, 5 pole, application 250/400V with PE, 16 A, 1 input and 2 outputs, 1 input and 2 outputs, coding color black



| | |
|------------|---------------|
| Art.No. | 46.050.1253.1 |
| EAN | 4049088334696 |
| Order Unit | 1 |

Certificates / Approvals



Technical data

General

| | |
|----------------------------------|----------------------------------|
| Rated current | 16 A |
| Rated voltage | 250 V / 400 V |
| Rated impulse voltage | 4 kV |
| Pollution degree | 3 |
| Lockable | self-locking (unlocking by hand) |
| Color of coding/ contact carrier | black |
| Marking of poles | 1, 2, 3, N, PE |

Model

| | |
|---------------------------|-----------------------|
| Number of inputs | 1 |
| Number of outputs | 2 |
| Type of fastening | Yes |
| Degree of protection (IP) | IP66/68 (3m;2h) /IP69 |
| Type of distributor | Distribution block |

Material

| | |
|--|---------------|
| Housing material | Polyamide |
| halogen free | Yes |
| Contact material | CuZn |
| Fire load | 0.267 kWh |
| Insulation components continuous temperature | 100 °C |
| Surface finish | Silver-plated |

Dimensions

| | |
|--------|---------|
| Length | 69.5 mm |
|--------|---------|

| | |
|--------|---------|
| Width | 36.5 mm |
| Height | 60 mm |

Classification

| | |
|------------|----------|
| ECLASS 8.1 | 27440603 |
| ETIM 7.0 | EC002567 |
| ETIM 6.0 | EC002567 |
| ETIM 5.0 | EC002567 |