

Data sheet

Art.No.: 92.030.5958.0

Distributor GST18I3Z 1P1 WS

GST18i3 I-distributor, 3 pole, 1 IN, 1 OUT, without mounting option, coding mains 250 V, 20 A, coding color white

10110110100010100101011101
0100110110010110100101010
1010011101100111001010010
10101001010101010101010010
1101010011011001011010010
1010101001010110101010011

**DIGITALIZATION
IN PROGRESS**

Art.No.	92.030.5958.0
EAN	4015573236813
Order Unit	1

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	No
Color of coding/ contact carrier	white
Marking of poles	L, N, PE

Model

Number of inputs	1
Number of outputs	1
Type of fastening	No
Degree of protection (IP)	IP20
Type of distributor	intermediate coupling

Material

Housing material	Polyamide
halogen free	Yes
Contact material	CuZn
Fire load	0 kWh
Insulation components continuous temperature	100 °C
Surface finish	Tin-plated

Classification

ECLASS 8.1	27440603
ETIM 7.0	EC002567
ETIM 6.0	EC002567

ETIM 5.0	EC002567
ETIM 4.0	EC002567

Dimensions

Length	39 mm
Width	28.2 mm
Height	13 mm