




AVK Series Terminals

AVK Series Screw Connection Rail Terminals provide the whole range of cross sections from 2,5 up to 240 mm². Terminals accessories like Cross Connection, End Plate, Comb Connector are available. Special Marking solutions for each cross section can be provided by Plotter labeling. The color of products can be selected from the color table.




Thanks to push-in type jumpers, AVK RD series 2.5 and 4 mm² cross section feed-through terminal blocks can be cross connected easier and faster way. AVK 2.5 R and AVK 4 R terminals blocks are suitable for double line push-in cross connection, also suitable for strip label.




AVK 2.5 - 4,0 - 6,0 - 10,0 mm² range has the same height and length so that, one type of end plate and partition plate can be used.

You can also use comb type cross connection with AVK series terminal blocks in 2.5 - 4 - 6 - 10 mm² cross sections. All AVK series terminal blocks have special marking solutions for your projects.



You can safely connect solid and stranded cables with ferrules and also you can use stranded cables without ferrule.



AVK RD series earth terminal blocks provide easy and screwless installation on the rail.

FEATURE OF AVK EARTH TERMINAL BLOCKS

Screw type earth terminal blocks can meet all important IEC requirements, such as low contact resistance, corrosion-resistant of connection points, secure screws etc. between 2.5 mm² - 50 mm² cross section options.

Yellow-green (mixed commando) body color is easily distinguishable from other terminal blocks. They do not cause visual problems when they are mounted side by side on the rail, because they are equal in size with the feed-through terminal block in the same cross section.


EASY RAIL MOUNT AND ASSEMBLY

AVK RD series earth terminal blocks provide easy and screwless installation on the rail. For this reason, they are fast and economical, compared to standard screw type earth terminal blocks.

AVK Series
Terminals

AVK 2,5

Width: 5 mm



Cat No:

- 304 120RP
- 304 129RP



Electrical Ratings
CE (EN 60947-7-1)
UL - CuLus
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min-max.)
Conductor cross section stranded (min-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min-max.)
Screwdriver

End Plate - Disconnect Plate

Cross Connection


Comb Connector

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix
Package Quantity

Color							
Color code is the last digit of the order number							
Blue	Green	Yellow	Red	Black	White	Orange	Brown
1	2	3	4	5	6	7	8

AVK 4

Width: 6 mm



Cat No:

- 304 130RP
- 304 139RP

Voltage, V ~	Current, A	Cross-Section
750	32	4 mm²
600	30	AWG 26–10
750	32	4 mm²
600	30	AWG 28–10
630	30,5	

Voltage, V ~	Current, A	Cross-Section
750	32	4 mm²
600	30	AWG 26–10
750	32	4 mm²
600	30	AWG 28–10
630	30,5	

Type	Cat.No.	Qty.
NPP/AVK 2,5-10	444 120	100
APP/AVK 2,5-10	462 120	25

Type	Cat.No.	Qty.
UK 4/2	474 132	25
UK 4/3	474 133	20
UK 4/4	474 134	15
UK 4/10	474 139	5
UK 4/20	474 180	5


Type	Cat.No.	Qty.
TKO 4/2	476 272	25
TKO 4/3	476 273	20
TKO 4/4	476 274	15
TKO 4/10	476 279	5

Type	Cat.No.	Qty.
8/3		
1/A4		
IP 20 / -		
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T		

Package Quantity
80 pcs.

AVK 6

Width: 8 mm



Cat No:

- 304 140RP
- 304 149RP

Voltage, V ~	Current, A	Cross-Section
630	41	6 mm²
600	50	AWG 26–8
630	41	6 mm²
600	40	AWG 28–8
630	41	

Voltage, V ~	Current, A	Cross-Section
630	41	6 mm²
600	50	AWG 26–8
630	41	6 mm²
600	40	AWG 28–8
630	41	

Type	Cat.No.	Qty.
NPP/AVK 2,5-10	444 120	100
APP/AVK 2,5-10	462 120	25

Type	Cat.No.	Qty.
UK 6/2	474 142	25
UK 6/3	474 143	20
UK 6/4	474 144	15
UK 6/10	474 149	5


Type	Cat.No.	Qty.
TKO 6/2	476 282	25
TKO 6/3	476 283	20
TKO 6/4	476 284	15
TKO 6/10	476 289	5

Type	Cat.No.	Qty.
8/3		
1/B5		
IP 20 / -		
D_NS 8x10, DG 10/8		

Package Quantity
60 pcs.

AVK 10

Width: 10 mm



Cat No:

- 304 150RP
- 304 159RP

Voltage, V ~	Current, A	Cross-Section
630	57	10 mm²
600	65	AWG 16-6
630	57	10 mm²
600	65	AWG 16-6
630	57	

Voltage, V ~	Current, A	Cross-Section
630	57	10 mm²
600	65	AWG 16-6
630	57	10 mm²
600	65	AWG 16-6
630	57	

Type	Cat.No.	Qty.
NPP/AVK 2,5-10	444 120	100
APP/AVK 2,5-10	462 120	25

Type	Cat.No.	Qty.
UK 10/2	474 152	25
UK 10/3	474 153	20
UK 10/4	474 154	15
UK 10/10	474 159	5


Type	Cat.No.	Qty.
TKO 10/2	476 292	25
TKO 10/3	476 293	20
TKO 10/4	476 294	15
TKO 10/10	476 299	5

Type	Cat.No.	Qty.
8/3		
1/B6		
IP 20 / -		
D_NS 10x10, DG 10/10		

Package Quantity
50 pcs.

AVK 16

Width: 12 mm



Cat No:

- 304 160
- 304 169

Voltage, V ~	Current, A	Cross-Section
750	76	16 mm²
600	85	AWG 12-4
750	76	16 mm²
630	71	

Voltage, V ~	Current, A	Cross-Section
750	76	16 mm²
600	85	AWG 12-4
750	76	16 mm²
630	71	

Type	Cat.No.	Qty.
NPP/AVK 16	444 160	100
APP/AVK 16	462 160	25

Type	Cat.No.	Qty.
UK 16/2	474 162	25
UK 16/3	474 163	20
UK 16/4	474 164	15
UK 16/10	474 169	5

Type	Cat.No.	Qty.

Type	Cat.No.	Qty.
8/3		
1/B7		
IP 20 / -		
D_NS 10x10, D_NS 12x10, DG 10x10		


Package Quantity
50 pcs.

Color							
Color code is the last digit of the order number							
Blue	Green	Yellow	Red	Black	White	Orange	Brown
1	2	3	4	5	6	7	8

AVK Series
Terminals

AVK 16 RD

Width: 12 mm




Cat No:

- 304 240
- 304 249

AVK 25 RD

Width: 12 mm




Cat No:

- 304 290
- 304 299

AVK 35 RDS

Width: 16 mm




Cat No:

- 304 580
- 304 589

AVK 35 IRDS

Width: 16 mm




Cat No:

- 304 590
- 304 599

AVK 35 RD

Width: 16 mm



Cat No:

- 304 250
- 304 259



Electrical Ratings
CE (EN 60947-7-1)
UL - CuLus
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min-max.)
Conductor cross section stranded (min-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min-max.)
Screwdriver

End Plate - Disconnect Plate

Cross Connection

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix
Package Quantity

Voltage, V ~	Current, A	Cross-Section
750	76	16 mm²
600	80	AWG 12-4
750	76	16 mm²
600	80	AWG 12-4
630	76	

1,5-25 mm²
1,5-25 mm²
0,75-10 mm²
AWG 16-4
12-14 mm
1,2-2,0 Nm
IKT 5 (1,0x5,5)

Type	Cat.No.	Qty.
NPP/AVK 16 RD	444 170	100
APP/AVK 16 RD	462 170	25

Type	Cat.No.	Qty.
UK 16/2	474 162	25
UK 16/3	474 163	20
UK 16/4	474 164	15
UK 16/10	474 169	5

8/3
1/B7
IP 20 / -
D_NS 10x10, D_NS 12x10, DG 10x10
50 pcs.

Voltage, V ~	Current, A	Cross-Section
750	101	25 mm²
600	100	AWG 12-2

1,5-35 mm²
1,5-35 mm²
1,5-10 mm²
AWG 16-2
12-14 mm
2,0-3,0 Nm
IKT 5 (1,0x5,5)

Type	Cat.No.	Qty.
NPP/AVK 25 RD	450 250	50

Type	Cat.No.	Qty.
UK 16/2	474 162	25
UK 16/3	474 163	20
UK 16/4	474 164	15
UK 16/10	474 169	5

8/3
1/B8
IP 20 / -
D_NS 10x10, D_NS 12x10, DG 10x10
50 pcs.

Voltage, V ~	Current, A	Cross-Section
1000	125	35 mm²
600	115	AWG 10-2

6-50 mm²
6-35 mm²
4-16 mm²
AWG 10-2
16-18 mm
4,0-6,0 Nm
IKT 6 (1,2x6,5)

Type	Cat.No.	Qty.

Type	Cat.No.	Qty.
UK 35/2 RDS	480 212	25
UK 35/3 RDS	480 213	20
UK 35/4 RDS	480 214	15
UK 35/10 RDS	480 219	5

8/3
1/B9
IP 20 / -
D_NS 10x10, D_NS 14x10, DG 10/10
50 pcs.

* Higher torque value compare to AVK 35 RD

Voltage, V ~	Current, A	Cross-Section
1000	125	35 mm²
600	115	AWG 10-2

6-50 mm²
6-35 mm²
4-16 mm²
AWG 10-2
16-18 mm
4,0-6,0 Nm
S 5 (DIN6911)

Type	Cat.No.	Qty.

Type	Cat.No.	Qty.
UK 35/2 RDS	480 212	25
UK 35/3 RDS	480 213	20
UK 35/4 RDS	480 214	15
UK 35/10 RDS	480 219	5

8/3
1/B9
IP 20 / -
D_NS 10x10, D_NS 14x10, DG 10/10
50 pcs.

* Inbus screw

Voltage, V ~	Current, A	Cross-Section
750	125	35 mm²
600	115	AWG 12-2
750	125	
600	115	AWG 12-2
630	125	

1,5-50 mm²
1,5-50 mm²
1,5-16 mm²
AWG 16-2
16-18 mm
2,5-3,5 Nm
IKT 6 (1,2x6,5)

Type	Cat.No.	Qty.
APP/AVK 35 RD	462 180	10

Type	Cat.No.	Qty.
UK 35/2	474 172	25
UK 35/3	474 173	20
UK 35/4	474 174	15
UK 35/10	474 179	5


8/3
1/B9
IP 20 / -
D_NS 10x10, D_NS 14x10, DG 10/10
40 pcs.

Color							
Color code is the last digit of the order number							
Blue	Green	Yellow	Red	Black	White	Orange	Brown
1	2	3	4	5	6	7	8

Color							
Color code is the last digit of the order number							
Blue	Green	Yellow	Red	Black	White	Orange	Brown
1	2	3	4	5	6	7	8

AVK T Series
Earth Terminals


AVK 2,5 / 4 TK



Cat No:

334 450


AVK 6 TK



Cat No:

334 460


AVK 10 TK



Cat No:

334 470


AVK 16 T RD



Cat No:

334 200

AVK 35 T RD



Cat No:

334 210



Electrical Ratings
CE (EN 60947-7-2)
UL - CuLus
VDE (IEC 60947-7-2)
CSA
ATEX

Connection Data
Conductor cross section solid (min-max.)
Conductor cross section stranded (min-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min-max.)
Rail Tightening torque, (min-max.)
Screwdriver

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
50 pcs.

Voltage, V ~	Current, A	Cross-Section
		2,5-4 mm²
		AWG 26-10

0,2-6 mm²
0,2-6 mm²
0,5-2,5 mm²
AWG 24-10
9-10 mm
0,5-0,8 Nm
0,4-0,6 Nm
IKT 3 (0,6x3,5)

8/3
1/A4
IP 20 / PE
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

Voltage, V ~	Current, A	Cross-Section
		6 mm²
		AWG 26-8

0,2-10 mm²
0,2-10 mm²
0,5-4 mm²
AWG 24-8
10-12 mm
0,8-1,2 Nm
0,6 -0,8 Nm
IKT 4 (0,8x4)

8/3
1/B5
IP 20 / PE
D_NS 8x10, DG 10/8

25 pcs.

--

Voltage, V ~	Current, A	Cross-Section
		10 mm²
		AWG 16-6

0,5-16 mm²
0,5-16 mm²
0,5-6 mm²
AWG 20-6
10-12 mm
1,2-1,8 Nm
0,8-1,0 Nm
IKT 4 (1,2x6,5)

8/3
1/B6
IP 20 / PE
D_NS 10x10, DG 10/10

25 pcs.

Voltage, V ~	Current, A	Cross-Section
		16 mm²
		AWG 12-4
		16 mm²
		AWG 12-4

1,5-25 mm²
1,5-25 mm²
0,75-10 mm²
AWG 16-4
12-14 mm
1,2-2,0 Nm
1,0-1,2 Nm
IKT 5 (1,2x6,5)

8/3
1/B7
IP 20 / PE
D_NS 10x10, D_NS 12x10, DG 10/10

50 pcs.

Voltage, V ~	Current, A	Cross-Section
		35 mm²
		AWG 12-2
		35 mm²
		AWG 12-2


1,5-50 mm²
1,5-50 mm²
1,5-16 mm²
AWG 16-2
16-18 mm
2,5-3,5 Nm
1,2-1,5 Nm
IKT 6 (1,2x6,5)

8/3
1/B9
IP 20 / PE
D_NS 10x10, D_NS 1x10, DG 10/10

40 pcs.

AVK T Series
Earth Terminals


AVK 35 T RDS



Cat No:

334 240


AVK 35 T IRDS



Cat No:

334 250

AVK 50 T



Cat No:

334 190



Electrical Ratings
CE (EN 60947-7-2)
UL - CuLus
VDE (IEC 60947-7-2)
CSA
ATEX

Connection Data
Conductor cross section solid (min-max.)
Conductor cross section stranded (min-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min-max.)
Rail Tightening torque, (min-max.)
Screwdriver

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
25 pcs.

Voltage, V ~	Current, A	Cross-Section
		35 mm²
		AWG 10-2

6-50 mm²
6-35 mm²
4-16 mm²
AWG 10-2
16-18 mm
4,0-6,0 Nm
1,2-1,5 Nm
IKT 6 (1,2x6,5)

8/3
1/B9
IP 20 / PE
D_NS 10x10, D_NS 14x10, DG 10/10

Voltage, V ~	Current, A	Cross-Section
		35 mm²
		AWG 10-2

6-50 mm²
6-35 mm²
4-16 mm²
AWG 10-2
16-18 mm
4,0-6,0 Nm
1,2-1,5 Nm
S 5 (DIN6911)

8/3
1/B9
IP 20 / PE
D_NS 10x10, D_NS 14x10, DG 10/10

25 pcs.

Voltage, V ~	Current, A	Cross-Section
		50 mm²
		AWG 16-1/0

16-70 mm²
25-50 mm²
10-16 mm²
AWG 10-1/0
22-24 mm
6,0-10 Nm
1,5-2,0 Nm
S 5 (DIN6911)

8/3
1/B10
IP 20 / PE
KOIP SW, SLF-P1 W

10 pcs.

Voltage, V ~	Current, A	Cross-Section
		50 mm²
		AWG 16-1/0



16-70 mm²
25-50 mm²
10-16 mm²
AWG 10-1/0
22-24 mm
6,0-10 Nm
1,5-2,0 Nm
S 5 (DIN6911)

8/3
1/B10
IP 20 / PE
KOIP SW, SLF-P1 W



10 pcs.

AVK RD Series
Terminals



AVK 2,5 RD





AVK 4 RD



AVK 2,5 R



AVK 4 R



Cat No:

- 304 200RP
- 304 209RP

Electrical Ratings
CE (EN 60947-7-1)
UL - CuLus
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min-max.)
Conductor cross section stranded (min-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min-max.)
Screwdriver

End Plate - Disconnect Plate	
	

Cross Connection	
	

Comb Connector	
	

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix
Package Quantity

Cat No:

- 304 210RP
- 304 219RP

Voltage, V ~	Current, A	Cross-Section
750	32	4 mm²
600	30	AWG 26-10
750	32	4 mm²
630	29	

0,2-4 mm²
0,2-4 mm²
0,5-1,5 mm²
AWG 24-12
9-10 mm
0,4-0,6 Nm
IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/AVK 2,5-10	444 120	100
APP/AVK 2,5-10	462 120	25

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

Type	Cat.No.	Qty.
TKO 2,5/2	476 262	25
TKO 2,5/3	476 263	20
TKO 2,5/4	476 264	15
TKO 2,5/10	476 269	5

8/3
1/A3
IP 20 / -
DB 10/5, DG 10/5, DG 10/5T

Cat No:

- 304 409
- 304 400

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²

0,2-4 mm²
0,2-4 mm²
0,5-1,5 mm²
AWG 24-12
9-10 mm
0,4-0,6 Nm
IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/AVK 2,5 R	450 330	25

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

--	--	--

8/3
1/A3
IP 20 / -
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T

Cat No:

- 304 390
- 304 399

Voltage, V ~	Current, A	Cross-Section
800	32	4 mm²

0,2-6 mm²
0,2-6 mm²
0,5-2,5 mm²
AWG 24-10
9-10 mm
0,5-0,8 Nm
IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/AVK 4 R	450 330	25

Type	Cat.No.	Qty.
UK 4/2	476 232	25
UK 4/3	476 233	20
UK 4/4	476 234	15
UK 4/10	476 239	5


--	--	--

8/3
1/A4
IP 20 / -
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

Color							
Color code is the last digit of the order number							
Blue	Green	Yellow	Red	Black	White	Orange	Brown
1	2	3	4	5	6	7	8

AVK RD Series
Earth Terminals


AVK 2,5 T RD



Cat No:

334 170


AVK 4 T RD



Cat No:

334 180


AVK 4 RT



Cat No:

334 270

AVK 2,5 RT



Cat No:

334 280



Electrical Ratings
CE (EN 60947-7-1 / EN 60947-7-2)
UL - CuLus
VDE (IEC 60947-7-1 / EN 60947-7-2)
CSA
ATEX

Connection Data
Conductor cross section solid (min-max.)
Conductor cross section stranded (min-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min-max.)
Rail Tightening torque, (min-max.)
Screwdriver

End Plate - Disconnect Plate

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity

Voltage, V ~	Current, A	Cross-Section
		2,5 mm²
		AWG 26-12

	0,2-4 mm²
	0,2-4 mm²
	0,5-1,5 mm²
	AWG 24-12
	9-10 mm
	0,4-0,6 Nm
	IKT 3 (0,6x3,5)

--

8
1/A3
IP 20 / PE
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T

50 pcs.

Voltage, V ~	Current, A	Cross-Section
		4 mm²
		AWG 26-10

	0,2-6 mm²
	0,2-6 mm²
	0,5-2,5 mm²
	AWG 24-10
	9-10 mm
	0,5-0,8 Nm
	IKT 3 (0,6x3,5)

--

8
1/A4
IP 20 / PE
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

50 pcs.

--

--

Voltage, V ~	Current, A	Cross-Section
		4 mm²

	0,2-6 mm²
	0,2-6 mm²
	0,5-2,5 mm²
	AWG 24-10
	9-10 mm
	0,5-0,8 Nm
	IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP /AVK 4 RT	450 332 T	25

8
1/A4
IP 20 / PE
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

50 pcs.

Voltage, V ~	Current, A	Cross-Section
		2,5 mm²

	0,2-4 mm²
	0,2-4 mm²
	0,5-1,5 mm²
	AWG 24-12
	9-10 mm
	0,4-0,6 Nm
	IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP /AVK 2,5 RT	450 332 T	25

8
1/A3
IP 20 / PE
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T, SLF-P1 W

50 pcs.

AVK RD Series
Earth Terminals



Cat No:

334 220



Electrical Ratings
CE (EN 60947-7-2)
UL - CuLus
VDE (IEC 60947-7-2)
CSA
ATEX

Connection Data
Conductor cross section solid (min-max.)
Conductor cross section stranded (min-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min-max.)
Rail Tightening torque, (min-max.)
Screwdriver

End Plate - Disconnect Plate

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
25 pcs.


Voltage, V ~	Current, A	Cross-Section
		2,5 mm ²
		AWG 26-12
630		

	0,2-4 mm ²
	0,2-4 mm ²
	0,5-1,5 mm ²
	AWG 24-12
	9-10 mm
	0,4-0,6 Nm
	IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/AVK 2,5 CCT	444 132T	25

8/3
1/A3
IP 20 / PE
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T

25 pcs.



Cat No:

334 260


Voltage, V ~	Current, A	Cross-Section
		4 mm ²

	0,2-6 mm ²
	0,2-6 mm ²
	0,5-2,5 mm ²
	AWG 24-10
	9-10 mm
	0,5-0,8 Nm
	IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/AVK 4 CCT	450 342T	25

8/3
1/A4
IP 20 / PE
D-NS 6x10, DG 10/6, DG 10/6T, DB 10/6

50 pcs.



Cat No:

334 230

Voltage, V ~	Current, A	Cross-Section
		10-4 mm ²

	0,5 mm ² / 0,2 mm ² - 16 mm ² / 4 mm ²
	0,5 mm ² / 0,2 mm ² - 16 mm ² / 4 mm ²
	0,5 / 0,5 mm ² - 6 / 1,5 mm ²
	AWG 20/24 - 6 /12
	10/7 - 12/8 mm
	1,2/0,5 - 1,8/0,8 Nm
	0,8 -1,0 Nm
	IKT 3 (0,6x3,5) / IKT 4 (0,8x4,0)

Type	Cat.No.	Qty.


8/3
1/B6-A4
IP 20 / PE
D_NS 10x10, DG 10/10

60 pcs.

AVK Series
Terminals

AVK 10 RD 4

Width: 10 mm



Cat No:

- 304 289
- 304 280

Electrical Ratings
CE (EN 60947-7-1)
UL - CuLus
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min.-max.)
Screwdriver

End Plate - Disconnect Plate

Cross Connection


Comb Connector

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
60 pcs.

AVK 4 CE

Width: 6 mm



Cat No:

- 325 229
- 325 220

Voltage, V ~	Current, A	Cross-Section
500	32	4 mm²

0,5/0,2 mm² - 16/4 mm²
0,5/0,2 mm² - 16/4 mm²
0,5/0,5 - 6/1,5 mm²
AWG 20/24 - 6/12
10/7 - 12/8 mm
1,2-0,5 / 1,8-0,8 Nm
IKT 3 (0,6x3,5) / IKT 4 (0,8x4)

Type	Cat.No.	Qty.
NPP/AVK 4 CE	450 349	25

Type	Cat.No.	Qty.
UK 4/2	476 232	25
UK 4/3	476 233	20
UK 4/4	476 234	15
UK 4/10	476 239	5


TKO 10/2	476 292	25
TKO 10/3	476 293	20
TKO 10/4	476 294	15
TKO 10/10	476 299	5

6/3
1/A4
IP 20 / -
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

50 pcs.

AVK 4 CC

Width: 6 mm



Cat No:

- 325 209
- 325 200

Voltage, V ~	Current, A	Cross-Section
500	32	4 mm²

0,2-6 mm²
0,2-6 mm²
0,5-2,5 mm²
AWG 24-10
9-10 mm
0,5-0,8 Nm
IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/AVK 4 CC	450 349	25


Type	Cat.No.	Qty.
UK 4/2	476 232	25
UK 4/3	476 233	20
UK 4/4	476 234	15
UK 4/10	476 239	5

6/3
1/A4
IP 20 / -
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

50 pcs.

AVK 2,5 CC

Width: 5 mm



Cat No:

- 324 909
- 304 900

Voltage, V ~	Current, A	Cross-Section
750	24	2,5 mm²
600	20	AWG 26-12
630	24	

0,2-4 mm²
0,2-4 mm²
0,5-1,5 mm²
AWG 24-12
9-10 mm
0,4-0,6 Nm
IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/AVK 2,5 CC	444 139	25


Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

8/3
1/A3
IP 20 / -
D_NS 5x10, DB 10/5, Dg 10/5, DG 10/5T

100 pcs.

AVK 4 GD

Width: 6 mm



Cat No:

- 304 270
- 304 279

Voltage, V ~	Current, A	Cross-Section
500	32	4 mm²
500	26	

0,2-6 mm²
0,2-6 mm²
0,5-2,5 mm²
AWG 24-10
9-10 mm
0,5-0,8 Nm
IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/AVK 4GD	444 140	25

Type	Cat.No.	Qty.
UK 4/2	476 232	25
UK 4/3	476 233	20
UK 4/4	476 234	15
UK 4/10	476 239	5

Type	Cat.No.	Qty.
TKO 4/2	476 272	25
TKO 4/3	476 273	20
TKO 4/4	476 274	15
TKO 4/10	476 279	5

8/3
1/A4
IP 20 / -
D_NS 5x6, D_NS 6x10, DB 5, DB 10/6, DG 6/5, DG 10/6, DG 10/6T


100 pcs.

AVK Y Series
Terminals

AVK Y 4

Width: 6 mm





56,10

MR 35 x 7,5

49,40

Cat No:

304 500

304 509

Electrical Ratings	Voltage, V ~	Current, A	Cross-Section
CE (EN 60947-7-1)	800	32	4 mm²
UL - CuLus			
VDE (IEC 60947-7-1)			
CSA			
ATEX			

Connection Data	
Conductor cross section solid (min.-max.)	0,2-6 mm²
Conductor cross section stranded (min.-max.)	0,2-6 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-2,5 mm²
AWG Conductor	AWG 24-10
Insulation Stripping Length (min.-max.)	10-12 mm
Torque (min.-max.)	0,5-0,8 Nm
Screwdriver	IKT 3 (0,6x3,5)

End Plate - Disconnect Plate	Type	Cat.No.	Qty.
	NPP AVK Y 4/6	450 300	50

Cross Connection	Type	Cat.No.	Qty.
	UK 4/2	474 132	25
	UK 4/3	474 133	20
	UK 4/4	474 134	15
	UK 4/10	474 139	5
	Uk 4/20	474 180	5
	UK 4/50	474 190	5


Technical Data	
Rated Impulse Voltage / Pollution severity	8/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/B4
Protection class / Protection conductor type	IP 20 / -
Marking Tags (Dekafix)	
See pages 326-333 for a list of Dekafix	DB 10/6, DG 10/6T, SLF-P1 W

Package Quantity	
	120 pcs.

AVK Y 4 A

Width: 6 mm





57,70

MR 35 x 7,5

61,15

Cat No:

304 600

304 609

Electrical Ratings	Voltage, V ~	Current, A	Cross-Section
	500	32	4 mm²

Connection Data	
Conductor cross section solid (min.-max.)	0,2-6 mm²
Conductor cross section stranded (min.-max.)	0,2-6 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-2,5 mm²
AWG Conductor	AWG 24-10
Insulation Stripping Length (min.-max.)	10-12 mm
Torque (min.-max.)	0,5-0,8 Nm
Screwdriver	IKT 3 (0,6x3,5)

End Plate - Disconnect Plate	Type	Cat.No.	Qty.
	NPP AVK Y 4A	450 390	20

Cross Connection	Type	Cat.No.	Qty.
	UK 4/2	474 132	25
	UK 4/3	474 133	20
	UK 4/4	474 134	15
	UK 4/10	474 139	5
	Uk 4/20	474 180	5
	UK 4/50	474 190	5


Technical Data	
Rated Impulse Voltage / Pollution severity	8/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/B4
Protection class / Protection conductor type	IP 20 / -
Marking Tags (Dekafix)	
	D-NS 6x10, DG 10/6, DG 10/6T, DB 10/6, SLF-P1 W

Package Quantity	
	30 pcs.

AVK Y 6

Width:8 mm





56,10

MR 35 x 7,5

49,40

Cat No:

304 510

304 519

Electrical Ratings	Voltage, V ~	Current, A	Cross-Section
	800	41	6 mm²

Connection Data	
Conductor cross section solid (min.-max.)	0,2-10 mm²
Conductor cross section stranded (min.-max.)	0,2-10 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-4 mm²
AWG Conductor	AWG 24-8
Insulation Stripping Length (min.-max.)	10-12 mm
Torque (min.-max.)	0,8-1,2 Nm
Screwdriver	IKT 4 (0,8x0,4)

End Plate - Disconnect Plate	Type	Cat.No.	Qty.
	NPP AVK Y 4/6	450 300	50

Cross Connection	Type	Cat.No.	Qty.
	UK 6/2	474 142	25
	UK 6/3	474 143	20
	UK 6/4	474 144	15
	UK 6/10	474 149	5

Technical Data	
Rated Impulse Voltage / Pollution severity	8/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/B5
Protection class / Protection conductor type	IP 20 / -
Marking Tags (Dekafix)	
	D_NS 8x10, DG 10/8, SLF-P1 W

Package Quantity	
	90 pcs.

AVK Y 10

Width:10 mm





59,20

MR 35 x 7,5

49,40

Cat No:

304 520

304 529

Electrical Ratings	Voltage, V ~	Current, A	Cross-Section
	800	57	10 mm²

Connection Data	
Conductor cross section solid (min.-max.)	0,5-16 mm²
Conductor cross section stranded (min.-max.)	0,5-16 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-6 mm²
AWG Conductor	AWG 20-16
Insulation Stripping Length (min.-max.)	10-12 mm
Torque (min.-max.)	1,2-1,8 Nm
Screwdriver	IKT 4 (0,8x0,4)

End Plate - Disconnect Plate	Type	Cat.No.	Qty.
	NPP/AVK Y 10	450 260	50

Cross Connection	Type	Cat.No.	Qty.
	UK 10/2	474 152	25
	UK 10/3	474 153	20
	UK 10/4	474 154	15
	UK 10/10	474 159	5

Technical Data	
Rated Impulse Voltage / Pollution severity	8/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/B6
Protection class / Protection conductor type	IP 20 / -
Marking Tags (Dekafix)	
	D_NS 10x10, DG 10/10, SLF-P1 W

Package Quantity	
	70 pcs.

50

51

MVK Type
Mini Terminals
for MR 15 Rails

Width: 5 mm

33,75

MR 35 x 5,5

27,00

Cat No:

304 429

304 420

Electrical Ratings	Voltage, V ~	Current, A	Cross-Section
CE (EN 60947-7-1 / EN 60947-7-2)	400	24	2,5 mm²
UL - CuLus	300	20	AWG 26-12
VDE (IEC 60947-7-1)			
CSA			
ATEX	400	23	

Connection Data	
Conductor cross section solid (min.-max.)	0,2-4 mm²
Conductor cross section stranded (min.-max.)	0,2-4 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-1,5 mm²
AWG Conductor	AWG 24-12
Insulation Stripping Length (min.-max.)	9-10 mm
Torque (min.-max.)	0,4-0,6 Nm
Screwdriver	IKT 3 (0,6x3,5)

End Plate - Disconnect Plate	Type	Cat.No.	Qty.
	NPP/MVK 2,5-4	444 429	100

Cross Connection	Type	Cat.No.	Qty.
	UK 2,5/2	476 222	25
	UK 2,5/3	476 223	20
	UK 2,5/4	476 224	15
	UK 2,5/10	476 229	5

Technical Data	
Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/B3
Protection class / Protection conductor type	IP 20 / -
Marking Tags (Dekafix)	
See pages 326-333 for a list of Dekafix	DB 5

Package Quantity	
	100 pcs.

Width: 6 mm

33,75

MR 35 x 5,5

27,00

Cat No:

304 439

304 430

Electrical Ratings	Voltage, V ~	Current, A	Cross-Section
	400	32	4 mm²
	300	30	AWG 24-10
	400	31,5	

Connection Data	
Conductor cross section solid (min.-max.)	0,2-6 mm²
Conductor cross section stranded (min.-max.)	0,2-6 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-2,5 mm²
AWG Conductor	AWG 24-10
Insulation Stripping Length (min.-max.)	9-10 mm
Torque (min.-max.)	0,5-0,8 Nm
Screwdriver	IKT 3 (0,6x3,5)

End Plate - Disconnect Plate	Type	Cat.No.	Qty.
	NPP/MVK 2,5-4	444 429	100

Cross Connection	Type	Cat.No.	Qty.
	UK 4/2	476 232	25
	UK 4/3	476 233	20
	UK 4/4	476 234	15
	UK 4/10	476 239	5

Technical Data	
Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/B4
Protection class / Protection conductor type	IP 20 / -
Marking Tags (Dekafix)	
See pages 326-333 for a list of Dekafix	DB 5

Package Quantity	
	100 pcs.

Width: 5 mm

33,75

MR 35 x 5,5

27,00

Cat No:

334 420

Electrical Ratings	Voltage, V ~	Current, A	Cross-Section
			2,5 mm²
			AWG 26-12
	400		

Connection Data	
Conductor cross section solid (min.-max.)	0,2-4 mm²
Conductor cross section stranded (min.-max.)	0,2-4 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-1,5 mm²
AWG Conductor	AWG 24-12
Insulation Stripping Length (min.-max.)	9-10 mm
Torque (min.-max.)	0,4-0,6 Nm
Screwdriver	IKT 3 (0,6x3,5)

End Plate - Disconnect Plate	Type	Cat.No.	Qty.
	NPP/MVK 2,5T	444 422T	100

Cross Connection			

Technical Data	
Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/B3
Protection class / Protection conductor type	IP 20 / PE
Marking Tags (Dekafix)	
See pages 326-333 for a list of Dekafix	DB 5

Package Quantity	
	50 pcs.

Width: 6 mm

33,75

MR 35 x 5,5

27,00

Cat No:

334 430

Electrical Ratings	Voltage, V ~	Current, A	Cross-Section
			4 mm²
			AWG 24-10
	400		

Connection Data	
Conductor cross section solid (min.-max.)	0,2-6 mm²
Conductor cross section stranded (min.-max.)	0,2-6 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-2,5 mm²
AWG Conductor	AWG 24-10
Insulation Stripping Length (min.-max.)	9-10 mm
Torque (min.-max.)	0,5-0,8 Nm
Screwdriver	IKT 3 (0,6x3,5)

End Plate - Disconnect Plate	Type	Cat.No.	Qty.
	NPP/MVK 4T	444 422T	100

Cross Connection			

Technical Data	
Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/B4
Protection class / Protection conductor type	IP 20 / PE
Marking Tags (Dekafix)	
See pages 326-333 for a list of Dekafix	DB 5

Package Quantity	
	50 pcs.

52


53

Functional Terminals and Sockets

AVK 2,5 F

Width: 6 mm





50,10

MR 35 x 7,5

57,10

Cat No:

324 929

324 920

Electrical Ratings	Voltage, V ~	Current, A	Cross-Section
CE (EN 60947-7-1)	400	16	2,5 mm²
UL - CuLus			
VDE (IEC 60947-7-1)			
CSA			
ATEX			

Connection Data	
Conductor cross section solid (min.-max.)	0,2-4 mm²
Conductor cross section stranded (min.-max.)	0,2-4 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-1,5 mm²
AWG Conductor	AWG 24-12
Insulation Stripping Length (min.-max.)	9-10 mm
Torque (min.-max.)	0,4-0,6 Nm
Screwdriver	IKT 3 (0,6x3,5)

End Plate - Disconnect Plate	Type	Cat.No.	Qty.
	NPP AVK 2,5 F	444 139	25

Technical Data For Diode	
Diode Voltage	
Diode Current	
Diod	


Technical Data	
Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/A3
Protection class / Protection conductor type	IP 20 / -
Marking Tags (Dekafix)	
See pages 326-333 for a list of Dekafix	D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T

Package Quantity
80 pcs.

AVK 2,5 CF

Width: 6 mm





50,10

MR 35 x 7,5

57,10

Cat No:

324 919

324 910

Electrical Ratings	Voltage, V ~	Current, A	Cross-Section
	400	16	4 mm²

Connection Data	
Conductor cross section solid (min.-max.)	0,2-4 mm²
Conductor cross section stranded (min.-max.)	0,2-4 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-1,5 mm²
AWG Conductor	AWG 24-12
Insulation Stripping Length (min.-max.)	9-10 mm
Torque (min.-max.)	0,4-0,6 Nm
Screwdriver	IKT 3 (0,6x3,5)

End Plate - Disconnect Plate	Type	Cat.No.	Qty.
	NPP AVK 2,5 CF	444 139	25

Technical Data For Diode	
Diode Voltage	
Diode Current	
Diod	

Technical Data	
Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/A3
Protection class / Protection conductor type	IP 20 / -
Marking Tags (Dekafix)	
See pages 326-333 for a list of Dekafix	D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T

Package Quantity
80 pcs.

AVK SKT

Width: 5,80 mm





39,10

38,30

Cat No:

498 759

498 750

Electrical Ratings	Voltage, V ~	Current, A	Cross-Section
	400	16	2,5 mm²

Connection Data	
Conductor cross section solid (min.-max.)	0,2-0,4 mm²
Conductor cross section stranded (min.-max.)	0,2-0,4 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-1,5 mm²
AWG Conductor	AWG 24-12
Insulation Stripping Length (min.-max.)	6-7 mm
Torque (min.-max.)	0,4-0,6 Nm
Screwdriver	IKT 3 (0,6x3,5)

End Plate - Disconnect Plate	Type	Cat.No.	Qty.

Technical Data For Diode	
Diode Voltage	1000V
Diode Current	1A
Diod	1 N 4007

Technical Data	
Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/A3
Protection class / Protection conductor type	IP 20 / PE
Marking Tags (Dekafix)	
See pages 326-333 for a list of Dekafix	D_NS 5x6, DB 5, DG 6/5

Package Quantity
50 pcs.

NOTE: AVK SKTD product is just used with AVK 2,5 F and AVK 2,5 CF terminals.

AVK SKTD

Width: 5,80 mm





39,10

38,30

Cat No:

498 859

498 850

Electrical Ratings	Voltage, V ~	Current, A	Cross-Section
	400	0,5	2,5 mm²

Connection Data	
Conductor cross section solid (min.-max.)	0,2-0,4 mm²
Conductor cross section stranded (min.-max.)	0,2-0,4 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-1,5 mm²
AWG Conductor	AWG 24-12
Insulation Stripping Length (min.-max.)	6-7 mm
Torque (min.-max.)	0,4-0,6 Nm
Screwdriver	IKT 3 (0,6x3,5)

End Plate - Disconnect Plate	Type	Cat.No.	Qty.

Technical Data For Diode	
Diode Voltage	1000V
Diode Current	1A
Diod	1 N 4007

Technical Data	
Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/A3
Protection class / Protection conductor type	IP 20 / PE
Marking Tags (Dekafix)	
See pages 326-333 for a list of Dekafix	D_NS 5x6, DB 5, DG 6/5

Package Quantity
50 pcs.

NOTE: AVK SKTD product is just used with AVK 2,5 F and AVK 2,5 CF terminals.


54

55

AVK PV Series
Terminals



AVK 16 PV



Cat No:

- 304 160 P
- 304 169 P
- 304 161 P

Electrical Ratings
CE (EN 60947-7-1)
UL - CuLus
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min.-max.)
Screwdriver


End Plate - Disconnect Plate

Cross Connection

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
50 pcs.

AVK 35 RD PV



Cat No:

- 304 250 P
- 304 259 P
- 304 251 P

Electrical Ratings
750
1000

Connection Data
1,5-50 mm²
1,5-50 mm²
1,5-16 mm²
AWG 16-2
16-18 mm
2,5-3,5 Nm
IKT 6 (1,2x6,5)

Type	Cat.No.	Qty.
NPP / AVK 16	444 160	100
APP / AVK 16	462 160	25


Type	Cat.No.	Qty.
UK 16/2	474 162	25
UK 16/3	474 163	22
UK 16/4	474 164	15
UK 16/10	474 169	5

Type	Cat.No.	Qty.
UK 35/2	474 172	25
UK 35/3	474 173	22
UK 35/4	474 174	15
UK 35/10	474 179	5

Type	Cat.No.	Qty.
8/3		
1/B7		
IP 20 / -		
D-NS 12x10, DG 10/10		

Type	Cat.No.	Qty.
40 pcs.		

AVK 50 PV



Cat No:

- 304 330 P
- 304 339 P
- 304 331 P

Electrical Ratings
1000
1000

Connection Data
16-70 mm²
25-50 mm²
10-16 mm²
AWG 10-1/0
22-24 mm
6-10 Nm
S 5 (DIN 6911)


Type	Cat.No.	Qty.
UK 50/2	478 332	5
UK 50/3	478 333	5
UK 50/4	478 334	5

Type	Cat.No.	Qty.
UK 50/2	478 332	5
UK 50/3	478 333	5
UK 50/4	478 334	5

Type	Cat.No.	Qty.
8/3		
1/B10		
IP 20 / -		
KOIP SM W		

Type	Cat.No.	Qty.
25 pcs.		

AVK 70 PV



Cat No:

- 304 190 P
- 304 199 P
- 304 191 P

Electrical Ratings
750
1000

Connection Data
16-70 mm²
16-70 mm²
16-25 mm²
AWG 6-2/0
22-24 mm
6-12 Nm
S 6 (DIN 6911)


Type	Cat.No.	Qty.
UK 70/2	478 372	5
UK 70/3	478 373	5
UK 70/4	478 374	5

Type	Cat.No.	Qty.
UK 70/2	478 372	5
UK 70/3	478 373	5
UK 70/4	478 374	5

Type	Cat.No.	Qty.
8/3		
1/A11		
IP 20 / -		
D-NS 12x10, DG 10/10		

Type	Cat.No.	Qty.
25 pcs.		

AVK 70 RD PV



Cat No:

- 304 490 P
- 304 499 P
- 304 491 P

Electrical Ratings
1000
1000

Connection Data
16-70 mm²
16-70 mm²
16-25 mm²
AWG 6-2/0
22-24 mm
6-12 Nm
S 6 (DIN 6911)

Type	Cat.No.	Qty.
UK 70/2	478 372	5
UK 70/3	478 373	5
UK 70/4	478 374	5

Type	Cat.No.	Qty.
UK 70/2	478 372	5
UK 70/3	478 373	5
UK 70/4	478 374	5

Type	Cat.No.	Qty.
8/3		
1/A11		
IP 20 / -		
D-NS 12x10, DG 10/10		






Type	Cat.No.	Qty.
10 pcs.		

PB, CPB Series Terminals

PB & CPB Series Ring and Fork Type Plug inTerminals are suitable for heavy industries and provide practical safe connection. For PB series, cable assembly is done with insulated ring type terminals. With this feature, they are preferred in iron and steel plants, mining industry and medium voltage modular units. PB & CPB Series provide cross section for 6 mm². Comb connector and End plate are available. Special Marking solutions can be provided by Plotter labeling.



Cable assembly for CPB Series is done with insulated fork type terminals.
CPB Series provide cross section for 6 mm².
Special Marking solutions can be provided by Plotter labeling.




PB - CPB Series
Feed Through and
Earth Terminals



PB 2,5/NM

Width: 9 mm




Cat No:

308 029

PB 2,5K/NM

Width: 9 mm




Cat No:

308 039

PB 2,5T/NM

Width: 10 mm




Cat No:

337 010

PB 6/NM

Width: 11 mm




Cat No:

308 009

PB 6K/NM

Width: 11 mm



Cat No:

308 019



Electrical Ratings
CE (EN 60947-7-1 / EN 60947-7-2)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20/15	AWG 26-14
600	20/15	AWG 26-14

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20/15	AWG 26-14
600	20/15	AWG 26-14

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20/15	AWG 26-14
600	20/15	AWG 26-14

Voltage, V ~	Current, A	Cross-Section
800	41	6 mm²
600	45	AWG 22-8
600	45	AWG 22-8

Voltage, V ~	Current, A	Cross-Section
800	41	6 mm²
600	45	AWG 22-8
600	45	AWG 22-8

Voltage, V ~	Current, A	Cross-Section
800	41	6 mm²
600	45	AWG 22-8
600	45	AWG 22-8

Connection Data
Conductor cross section solid (min-max.)
Conductor cross section stranded (min.-max.)
AWG Conductor
Torque (min-max.)
Hole Diameter
Bolt Diameter
Screwdriver
Rail Tightening torque, min-max.

Type	Cat.No.	Qty.
NPP/PB 2,5/NM	451 029	25
APP/PB 2,5-6/NM	464 009	25

Type	Cat.No.	Qty.
NPP/PB 2,5/NM	451 029	25
APP/PB 2,5-6/NM	464 009	25

Type	Cat.No.	Qty.
NPP/PB 2,5/NM	451 029	25
APP/PB 2,5-6/NM	464 009	25

Type	Cat.No.	Qty.
NPP / PB 6/NM	451 019	25
APP / PB 2,5-6/NM	464 009	25

Type	Cat.No.	Qty.
NPP / PB 6/NM	451 019	25
APP / PB 2,5-6/NM	464 009	25

Type	Cat.No.	Qty.
NPP / PB 6/NM	451 019	25
APP / PB 2,5-6/NM	464 009	25

End Plate - Disconnect Plate
TKO PB 2,5/2
TKO PB 2,5/3
TKO PB 2,5/4
TKO PB 2,5/7
TKO PB 2,5/10

Type	Cat.No.	Qty.
TKO PB 2,5/2	479 012	25
TKO PB 2,5/3	479 013	20
TKO PB 2,5/4	479 014	15
TKO PB 2,5/7	479 017	5
TKO PB 2,5/10	479 019	5

Type	Cat.No.	Qty.
TKO PB 2,5/2	479 012	25
TKO PB 2,5/3	479 013	20
TKO PB 2,5/4	479 014	15
TKO PB 2,5/7	479 017	5
TKO PB 2,5/10	479 019	5

Type	Cat.No.	Qty.
TKO PB 2,5/2	479 012	25
TKO PB 2,5/3	479 013	20
TKO PB 2,5/4	479 014	15
TKO PB 2,5/7	479 017	5
TKO PB 2,5/10	479 019	5

Type	Cat.No.	Qty.
TKO- PB 6/2	479 002	25
TKO- PB 6/3	479 003	20
TKO- PB 6/4	479 004	15
TKO- PB 6/7	479 007	5
TKO- PB 6/10	479 009	5

Type	Cat.No.	Qty.
TKO- PB 6/2	479 002	25
TKO- PB 6/3	479 003	20
TKO- PB 6/4	479 004	15
TKO- PB 6/7	479 007	5
TKO- PB 6/10	479 009	5

Type	Cat.No.	Qty.
TKO- PB 6/2	479 002	25
TKO- PB 6/3	479 003	20
TKO- PB 6/4	479 004	15
TKO- PB 6/7	479 007	5
TKO- PB 6/10	479 009	5

Cross Connection
TF (Ø2,3)

Type	Cat.No.	Qty.
TF (Ø2,3)	493 023	5

Type	Cat.No.	Qty.
TF (Ø2,3)	493 023	5

Type	Cat.No.	Qty.
TF (Ø2,3)	493 023	5

Type	Cat.No.	Qty.
TF (Ø2,3)	493 023	5

Type	Cat.No.	Qty.
TF (Ø2,3)	493 023	5

Type	Cat.No.	Qty.
TF (Ø2,3)	493 023	5

Test Plug
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

Type	Cat.No.	Qty.
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T		

Type	Cat.No.	Qty.
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T		

Type	Cat.No.	Qty.
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T		

Type	Cat.No.	Qty.
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T		

Type	Cat.No.	Qty.
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T		

Type	Cat.No.	Qty.
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T		

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix
Package Quantity

8/3
1/NA
IP 20 / -
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T
45 pcs.

8/3
1/NA
IP 20 / -
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T
45 pcs.

8/3
1/NA
IP 20 / PE
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T
45 pcs.

8/3
1/NA
IP 20 / -
DN_S 8x10, DG 10/8
40 pcs.


8/3
1/NA
IP 20 / -
DN_S 8x10, DG 10/8
40 pcs.

8/3
1/NA
IP 20 / -
DN_S 8x10, DG 10/8
40 pcs.

PB - CPB Series
Feed Through and
Earth Terminals




PB 6 T/NM



Cat No:

337 000


PB 25/NM (M5)



Cat No:

308 049


PB 25/NM (M6)



Cat No:

308 059


CPB 6



Cat No:

326 809
326 800

CPB 6 B



Cat No:

326 819
326 810



Electrical Ratings
CE (EN 60947-7-1 / EN 60947-7-2)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min-max.)
Conductor cross section stranded (min.-max.)
AWG Conductor
Torque (min-max.)
Hole Diameter
Bolt Diameter
Screwdriver
Rail Tightening torque, min-max.

End Plate - Disconnect Plate

Comb Connection

Cross Connector

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
40 pcs.

Voltage, V ~	Current, A	Cross-Section
		6 mm²
		AWG 22-8
		AWG 22-8

0,5-6 mm²
0,5-6 mm²
AWG 22-8
0,8-1,2 Nm
4 mm
4,0 mm
IKT 5 (1,0x5,5)
0,6-08 Nm

Type	Cat.No.	Qty.
NPP PB 25/NM	451 039	25
APP PB 25/NM	464 019	25

Type	Cat.No.	Qty.

Type	Cat.No.	Qty.
TKO PB 25/2	479 022	25

8/3
1/NA
IP 20 / PE
D_NS 8x10, DG 10/8

40 pcs.

Voltage, V ~	Current, A	Cross-Section
800	101	25 mm²
600	115/85	AWG 26-4
600	115/85	AWG 26-4

1,5-25 mm²
1,5-25 mm²
AWG 26-4
3-3,5 Nm
5,2 mm
5,0 mm
IKT 5 (1,0x5,5)

Type	Cat.No.	Qty.
NPP PB 25/NM	451 039	25
APP PB 25/NM	464 019	25

Type	Cat.No.	Qty.

Type	Cat.No.	Qty.
TKO PB 25/2	479 022	25

8/3
1/NA
IP 20 / PE
D_NS 10x10, DG 10/10

10 pcs.

Voltage, V ~	Current, A	Cross-Section

Type	Cat.No.	Qty.
NPP PB 25/NM	451 039	25
APP PB 25/NM	464 019	25

Type	Cat.No.	Qty.

Type	Cat.No.	Qty.
TKO PB 25/2	479 022	25

--

Voltage, V ~	Current, A	Cross-Section
800	101	25 mm²
600	115/85	AWG 26-4
600	115/85	AWG 26-4

1,5-25 mm²
1,5-25 mm²
AWG 16-4
3,2-3,7 Nm
6,2 mm
6,0 mm
IKT 5 (1,0x5,5)

Type	Cat.No.	Qty.
NPP PB 25/NM	451 039	25
APP PB 25/NM	464 019	25

Type	Cat.No.	Qty.

Type	Cat.No.	Qty.
TKO PB 25/2	479 022	25

8/3
1/NA
IP 20 / PE
D_NS 10x10, DG 10/10

10 pcs.

Voltage, V ~	Current, A	Cross-Section
800	41	6 mm²

0,5-6 mm²
0,5-6 mm²
AWG 20-10
0,8-1,2 Nm
3,5 mm
IKT 4 (0,8x4,0)

Type	Cat.No.	Qty.
NPP CPB 6	450 289	50

Type	Cat.No.	Qty.
UK 9,5/2	480 192	25
UK 9,5/3	480 193	20
UK 9,5/4	480 194	15
UK 9,5/7	480 197	10
UK 9,5/10	480 199	5

Type	Cat.No.	Qty.

8/3
1/NA
IP 20
D_NS 5x6, DB 5, DG 6/5

50 pcs.

Voltage, V ~	Current, A	Cross-Section
800	57	10 mm²

0,5-10 mm²
0,5-10 mm²
AWG 20-8
1,2-1,8 Nm
4 mm
IKT 4 (0,8x4,0)

Type	Cat.No.	Qty.
NPP/CPB 6	450 299	50

Type	Cat.No.	Qty.
UK 13/2	480 202	25
UK 13/3	480 203	20
UK 13/4	480 204	15
UK 13/7	480 207	10
UK 13/10	480 209	5





Type	Cat.No.	Qty.

8/3
1/NA
IP 20
D_NS 5x6, DB 5, DG 6/5

25 pcs.

High Current / PB Series / Bolt Connection Terminals

AVK Series Screw Connection High Current Terminals provide 50 240 mm² cross-section range. Cross Connection can be used for terminals with all cross-sections. These terminal blocks are fixed to each other via pins on sides, providing a rigid performance on DIN Rail and easy montage advantages in constricted environments where connection with Insulated Terminals are difficult. EK-6 terminals are used for taking additional cable (for signals etc.) from high current (big cross sectioned) terminal blocks. Marking solutions can be provided by Plotter Labeling.



For the panels where connection on din rails are not possible, AVK PB Series Screw Connection High Current Terminal is a good alternative where it can be mounted directly into the base of the cabinet with screws. These terminals have all the same features as High Current Terminals mounted on DIN-Rail. Special Marking solutions for each cross section can be provided by Plotter Labeling.

AVK Busbar Type High Current Terminals provides 95 240 mm² cross-section range, when cable connection is done by insulated terminals connected to the Types of the conductor. Isolation cover is designed for insulated terminals having different dimensions. Cross Connection can be used for terminals with all cross-sections. A fixing screw is available in order to maintain a more secure mounting on the DIN rail. Marking solutions can be provided by Plotter Labeling.

High Current
Terminals

AVK 50

Width: 20 mm



77,00
MR 35 x 7,5

95,20

Cat No:

- 304 330
- 304 339

Hexagon Socket Screw



Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min.-max.)
Screwdriver

Cross Connection


AVK / EK6


Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
25 pcs.

AVK 70 RD

Width: 22 mm



81,00
MR 35 x 7,5

94,60

Cat No:

- 304 490
- 304 499

Hexagon Socket Screw

Electrical Ratings
1000
600
800

Connection Data
16-70 mm ²
16-70 mm ²
10-16 mm ²
16-25 mm ²
AWG 10-1/0
22-24 mm
6-10 Nm
S5 (DIN 6911)

Type	Cat.No.	Qty.
UK 70/2	478 372	5
UK 70/3	478 373	5
UK 70/4	478 374	5

Type	Cat.No.	Qty.

Technical Data
8/3
1/A11
IP 10 / -
KOIP SW, SLF-P1 W

Package Quantity
10 pcs.

AVK 95

Width: 25 mm



90,00
MR 35 x 7,5

95,20

Cat No:

- 304 340
- 304 349

Hexagon Socket Screw

Electrical Ratings
1000
600
1000

Connection Data
25-95 mm ²
35-95 mm ²
16-35 mm ²
AWG 4-3/0
26-28 mm
10-15 Nm
S6 (DIN 6911)

Type	Cat.No.	Qty.
UK 95/2	478 342	5
UK 95/3	478 343	5
UK 95/4	478 344	5

Type	Cat.No.	Qty.
AVK / EK6	304 370	20

Technical Data
8/3
1/B12
IP 10 / -
KOIP SW, SLF-P1 W

Package Quantity
6 pcs.

AVK 150

Width: 31 mm



107,50
MR 35 x 7,5

95,50

Cat No:

- 304 350
- 304 359

Hexagon Socket Screw

Electrical Ratings
1000
600
1000

Connection Data
35-150 mm ²
50-150 mm ²
25-50 mm ²
AWG 2-300 kcmil
29-31 mm
10-18 Nm
S8 (DIN 6911)

Type	Cat.No.	Qty.
UK 150/2	478 352	5
UK 150/3	478 353	5
UK 150/4	478 354	5

Type	Cat.No.	Qty.
AVK / EK6	304 370	20

Technical Data
8/3
1/B14
IP 10 / -
KOIP SW, SLF-P1 W

Package Quantity
4 pcs.

AVK 240

Width: 36 mm



115,00
MR 35 x 7,5

95,50

Cat No:

- 304 360
- 304 369

Hexagon Socket Screw

Electrical Ratings
1000
600
1000

Connection Data
50-240 mm ²
70-240 mm ²
35-50 mm ²
AWG 2/0-500 kcmil
33-35 mm
10-20 Nm
S8 (DIN 6911)

Type	Cat.No.	Qty.
UK 240/2	478 362	5
UK 240/3	478 363	5
UK 240/4	478 364	5


Type	Cat.No.	Qty.
AVK / EK6	304 370	20

Technical Data
8/3
1/A16
IP 10 / -
KOIP SW, SLF-P1 W

Package Quantity
4 pcs.

PB Series Terminals
Panel Mount
Terminals

AVK PB 50



Cat No:

- 304 440
- 304 449

Hexagon Socket Screw



Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min.-max.)
Screwdriver


Cross Connection

AVK / EK6

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
6 pcs.

AVK PB 70 RD



Cat No:

- 304 450
- 304 459

Hexagon Socket Screw

Voltage, V ~	Current, A	Cross-Section
1000	192	70 mm²

Voltage, V ~	Current, A	Cross-Section
	16-70 mm²	
	16-70 mm²	
	16-25 mm²	
	AWG 6-2/0	
	22-24 mm	
	6-12 Nm	
	S6 (DIN 6911)	


Type	Cat.No.	Qty.
UK 70/2	478 372	5
UK 70/3	478 373	5
UK 70/4	478 374	5

Type	Cat.No.	Qty.

Type	Cat.No.	Qty.
8/3		
1/A11		
IP 10 / -		
Marking Tags (Dekafix)		
KOIP SW, SLF-P1 W		

Package Quantity
6 pcs.

AVK PB 95



Cat No:

- 304 460
- 304 469

Hexagon Socket Screw

Voltage, V ~	Current, A	Cross-Section
1000	232	95 mm²

Voltage, V ~	Current, A	Cross-Section
	25-95 mm²	
	35-95 mm²	
	16-35 mm²	
	AWG 4-3/0	
	26-28 mm	
	10-15 Nm	
	S6 (DIN 6911)	


Type	Cat.No.	Qty.
UK 95/2	478 342	5
UK 95/3	478 343	5
UK 95/4	478 344	5

Type	Cat.No.	Qty.
AVK / EK6	304 370	20

Type	Cat.No.	Qty.
8/3		
1/B12		
IP 10 / -		
Marking Tags (Dekafix)		
KOIP SW, SLF-P1 W		

Package Quantity
6 pcs.

AVK PB 150



Cat No:

- 304 470
- 304 479

Hexagon Socket Screw

Voltage, V ~	Current, A	Cross-Section
1000	309	150 mm²

Voltage, V ~	Current, A	Cross-Section
	35-150 mm²	
	50-150 mm²	
	25-50 mm²	
	AWG 2/300 kcmil	
	29-31 mm	
	10-18 Nm	
	S8 (DIN 6911)	


Type	Cat.No.	Qty.
UK 150/2	478 352	5
UK 150/3	478 353	5
UK 150/4	478 354	5

Type	Cat.No.	Qty.
AVK / EK6	304 370	20

Type	Cat.No.	Qty.
8/3		
1/B14		
IP 10 / -		
Marking Tags (Dekafix)		
KOIP SW, SLF-P1 W		

Package Quantity
4 pcs.

AVK PB 240



Cat No:

- 304 480
- 304 489

Hexagon Socket Screw

Voltage, V ~	Current, A	Cross-Section
1000	415	240 mm²

Voltage, V ~	Current, A	Cross-Section
	50-240 mm²	
	70-240 mm²	
	35-50 mm²	
	AWG 2/0 500 kcmil	
	33-35 mm	
	10-20 Nm	
	S8 (DIN 6911)	

Type	Cat.No.	Qty.
UK 240/2	478 362	5
UK 240/3	478 363	5
UK 240/4	478 364	5

Type	Cat.No.	Qty.
AVK / EK6	304 370	20


Type	Cat.No.	Qty.
8/3		
1/A16		
IP 10 / -		
Marking Tags (Dekafix)		
KOIP SW, SLF-P1 W		

Package Quantity
6 pcs.

Bolt Connection
Terminals

AVK 95 B

Width: 40 mm



90,00

Cat No:

304 300

304 309

Electrical Ratings

CE (EN 60947-7-1)

UL

VDE (IEC 60947-7-1)

CSA

ATEX

Connection Data

Conductor cross section solid (min-max.)

Conductor cross section stranded (min.-max.)

AWG Conductor

Insulation Stripping Length

Torque (min-max.)

Hole Diameter

Bolt Diameter

Screwdriver

Cross Connection



Isolation Cover



Technical Data

Rated Impulse Voltage / Pollution severity

Insulation material group / Gauge pin code according to IEC 60947-1

Protection class / Protection conductor type


Marking Tags (Dekafix)

See pages 326-333 for a list of Dekafix

Package Quantity

AVK 150 B

Width: 48 mm



108,00

Cat No:

304 310

304 319

Electrical Ratings

1000

232

95 mm²

Connection Data

25-95 mm²

35-95 mm²

AWG 4-3/0

29 mm

25-30 Nm

10,5 mm

10 mm

17 (DIN 3110)

Cross Connection

Type	Cat.No.	Qty.
UKB 95/2	478 302	5
UKB 95/3	478 303	5
UKB 95/4	478 304	5

Isolation Cover

Type	Cat.No.	Qty.
KKB 95	466 100	4

Technical Data

8/3

1/NA

IP 10 / -


D_NS 10x10, DG 10/10

Package Quantity

4 pcs.

AVK 240 B

Width: 53 mm



122,00

Cat No:

304 320

304 329

Electrical Ratings

1000

415

240 mm²

Connection Data

70-240 mm²

70-240 mm²

AWG 2/0 - 500 kcmil

34 mm

30-35 Nm

17 mm

16 mm

24 (DIN 3110)

Cross Connection

Type	Cat.No.	Qty.
UKB 240/2	478 322	5
UKB 240/3	478 323	5
UKB 240/4	478 324	5

Isolation Cover

Type	Cat.No.	Qty.
KKB 240	466 120	4

Technical Data

8/3

1/NA

IP 10 / -

D_NS 10x10, DG 10/10


Package Quantity

4 pcs.



70

71





Screw Type Multilevel / Sensor Terminals




PUK Series Screw Connection Sensor Terminals are making sensor connections, which are often used in industry, more practical and esthetic. Provide individual cross connections for each layer, time saving in mounting process. Terminals can be used with NPN and PNP types of sensors. Special Marking solutions for each cross section can be provided by Plotter Labeling.



Fine strand wire up to 16 mm² cross-section can be used in panels with limited space. PIK series terminals allow you to make more connections in less space. Usage with Cross Connections gains features of distribution block. Special Marking solutions for each cross section can be provided by Plotter Labeling.



Double Deck Earth Terminals can be used in panels with limited space. Multipole connection on a single block and cross connection on both levels provide practical Earth connection. Special Marking solutions for each cross section can be provided by Plotter Labeling.



50% space saving


PIK Series Screw Connection Double-Deck Rail Terminals provide 2,5 - 4 - 10 mm² cross-section range. Double wiring density available without extension of mounting rails. Interconnection / shorting can be done at both layers. Special Marking solutions for each cross section can be provided by Plotter Labeling. The color of products can be selected from the color table.



PUK Series Screw Connection Multilevel terminals provides solutions for different users' needs. They are ideal for limited spaces with their compact designs. In panels which exist switch lines & lightening, provide phase-neutral-Earth connection in one terminal. PUK Series are ideal for usage in industries where motors are working a lot, with practical wiring. Cross connection can be used on each level. Special Marking solutions for each cross section can be provided by Plotter Labeling.

Screw Type
Double - Deck
Terminals

PIK 4 N



Cat No:

- 319 109
- 319 100
- 319 101

Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min.-max.)
Screwdriver

Ordering Data

Technical Data For Diode
Diode Voltage
Diode Current
Diod

End Plate



Small Partition


Cross Connection


Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
100 pcs.

PIK 4 RD



Cat No:

- 325 349
- 325 340
- 324 341

Voltage, V ~	Current, A	Cross-Section
500	32	4 mm²
300	30	AWG 26-10
400	29,5	

0,2-6 mm²
0,2-6 mm²
0,5-2,5 mm²
AWG 24-10
9-10 mm
0,5-0,8 Nm
IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP PIK 2,5-4 N	449 019	25


Type	Cat.No.	Qty.
AD 1	467 919	100

Type	Cat.No.	Qty.
UK 4/2	474 132	25
UK 4/3	474 133	20
UK 4/4	474 134	15
UK 4/10	474 139	5
UK 4/20	474 180	5

6/3
1/A4
IP 20 / -
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

100 pcs.

PIK 4 NK



Cat No:

- 319 129
- 319 120
- 319 121

Voltage, V ~	Current, A	Cross-Section
500	32	4 mm²
300	30	AWG 26-10
400	29,5	

0,2-6 mm²
0,2-6 mm²
0,5-2,5 mm²
AWG 24-10
9-10 mm
0,5-0,8 Nm
IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP PIK 2,5-4 N	449 019	25


Type	Cat.No.	Qty.
AD 1	467 919	100

Type	Cat.No.	Qty.
UK 4/2	474 132	25
UK 4/3	474 133	20
UK 4/4	474 134	15
UK 4/10	474 139	5
UK 4/20	474 180	5
Note: Only lower decks can be cross-connected		

6/3
1/A4
IP 20 / -
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

20 pcs.

PIK 4 RDK



Cat No:

- 325 359
- 325 350

Voltage, V ~	Current, A	Cross-Section
500	32	4 mm²

0,2-6 mm²
0,2-6 mm²
0,5-2,5 mm²
AWG 24-10
9-10 mm
0,5-0,8 Nm
IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP PIK 2,5-4 N	449 019	25


Type	Cat.No.	Qty.

Type	Cat.No.	Qty.
UK 4/2	474 132	25
UK 4/3	474 133	20
UK 4/4	474 134	15
UK 4/10	476 239	5
Note: Only lower decks can be cross-connected		

6/3
1/A4
IP 20 / -
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

100 pcs.

PIK 4 ND



Cat No:

- 319 219
- 319 210

Voltage, V ~	Current, A	Cross-Section
500	0,5	4 mm²
300	30	AWG 26-10
400	29,5	

0,2-6 mm²
0,2-6 mm²
0,5-2,5 mm²
AWG 24-10
9-10 mm
0,5-0,8 Nm
IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
PIK 4 ND A	319 219	20
PIK 4 ND B	319 229	20

1000 V
1 A
1 N 4007

Type	Cat.No.	Qty.
NPP PIK 2,5-4 N	449 019	25


Type	Cat.No.	Qty.
AD 1	467 919	100

Type	Cat.No.	Qty.
UK 4/2	474 132	25
UK 4/3	474 133	20
UK 4/4	474 134	15
UK 4/10	474 139	5
UK 4/20	474 180	5
Note: Only lower decks can be cross-connected		

6/3
1/A4
IP 20 / -
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

20 pcs.

PIK 4 NLD



Cat No:

- 319 319
- 319 310

Voltage, V ~	Current, A	Cross-Section
	24	4 mm²
	30	AWG 26-10
	29,5	

0,2-6 mm²
0,2-6 mm²
0,5-2,5 mm²
AWG 24-10
9-10 mm
0,5-0,8 Nm
IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
PIK 4 NLD (24AC)	319 319	20
PIK 4 NLD (24DC)	319 329	20
PIK 4 NLD (48AC)	319 419	20
PIK 4 NLD (48DC)	319 429	20
PIK 4 NLD (110AC)	319 619	20
PIK 4 NLD (110DC)	319 629	20
PIK 4 NLD (220AC)	319 719	20
PIK 4 NLD (220DC)	319 729	20

Type	Cat.No.	Qty.
NPP PIK 2,5-4 N	449 019	25

Type	Cat.No.	Qty.
AD 1	467 919	100


Type	Cat.No.	Qty.
UK 4/2	474 132	25
UK 4/3	474 133	20
UK 4/4	474 134	15
UK 4/10	474 139	5
UK 4/20	474 180	5
Note: Only lower decks can be cross-connected		

6/3
1/A4
IP 20 / -
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

20 pcs.

Screw Type
Multilevel
Terminals

PUK 3



Cat No:

- 324 109
- 324 100



Electrical Ratings
CE (EN 60947-7-1 - EN 60947-7-2)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min.-max.)
Screwdriver


End Plate

Cross Connection

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
20 pcs.

PUK 2 T



Cat No:

- 324 209
- 324 200

Voltage, V ~	Current, A	Cross-Section
440	24	2,5 mm²
300	24	AWG 24-12
400	24	

Voltage, V ~	Current, A	Cross-Section
440	24	2,5 mm²
300	24	AWG 24-12
400	24	


Type	Cat.No.	Qty.
NPP/PUK 2 T	450 149	10

Type	Cat.No.	Qty.
UK 2,5/2	480 132	25
UK 2,5/3	480 133	20
UK 2,5/4	480 134	15
UK 2,5/10	480 139	5
UK 2,5/35	480 140	5

6/3
1/A3
IP 20 / PE
DB 5

20 pcs.

PUK 3 T



Cat No:

- 324 309
- 324 300

Voltage, V ~	Current, A	Cross-Section
440	24	2,5 mm²
300	24	AWG 24-12
400	24	

Voltage, V ~	Current, A	Cross-Section
440	24	2,5 mm²
300	24	AWG 24-12
400	24	

Type	Cat.No.	Qty.
NPP/PUK 3 T	450 159	10


Type	Cat.No.	Qty.
UK 2,5/2	480 132	25
UK 2,5/3	480 133	20
UK 2,5/4	480 134	15
UK 2,5/10	480 139	5
Note: Only upper decks can be cross-connected		

6/3
1/A3
IP 20 / PE
DB 5

20 pcs.

Screw Type Sensor Terminals

PUK 3 S



Cat No:

	324 409
	324 400

Voltage, V ~	Current, A	Cross-Section
500	24	2,5 mm ²
300	24	AWG 24-12

0,2-4 mm ²
0,2-4 mm ²
0,5-1,5 mm ²
AWG 24-12
7-8 mm
0,4-0,6 Nm
IKT 3 (0,6x3,5)


Type	Cat.No.	Qty.
NPP/PUK 3 S	450 169	10

Type	Cat.No.	Qty.
UK 2,5/2	480 132	25
UK 2,5/3	480 133	20
UK 2,5/4	480 134	15
UK 2,5/10	480 139	5
UK 2,5/35	480 140	5

6/3
1/A3
IP 20 / -
DB 5

	20 pcs.

PUK 3 SLD (NPN)



Cat No:

324 419
324 410

Voltage, V ~	Current, A	Cross-Section
24	24	2,5 mm ²
300	24	AWG 24-12

	0,2-4 mm ²
	0,2-4 mm ²
	0,5-1,5 mm ²
	AWG 24-12
	7-8 mm
	0,4-0,6 Nm
	IKT 3 (0,6x3,5)


Type	Cat.No.	Qty.
NPP/PUK 3 S	450 169	10

Type	Cat.No.	Qty.
UK 2,5/2	480 132	25
UK 2,5/3	480 133	20
UK 2,5/4	480 134	15
UK 2,5/10	480 139	5
UK 2,5/35	480 140	5

6/3
1/A3
IP 20 / -
DB 5

	20 pcs.

PUK 3 SLD (PNP)



Cat No:

324 429
324 420

Voltage, V ~	Current, A	Cross-Section
24	24	2,5 mm ²
300	24	AWG 24-12

0,2-4 mm ²
0,2-4 mm ²
0,5-1,5 mm ²
AWG 24-12
7-8 mm
0,4-0,6 Nm
IKT 3 (0,6x3,5)


Type	Cat.No.	Qty.
NPP/PUK 3 S	450 169	10

Type	Cat.No.	Qty.
UK 2,5/2	480 132	25
UK 2,5/3	480 133	20
UK 2,5/4	480 134	15
UK 2,5/10	480 139	5
UK 2,5/35	480 140	5



6/3
1/A3
IP 20 / PE
DB 5

20 pcs.


Screw Connection Disconnect / Test and Disconnect / Fuse Terminals







WGO Y Series Test and Disconnect Terminals provide safe connection with spring force under the contact of the terminal block. Practical accessories like sliding cross connection system, isolated Test Sockets, Test Plugs and Comb Connectors are available. Special Marking solutions for each cross section can be provided by Plotter labeling.




Screw Connection Fuse Rail Terminals Terminals can be used with glass fuse between 1A...10A. The fuse inside of the terminal is easily mounted and dismantled, and is an ideal solution when there is a necessity to change it even when the power is on in the system. Marking solutions can be provided by Plotter Labeling.



WGO Series Test and Disconnect Terminals are used to perform required tests without switching off the power in the system. These products are installed at the secondary side of current transformers, and thus, electrical ratings can be observed by testing equipment connected to the product. Practical accessories like sliding cross connection system, isolated Test Sockets, Test Plugs and Comb Connectors are available. Special Marking solutions for each cross section can be provided by Plotter labeling.




WGO PB series Ring and Fork Type Plug inTerminals provide practical safe connection. For WGO PB series, cable assembly is done with insulated ring type terminals and the terminal blocks have two test sockets. Practical accessories like sliding cross connection system, isolated Test Sockets, Test Plugs and Comb Connectors are available. Special Marking solutions for each cross section can be provided by Plotter labeling.



Knife Disconnect System, enables Screw Connection Disconnect Terminals to switch energy in the system. Marking solutions can be provided by Plotter Labeling.

Disconnect
Terminals



Cat No:				Cat No:				Cat No:				Cat No:			
360 119 360 110				304 419 304 410				324 949 324 940				324 939 324 930			
Electrical Ratings				Voltage, V ~Current, ACross-Section								Voltage, V ~Current, ACross-Section			
CE (EN 60947-7-1)				5006,36 mm²								400162,5 mm²			
UL				3006,3AWG 26-8											
VDE (IEC 60947-7-1)															
CSA															
ATEX															
Connection Data															
Conductor cross section solid (min.-max.)				0,2-10 mm²				0,2-4 mm²				0,2-4 mm²			
Conductor cross section stranded (min.-max.)				0,2-10 mm²				0,2-4 mm²				0,2-4 mm²			
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)				0,5-4 mm²				0,5-1,5 mm²				0,5-1,5 mm²			
AWG Conductor				AWG 24-8				AWG 24-12				AWG 24-12			
Insulation Stripping Length (min.-max.)				10-12 mm				9-10 mm				9-10 mm			
Torque (min.-max.)				0,8-1,2 Nm				0,4-0,6 Nm				0,4-0,6 Nm			
Screwdriver				IKT 3 (0,6x3,5)				IKT 3 (0,6x3,5)				IKT 3 (0,6x3,5)			
End Plate				TypeCat.No.Qty.				TypeCat.No.Qty.				TypeCat.No.Qty.			
				NPP/ASK 2450 04925				NPP/AVK 2,5A450 33025				NPP/AVK 2,5 CC444 13925			
Push-in Cross Connection								TypeCat.No.Qty.							
								UK 2,5/2476 22225							
								UK 2,5/3476 22320							
								UK 2,5/4476 22415							
								UK 2,5/10476 2295							
Technical Data															
Rated Impulse Voltage / Pollution severity				6/3				6/3				6/3			
Insulation material group / Gauge pin code according to IEC 60947-1				1/B5				1/A3				1/A3			
Protection class / Protection conductor type				IP 20 / -				IP 20 / -				IP 20 / -			
Marking Tags (Dekafix)															
See pages 326-333 for a list of Dekafix				DB 5				D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T SLF-P1 W				D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T			
Package Quantity															
				25 pcs.				50 pcs.				80 pcs.			

Disconnect
Terminals

AVK 4 A

Width: 6 mm

Cat No:

304 380

304 389

Electrical Ratings	Voltage, V ~	Current, A	Cross-Section
CE (EN 60947-7-1)	500	20	4 mm²
UL	300	16	AWG 26-10
VDE (IEC 60947-7-1)			
CSA			
ATEX			

Connection Data

Conductor cross section solid (min.-max.)	0,2-6 mm²
Conductor cross section stranded (min.-max.)	0,2-6 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-2,5 mm²
AWG Conductor	AWG 24-10
Insulation Stripping Length (min.-max.)	9-10 mm
Torque (min.-max.)	0,5-0,8 Nm
Screwdriver	IKT 3 (0,6x3,5)

End Plate

Type	Cat.No.	Qty.
NPP/AVK 4 R-A	450 330	25

Technical Data For Diode

Diode Voltage	
Diode Current	
Diode	

Push-in Cross Connection

Type	Cat.No.	Qty.
UK 4/2	476 232	25
UK 4/3	476 233	20
UK 4/4	476 234	15
UK 4/10	476 239	5

Technical Data

Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/A4
Protection class / Protection conductor type	IP 20 / -

Marking Tags (Dekafix)

See pages 326-333 for a list of Dekafix

Package Quantity

50 pcs.

AVK 4 CEA

Width: 6 mm

Cat No:

325 239

325 230

Voltage, V ~	Current, A	Cross-Section
500	20	4 mm²

Connection Data

Conductor cross section solid (min.-max.)	0,2-6 mm²
Conductor cross section stranded (min.-max.)	0,2-6 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-2,5 mm²
AWG Conductor	AWG 24-10
Insulation Stripping Length (min.-max.)	9-10 mm
Torque (min.-max.)	0,5-0,8 Nm
Screwdriver	IKT 3 (0,6x3,5)

End Plate

Type	Cat.No.	Qty.
NPP/AVK 4CEA	450 349	25

Technical Data For Diode

Diode Voltage	
Diode Current	
Diode	

Push-in Cross Connection

Type	Cat.No.	Qty.
UK 4/2	476 232	25
UK 4/3	476 233	20
UK 4/4	476 234	15
UK 4/10	476 239	5

Technical Data

Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/A4
Protection class / Protection conductor type	IP 20 / -

Marking Tags (Dekafix)

D_NS 6x10, DB 10/6, DG 10/6, DG 10,6T

Package Quantity

50 pcs.

AVK 4 CCA

Width: 6 mm

Cat No:

325 219

325 210

Voltage, V ~	Current, A	Cross-Section
500	20	4 mm²

Connection Data

Conductor cross section solid (min.-max.)	0,2-6 mm²
Conductor cross section stranded (min.-max.)	0,2-6 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-2,5 mm²
AWG Conductor	AWG 24-10
Insulation Stripping Length (min.-max.)	9-10 mm
Torque (min.-max.)	0,5-0,8 Nm
Screwdriver	IKT 3 (0,6x3,5)

End Plate

Type	Cat.No.	Qty.
NPP/AVK 4CCA	450 349	25

Technical Data For Diode

Diode Voltage	
Diode Current	
Diode	

Push-in Cross Connection

Type	Cat.No.	Qty.
UK 4/2	476 232	25
UK 4/3	476 233	20
UK 4/4	476 234	15
UK 4/10	476 239	5

Technical Data

Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/A4
Protection class / Protection conductor type	IP 20 / -

Marking Tags (Dekafix)

D_NS 6x10, DB 10/6, DG 10/6, DG 10,6T

Package Quantity

50 pcs.

AVK AS

Width: 5,80 mm

Cat No:

498 959

498 950

Voltage, V ~	Current, A	Cross-Section
400	16	2,5 mm²

Connection Data

Conductor cross section solid (min.-max.)	0,2-4 mm²
Conductor cross section stranded (min.-max.)	0,2-4 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-1,5 mm²
AWG Conductor	AWG 24-12
Insulation Stripping Length (min.-max.)	6-7 mm
Torque (min.-max.)	0,4-0,6 Nm
Screwdriver	IKT 3 (0,6x3,5)

End Plate

Type	Cat.No.	Qty.

Technical Data For Diode

Diode Voltage	
Diode Current	
Diode	

Push-in Cross Connection

Type	Cat.No.	Qty.

Technical Data

Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/A3
Protection class / Protection conductor type	IP 20 / PE

Marking Tags (Dekafix)

DB 5, DB 10/6, DG 10/6, DG 10/6T

Package Quantity

50 pcs.

AVK ASD

Width: 5,80 mm

Cat No:

499 059

499 050

Voltage, V ~	Current, A	Cross-Section
400	0,5	2,5 mm²

Connection Data

Conductor cross section solid (min.-max.)	0,2-4 mm²
Conductor cross section stranded (min.-max.)	0,2-4 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-1,5 mm²
AWG Conductor	AWG 24-12
Insulation Stripping Length (min.-max.)	6-7 mm
Torque (min.-max.)	0,4-0,6 Nm
Screwdriver	IKT 3 (0,6x3,5)

End Plate

Type	Cat.No.	Qty.

Technical Data For Diode

Diode Voltage	
Diode Current	
Diode	

Push-in Cross Connection

Type	Cat.No.	Qty.

Technical Data

Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/A3
Protection class / Protection conductor type	IP 20 / PE

Marking Tags (Dekafix)

DB 5, DB 10/6, DG 10/6, DG 10/6T

Package Quantity

50 pcs.

NOTE: AVK ASD is just used with AVK 4A, AVK 4CEA and AVK 4CCA terminal blocks.

NOTE: AVK ASD is just used with AVK 4A, AVK 4CEA and AVK 4CCA terminal blocks.

88

89


WGO Series

Test / Disconnect

Terminals

WGO 1

Width: 8 mm



66,25

Cat No:

370 590
370 500



Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min.-max.)
Screwdriver

Ordering Data
Without Socket - Beige / Grey
One Socket - Beige / Grey
Double Socket - Beige / Grey
One Test Socket - Beige / Grey
Double Test Socket - Beige / Grey

End Plate


Cross Connection


Test Plug
 suitable for test socket types


Comb Connector


Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
60 pcs.

WGL 1

Width: 8 mm



66,25

Cat No:

375 790
375 700

Electrical Ratings
400
300
250

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min.-max.)
Screwdriver

Ordering Data
Without Socket - Beige / Grey
One Socket - Beige / Grey
Double Socket - Beige / Grey
One Test Socket - Beige / Grey
Double Test Socket - Beige / Grey

End Plate


Cross Connection


Test Plug
 suitable for test socket types


Comb Connector


Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
60 pcs.

WGO 2 N

Width: 10 mm



74,60

Cat No:

375 890
375 800

Electrical Ratings
400
300
250

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min.-max.)
Screwdriver

Ordering Data
Without Socket - Beige / Grey
One Socket - Beige / Grey
Double Socket - Beige / Grey
One Test Socket - Beige / Grey
Double Test Socket - Beige / Grey

End Plate


Cross Connection


Test Plug
 suitable for test socket types


Comb Connector


Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
50 pcs.

WGO 3

Width: 8 mm



70,00

Cat No:

375 692
375 602

Electrical Ratings
400
300
250

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min.-max.)
Screwdriver

Ordering Data
Without Socket - Beige / Grey
One Socket - Beige / Grey
Double Socket - Beige / Grey
One Test Socket - Beige / Grey
Double Test Socket - Beige / Grey

End Plate


Cross Connection


Test Plug
 suitable for test socket types



Comb Connector


Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix


Package Quantity
50 pcs.

Socket Selections


Test Socket Socket




Without Socket




Single Socket



Double Socket



Single Test Socket



Double Test Socket


WGO Series

Test / Disconnect

Terminals

WGO 2 IR

Width: 10 mm




64,25

Cat No:

- 375 909
- 375 900

WGO 4

Width: 8 mm




88,30

Cat No:

- 376 090
- 376 000

WGO 5

Width: 8 mm




95,35

Cat No:

- 376 190
- 376 100

WGO D5

Width: 8 mm



95,35

Cat No:

- 376 290
- 376 200



Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min.-max.)
Screwdriver

Ordering Data
Without Socket - Beige / Grey
One Socket - Beige / Grey
Double Socket - Beige / Grey
One Test Socket - Beige / Grey
Double Test Socket - Beige / Grey

End Plate
Grey
Beige

Cross Connection
IZUK 10W/2
IZUK 10W/3
IZUK 10W/4
IZUK 10W/6
IZUK 10W/10

Test Plug
TF (Q4)

Comb Connector
TKO 10/2
TKO 10/3
TKO 10/4
TKO 10/10

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix
Package Quantity

Voltage, V ~	Current, A	Cross-Section
500	57	10 mm²
400	50	

Type	Cat.No.	Qty.
WGO 2 IR	375 900 - 909	50

Type	Cat.No.	Qty.
NPP/WGO 2 IR	450 249	25

Type	Cat.No.	Qty.
IZUK 10W/2	476 502	10
IZUK 10W/3	476 503	10
IZUK 10W/4	476 504	10
IZUK 10W/6	476 506	10
IZUK 10W/10	476 509	5

Type	Cat.No.	Qty.
TF (Q4)	493 050	10

Type	Cat.No.	Qty.
TKO 10/2	476 292	25
TKO 10/3	476 293	20
TKO 10/4	476 294	15
TKO 10/10	476 299	5

Type	Cat.No.	Qty.
TKO 10/2	476 292	25
TKO 10/3	476 293	20
TKO 10/4	476 294	15
TKO 10/10	476 299	5

Type	Cat.No.	Qty.
6/3		
1/B6		
IP 20 / -		
D_NS 10x10, DG 10/10, SLF-P1 W		
50 pcs.		

Voltage, V ~	Current, A	Cross-Section
1000	41	6 mm²

Type	Cat.No.	Qty.
WGO 4 (Grey)	376 091	50

Type	Cat.No.	Qty.
WGO 4 (Grey)	376 091	50

Type	Cat.No.	Qty.
IZUK 6/2	476 302	10
IZUK 6/3	476 303	10
IZUK 6/4	476 304	10
IZUK 6/6	476 306	10
IZUK 6/10	476 309	5

Type	Cat.No.	Qty.
TF (Ø4)	493 050	10

Type	Cat.No.	Qty.
TF (Ø4)	493 050	10

Type	Cat.No.	Qty.
UK 6/2	476 242	25
UK 6/3	476 243	20
UK 6/4	476 244	15
UK 6/10	476 249	5

Type	Cat.No.	Qty.
6/3		
1/B5		
IP 20 / -		
D_NS 8x10, DG 10/8, SLF-P1 W		
50 pcs.		

Voltage, V ~	Current, A	Cross-Section
500	41	6 mm²

Type	Cat.No.	Qty.
NPP/WGO 5	450 359	25
APP/WGO 5	463 219	25
Cover WGO 5	498 260	1 meter

Type	Cat.No.	Qty.
UK 6/2	476 242	25
UK 6/3	476 243	20
UK 6/4	476 244	15
UK 6/10	476 249	5

Type	Cat.No.	Qty.
TF (Ø4)	493 050	10

Type	Cat.No.	Qty.
TF (Ø4)	493 050	10

Type	Cat.No.	Qty.
TF (Ø4)	493 050	10

Type	Cat.No.	Qty.
UK 6/2	476 242	25
UK 6/3	476 243	20
UK 6/4	476 244	15
UK 6/10	476 249	5

Type	Cat.No.	Qty.
6/3		
1/A5		
IP 20 / -		
D_NS 8x10, DG 10/8, SLF-P1 W		
40 pcs.		

Voltage, V ~	Current, A	Cross-Section
500	41	6 mm²

Type	Cat.No.	Qty.
NPP/WGO 5	450 359	25
APP/WGO 5	463 219	25
Cover WGO 5	498 260	1 meter

Type	Cat.No.	Qty.
UK 6/2	476 242	25
UK 6/3	476 243	20
UK 6/4	476 244	15
UK 6/10	476 249	5

Type	Cat.No.	Qty.
TF (Ø4)	493 050	10

Type	Cat.No.	Qty.
TF (Ø4)	493 050	10

Type	Cat.No.	Qty.
TF (Ø4)	493 050	10

Type	Cat.No.	Qty.
UK 6/2	476 242	25
UK 6/3	476 243	20
UK 6/4	476 244	15
UK 6/10	476 249	5

Type	Cat.No.	Qty.
6/3		
1/A5		
IP 20 / -		
D_NS 8x10, DG 10/8, SLF-P1 W		
40 pcs.		

Voltage, V ~	Current, A	Cross-Section
500	41	6 mm²

Type	Cat.No.	Qty.
NPP/WGO 5	450 359	25
APP/WGO 5	463 219	25
Cover WGO 5	498 260	1 meter

Type	Cat.No.	Qty.
UK 6/2	476 242	25
UK 6/3	476 243	20
UK 6/4	476 244	15
UK 6/10	476 249	5

Type	Cat.No.	Qty.
TF (Ø4)	493 050	10


Type	Cat.No.	Qty.
TF (Ø4)	493 050	10

Type	Cat.No.	Qty.
TF (Ø4)	493 050	10

Type	Cat.No.	Qty.
UK 6/2	476 242	25
UK 6/3	476 243	20
UK 6/4	476 244	15
UK 6/10	476 249	5

Type	Cat.No.	Qty.
6/3		
1/A5		
IP 20 / -		
D_NS 8x10 SLF-P1 W, DG 10/8		
40 pcs.		

APP/WGO 5 - Cat No.: 463 219



Protection Cover for WGO 5 - Cat No.: 498 260

WGO Y Series
Test / Disconnect
Terminals

WGO Y 6

Width: 8 mm

61,10
MR 35 x 7,5

81,20

Cat No:

375 919

375 910

WGO YD 6

Width: 8 mm

61,10
MR 35 x 7,5

81,20

Cat No:

375 929

375 920

Electrical Ratings	Voltage, V ~	Current, A	Cross-Section
CE (EN 60947-7-1)	1000	41	6 mm²
UL			
VDE (IEC 60947-7-1)			
CSA			
ATEX			

Connection Data			
Conductor cross section solid (min.-max.)	0,2-10 mm²		
Conductor cross section stranded (min.-max.)	0,2-10 mm²		
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-4 mm²		
AWG Conductor	AWG 24-8		
Insulation Stripping Length (min.-max.)	10-12 mm		
Torque (min.-max.)	0,8-1,2 Nm		
Screwdriver	IKT 4 (0,8x4,0)		

End Plate			
	Grey		
	Beige		
	Type	Cat.No.	Qty.
	NPP/WGO Y 6	450 279	25
	NPP/WGO Y 6	450 270	25

Cross Connection			
	Type	Cat.No.	Qty.
	IZUK 6/2	476 302	10
	IZUK 6/3	476 303	10
	IZUK 6/4	476 304	10
	IZUK 6/6	476 306	10
	IZUK 6/10	476 309	5
	WGO UAA	498 300	1

Test Plug			
	Type	Cat.No.	Qty.
	TF (Q4)	493 050	10

Technical Data		
Rated Impulse Voltage / Pollution severity	6/3	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/B5	1/B5
Protection class / Protection conductor type	IP 20 / -	IP 20 / -
Marking Tags (Dekafix)		
See pages 326-333 for a list of Dekafix	D_NS 8x10, DG 10/8, SLF-P1 W	D_NS 8x10, DG 10/8, SLF-P1 W
Package Quantity		
	48 pcs.	48 pcs.

WGO PB Series
Test / Disconnect
Terminals

WGO PB 6/NM

Width: 11 mm

54,00
MR 35 x 7,5

86,60

Cat No:

308 069

308 060

WGO PBD 6/NM

Width: 11 mm

54,00
MR 35 x 7,5

86,60

Cat No:

308 079

308 070

Electrical Ratings	Voltage, V ~	Current, A	Cross-Section
CE (EN 60947-7-1)	1000	41	6 mm²
UL	600	45	AWG 22-8
VDE (IEC 60947-7-1)			
CSA	600	45	AWG 22-8
ATEX			

Connection Data			
Conductor cross section solid (min.-max.)	0,5-6 mm²		
Conductor cross section stranded (min.-max.)	0,5-6 mm²		
AWG Conductor	AWG 22-8		
Torque	0,8-1,2 Nm		
Hole Diameter	4,2 mm		
Bolt Diameter	4 mm		
Screwdriver	IKT 5 (1,0x5,5)		

End Plate			
	Type	Cat.No.	Qty.
	NPP/WGO PB 6	451 009	25
	APP/WGO PB 6	464 019	25

Comb Connector/Ring Type			
	Type	Cat.No.	Qty.
	TKO PB 6/2	479 002	25
	TKO PB 6/3	479 003	20
	TKO PB 6/4	479 004	15
	TKO PB 6/7	479 007	5
	TKO PB 6/10	479 009	5



Test Plug			

Technical Data		
Rated Impulse Voltage / Pollution severity	6/3	8/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/NA	1/NA
Protection class / Protection conductor type	IP 20 / -	IP 20 / -
Marking Tags (Dekafix)		
See pages 326-333 for a list of Dekafix	D_NS 8x10, DG 10/8, SLF-P1 W	D_NS 8x10, DG 10/8, SLF-P1 W
	25 pcs.	25 pcs.




WGO 6 Test and Disconnect Terminals

Complying EN 45545-2 European railway standard for fire safety classes R22-R23-R24-R26 for HL 1 – HL 2 –HL 3




- 6mm² Closed Type Test and Disconnect Terminal Block, no need for an extra end plate usage.
- Insulation Material V0 PA complied with UL 94
- Suitable for 4mm diameter test plug with preformed self socket. No need for a socket and test socket model selection, test plug can be inserted directly.
- Test Socket color coding is possible thanks to WGO 6KP coding plastics.
- WGO 6PK ensures the Sliding Disconnect Bridge safety with exact positioning. When the circuit is disconnected, you can use WGO 6PK as a safety isolation to prevent unexpected tripping and arcing.
- Suitable for 11.2mm marking strip.
- Din rail mounted ATCS 6 cross connection holder prevents possible accessory loss for SCS 6 and CS 6, when they are not in use.

CS type (2-3-4-5-10 poles) accessories are push-in cross connectors, SCS type (2-3-4 poles) accessories are longer push-in short-circuit connectors. In case there is no accessory holder (ATCS 6) usage, SCS type connectors can be mounted upside down to same connection holes to prevent any accessory loss.



WGO 6 Series Test / Disconnect Terminals



Cat No:

- 309 609
- 309 600



Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
AWG Conductor
Torque
Hole Diameter
Bolt Diameter
Screwdriver

Cross Connection

Plastic Lock
Grey
Orange


Coding Plastic
Orange
Blue
Green
Yellow
Red
Black

Test Plug

Cross Connection Holder

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
50 pcs.



Cat No:

- 309 619
- 309 610

Electrical Ratings
1000
600

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
AWG Conductor
Torque
Hole Diameter
Bolt Diameter
Screwdriver

Cross Connection

Plastic Lock
Grey
Orange

Coding Plastic
Orange
Blue
Green
Yellow
Red
Black

Test Plug


Cross Connection Holder

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
50 pcs.

Distribution
Terminals


AYK 10/16



Cat No:

395 100


AYK 10/16



Cat No:

395 200

AYK 10/16-2,3,4,5



Cat No:

395 220



Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min.-max.)
Screwdriver

Ordering Data

End Plate

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
20 pcs.

Voltage, V ~	Current, A	Cross-Section
750	76	16 mm²

2,5-0,5 mm²
25-16 mm²
1,5-0,5/10-6 mm²
AWG 14/20-4/6
14/8-16/10 mm
1,2/1,2-2,0/1,8 Nm
IKT 4 (0,8x4,0)

Type	Cat.No.	Qty.
NPP/AYK	450 090	10

8/3
1/B6
IP 20 / -
D_NS 5x6, DB 5, DG 6/5,

Voltage, V ~	Current, A	Cross-Section
750	76	16 mm²

2,5-0,5 mm²
25-16 mm²
1,5-0,5/10-6 mm²
AWG 14/20-4/6
14/8-16/10 mm
1,2/1,2-2,0/1,8 Nm
IKT 4 (0,8x4,0)

Type	Cat.No.	Qty.
NPP/AYK	450 090	10

8/3
1/B6
IP 20 / -
D_NS 5x6, DB 5, DG 6/5,

20 pcs.

--

Voltage, V ~	Current, A	Cross-Section
750	76	16 mm²

2,5-0,5 mm²
25-16 mm²
1,5-0,5/10-6 mm²
AWG 14/20-4/6
14/8-16/10 mm
1,2/1,2-2,0/1,8 Nm
IKT 4 (0,8x4,0)

Type	Cat.No.	Qty.
AYK 10/16 - 2	395 220	20
AYK 10/16 - 3	395 230	20
AYK 10/16 - 4	395 240	20
AYK 10/16 - 5	395 250	20

Type	Cat.No.	Qty.
NPP/AYK	450 090	10


8/3
1/B6
IP 20 / -
D_NS 5x6, DB 5, DG 6/5,

20 pcs.

Screw Type Fuse Terminals

ASK 3 F

Width: 6,2 mm



Cat No:

354 109

354 100

Electrical Ratings

CE (EN 60947-7-3)	500	10	4 mm²
UL	600	10	AWG 26-10
VDE (IEC 60947-7-1)			
CSA			
ATEX			

Connection Data

Conductor cross section solid (min.-max.)	0,2-6 mm²
Conductor cross section stranded (min.-max.)	0,2-6 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-2,5 mm²
AWG Conductor	AWG 24-10
Insulation Stripping Length (min.-max.)	9-10 mm
Torque (min.-max.)	0,5-0,8 Nm
Screwdriver	IKT 3 (0,6x3,5)

Ordering Data

End Plate



Type	Cat.No.	Qty.
NPP/ASK 3	450 059	10

Push-in Cross Connection



Type	Cat.No.	Qty.
UK 4/2	476 232	25
UK 4/3	476 233	20
UK 4/4	476 234	15

Technical Data


Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/A4
Protection class / Protection conductor type	IP 20 / -
Fuse / Fuse Type	G/5x20-5x25
Marking Tags (Dekafix)	
See pages 326-333 for a list of Dekafix	DB 5, DB 10/6

Package Quantity

30 pcs.

ASK 3 FLD

Width: 6,2 mm



Cat No:

354 219

354 210

Electrical Ratings

		10	4 mm²
		10	AWG 26-10

Connection Data

Conductor cross section solid (min.-max.)	0,2-6 mm²
Conductor cross section stranded (min.-max.)	0,2-6 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-2,5 mm²
AWG Conductor	AWG 24-10
Insulation Stripping Length (min.-max.)	9-10 mm
Torque (min.-max.)	0,5-0,8 Nm
Screwdriver	IKT 3 (0,6x3,5)

Ordering Data

End Plate

Type	Cat.No.	Qty.
NPP/ASK 3	450 059	10

Push-in Cross Connection

Type	Cat.No.	Qty.
UK 4/2	476 232	25
UK 4/3	476 233	20
UK 4/4	476 234	15

Technical Data


Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/A4
Protection class / Protection conductor type	IP 20 / -
Fuse / Fuse Type	G/5x20-5x25
Marking Tags (Dekafix)	
See pages 326-333 for a list of Dekafix	DB 5, DB 10/6

Package Quantity

30 pcs.

AVK 4 FS

Width: 8 mm



Cat No:

353 309

353 300

Electrical Ratings

	500	32	4 mm²
	300	6,3/30	AWG 26-10

Connection Data

Conductor cross section solid (min.-max.)	0,2-6 mm²
Conductor cross section stranded (min.-max.)	0,2-6 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-2,5 mm²
AWG Conductor	AWG 24-10
Insulation Stripping Length (min.-max.)	8-9 mm
Torque (min.-max.)	0,5-1,0 Nm
Screwdriver	IKT 3 (0,6x3,5)

Ordering Data

End Plate

Type	Cat.No.	Qty.
NPP/AVK 4 FS	450 209	10

Push-in Cross Connection

Type	Cat.No.	Qty.
UK 6/2	476 242	25
UK 6/3	476 243	20
UK 6/4	476 244	15
UK 6/10	476 249	5

Technical Data


Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/A4
Protection class / Protection conductor type	IP 20 / -
Fuse / Fuse Type	G/5x20-5x25
Marking Tags (Dekafix)	
See pages 326-333 for a list of Dekafix	D_NS 5x6, DB 5, DG 6/5

Package Quantity

50 pcs.

AVK 4 FSLD

Width: 8 mm



Cat No:

353 329

353 320

Electrical Ratings

	24	32	4 mm²
	300	6,3/30	AWG 26-10

Connection Data

Conductor cross section solid (min.-max.)	0,2-6 mm²
Conductor cross section stranded (min.-max.)	0,2-6 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)	0,5-2,5 mm²
AWG Conductor	AWG 24-10
Insulation Stripping Length (min.-max.)	8-9 mm
Torque (min.-max.)	0,5-1,0 Nm
Screwdriver	IKT 3 (0,6x3,5)

Ordering Data

End Plate

Type	Cat.No.	Qty.
NPP/AVK 4FS	450 209	10

Push-in Cross Connection

Type	Cat.No.	Qty.
UK 6/2	476 242	25
UK 6/3	476 243	20
UK 6/4	476 244	15
UK 6/10	476 249	5

Technical Data

Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/A4
Protection class / Protection conductor type	IP 20 / -
Fuse / Fuse Type	G/5x20-5x25
Marking Tags (Dekafix)	
See pages 326-333 for a list of Dekafix	D-NS 5x10, DG 6/5, DB 5

Package Quantity

50 pcs.



104

105

Screw Type Fuse Terminals

ASK 5

Width: 8 mm



Cat No:

- 353 409
- 353 400

Electrical Ratings	Voltage, V ~	Current, A	Cross-Section
CE (EN 60947-7-3)	500	10	4 mm²
UL	300	10	AWG 26-10
VDE (IEC 60947-7-1)			
CSA			
ATEX			

Connection Data	
Conductor cross section solid (min-max.)	0,2-6 mm²
Conductor cross section stranded (min.-max.)	0,2-6 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)	0,5-2,5 mm²
AWG Conductor	AWG 24-10
Insulation Stripping Length (min.-max.)	8-9 mm
Torque (min-max.)	0,5-0,8 Nm
Screwdriver	IKT 3 (0,6x3,5)

Ordering Data			


Push-in Cross Connection			
			

Technical Data	
Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/A4
Protection class / Protection conductor type	IP 20 / - G/5x20-5x25
Fuse / Fuse Type	
Marking Tags (Dekafix)	
See pages 326-333 for a list of Dekafix	D_NS 8x10, DG 10/8

Package Quantity	50 pcs.
------------------	---------

ASK 5 LD

Width: 8 mm



Cat No:

- 353 429
- 353 420

Electrical Ratings	Voltage, V ~	Current, A	Cross-Section
		10	4 mm²
		10	AWG 26-10

Connection Data	
Conductor cross section solid (min-max.)	0,2-6 mm²
Conductor cross section stranded (min.-max.)	0,2-6 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)	0,5-2,5 mm²
AWG Conductor	AWG 24-10
Insulation Stripping Length (min.-max.)	8-9 mm
Torque (min-max.)	0,5-0,8 Nm
Screwdriver	IKT 3 (0,6x3,5)

Ordering Data			

Push-in Cross Connection			



Technical Data	
Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/A4
Protection class / Protection conductor type	IP 20 / - G/5x20-5x25
Fuse / Fuse Type	
Marking Tags (Dekafix)	
See pages 326-333 for a list of Dekafix	D_NS 8x10, DG 10/8

Package Quantity	50 pcs.
------------------	---------

Fuse Terminals for American Standards

ASK 4 S

Width: 10 mm



Cat No:

- 351 129
- 351 120

Electrical Ratings	Voltage, V ~	Current, A	Cross-Section
CE (EN 60947-7-3)	750	6,3	6 mm²
UL	600	6,3	AWG 22-8
VDE (IEC 60947-7-1)			
CSA			
ATEX			

Connection Data	
Conductor cross section solid (min-max.)	0,34-10 mm²
Conductor cross section stranded (min.-max.)	0,34-10 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)	0,5-4 mm²
AWG Conductor	AWG 22-8
Insulation Stripping Length (min.-max.)	9-10 mm
Torque	0,5-0,8 Nm
Screwdriver	IKT 3 (0,6x3,5)


Ordering Data			

Technical Data	
Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/B5
Protection class / Protection conductor type	IP 20 / - 63,5x31,75
Fuse / Fuse Type	
Marking Tags (Dekafix)	
See pages 326-333 for a list of Dekafix	D_NS 8x10, DG 10/8

Package Quantity	20 pcs.
------------------	---------

ASK 4 LD

Width: 10 mm



Cat No:

- 351 719
- 351 710

Electrical Ratings	Voltage, V ~	Current, A	Cross-Section
		6,3	6 mm²
		6,3	AWG 22-8

Connection Data	
Conductor cross section solid (min-max.)	0,34-10 mm²
Conductor cross section stranded (min.-max.)	0,34-10 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)	0,5-4 mm²
AWG Conductor	AWG 22-8
Insulation Stripping Length (min.-max.)	9-10 mm
Torque	0,5-0,8 Nm
Screwdriver	IKT 3 (0,6x3,5)


Ordering Data			

Technical Data	
Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/B5
Protection class / Protection conductor type	IP 20 / - 63,5x31,75
Fuse / Fuse Type	
Marking Tags (Dekafix)	
See pages 326-333 for a list of Dekafix	D_NS 8x10, DG 10/8

Package Quantity	20 pcs.
------------------	---------

Double Level
Electronic Terminals


WG - EKi



From reverse current protection to lamp test circuit, you can select among 20 ready to use circuits of WG EKI-N, or choose the empty one and apply your own circuit. There are many choices with different number of contacts and housing type suitable for your needs. Spring clamp connections speed up the cable installations whereas plug-in cross connectors provides easy and safe connection. New WG EKI-N series terminal blocks can be labeled by using plotter or thermal marking systems.

Electrical Ratings	
Terminal Current	10 A
Diode Voltage	1000 V
Diode Current	1 A
Connection Data	
Solid Strand, Screw Connection	0,8 - 4 mm²
Fine Strand, Screw Connection	0,8 - 2,5 mm²
AWG Conductor	AWG 28 - 12
Terminal Width	6,2 mm
Terminal Length	100,5 mm



Sch. Cir. Dia.	Input Voltage	Circuit Type	Cat. No.
1	-	Reverse Current Protection	110 010N
2	-	Reverse Current Protection	110 020N
3	-	Reverse Current Protection	110 030N
4	-	Reverse Current Protection	110 040N
5	-	Lamp / Test Circuit	110 050N
6	-	Lamp / Test Circuit	110 060N
7	-	Reverse Current Protection	110 070N
8	-	Reverse Current Protection	110 080N
9	-	Lamp / Test Circuit	110 090N
10	-	Lamp / Test Circuit	110 100N
11	-	Lamp / Test Circuit	110 110N
12	24VAC/DC	Lamp / Test Circuit	110 120N
13	24VAC/DC	Lamp / Test Circuit	110 130N
14	24VDC	Voltage Indicator	110 140N
14	110VDC	Voltage Indicator	110 150N
14	220VDC	Voltage Indicator	110 160N
15	24VDC	Voltage Indicator	110 170N
15	110VDC	Voltage Indicator	110 180N
15	220VDC	Voltage Indicator	110 190N
16	24VDC	Voltage Indicator + Flyback Diode	110 200N
17	24VDC	Voltage Indicator + Flyback Diode	110 210N
18	24VAC/DC	Voltage Indicator	110 270N
18	48VAC/DC	Voltage Indicator	110 280N
18	110VAC/DC	Voltage Indicator	110 290N
18	220VAC/DC	Voltage Indicator	110 300N
19	24VAC/DC	Voltage Indicator + Rectifier	110 310N
19	110VAC/DC	Voltage Indicator + Rectifier	110 320N
19	220VAC/DC	Voltage Indicator + Rectifier	110 330N
20	-	Terminal with Cross Connection	110 380N
21	24VAC/DC	Voltage Divider	110 410N



Accessories and Components									
	End Plate	Plug-in Bridge 2 Holes	Plug-in Bridge 3 Holes	Plug-in Bridge 4 Holes	Plug-in Bridge 5 Holes	Plug-in Bridge 10 Holes	DG 6/5 Label	DB 5 Label	11.2 Strip Label
Cat. No.	450389	470112	470113	470114	470115	470119	505330	505850	1020100
Qty.	10	25	20	15	10	5	440	500	1


Easy Mounting of PYK Series Terminals

Solid/stranded cables(with ferrules) are connected to the terminal just by pushing-in,without the need to use a screwdriver. The patented design of its spring provides fast and safe connection in heavily vibrating environments.



PYK Series Disconnect Terminals

Knife Disconnect System, enables Practical Spring Clamp Disconnect Terminals to switch energy in the system. Marking can be done with marking strip printed on Thermal printer, using Klemark Software.




PYK Series Fuse Terminals

Practical Spring Clamp Fuse Terminals has a sliding type hinged carrier that has a specially designed space for cartridge type glass fuse of size Ø5x20 or Ø5x25 together with a spare one. Easy cross-connection can be done by the help of Push in type Practical Cross Connection. Accessories facilitating Plotter labeling are available.


PYK Series Multilevel Terminals

Practical Spring Clamp Multilevel Terminals are used to perform connection of wires in limited spaces, 2-3 times more connections can be done at the same space on the rail. Cross-connection can be done between the layers. Marking is possible at each layer, at the same time usage of group marking carrier makes marking even clearer and visible.




PYK Series Terminals



PYK Series Practical Spring Clamp Terminals provide 16 mm² cross-section range. Screwdriver is not necessary to install wire into the terminal block. Are suitable for usage with or without ferrules. So that to make connection, it is enough to push the cable into the terminal, PYK series provides more practical mounting. Terminals accessories like End Plates and Cross Connections, make the mounting process faster like in Test Terminals. Special Marking solutions for each cross section can be provided by Plotter labeling and with marking strip printed on Thermal printer, using Klemark Software. PYK Test Terminals, produced with the test and control aim, can be labeled with thermal marking strips and standard Dekafix markings.



PYK Series Earth Terminals provides 16 mm² cross-section range. Screwdriver is not necessary to mount the terminal block on the rail. Mounting is more time-saving and practical. Yellow-Green color of the insulation body provides easy identification out of other Terminals. Side-by-side mounting on DIN-Rail with feed-through terminals for same cross-sections is possible with good visual effect. Special Marking solutions for each cross section can be provided by Plotter labeling and with marking strip printed on Thermal printer, using Klemark Software.




PYKM Series Practical spring clamp mini Terminals, mounted on MR 15*5,5 rail, provide both feed-through and Earth terminals. These terminals can be connected to each other when mounted on the din rail and have safe connection. Practical Spring Clamp mini Terminals enable fast solutions on narrow spaces. Marking solutions are available with Thermal Printer labeling and Plotter labeling.

PYKMR Series Practical spring clamp mini Terminals, can be mounted on MR 35 rail, provide both feed-through and Earth terminals. These terminals can be connected to each other when mounted on the din rail and have safe connection. Practical Spring Clamp mini Terminals enable fast solutions on narrow spaces. Marking solutions are available with Thermal Printer labeling and Plotter labeling.

Practical Spring Clamp Terminals

PYK 10

Width: 10 mm




52,00
MR 35 x 7,5

75,40

PYK 16

Width: 12 mm



49,50
MR 35 x 7,5

81,45

Cat No:

- 307 139
- 307 130

Cat No:

- 307 659
- 307 650



Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver



Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity

Voltage, V ~	Current, A	Cross-Section
800	57	10 mm²
600	55	AWG 20-6
800	50	

	0,5-16 mm²
	0,5-10 mm²
	4 mm²
	AWG 20-6
	13-15 mm
	KT 4 (0,8x4,0)

Type	Cat.No.	Qty.
NPP/PYK 10	446 479	50

Type	Cat.No.	Qty.
APP PYK 10	463 200	25

Type	Cat.No.	Qty.
UK 10/2	476 252	25
UK 10/3	476 253	20
UK 10/4	476 254	15
UK 10/10	476 259	5

8/3
1/B6
IP 20 / -
D_NS 10x10, SLF-P2 W, DG 10/10, SLF-P1 W

50 pcs.

Voltage, V ~	Current, A	Cross-Section
1000	76	16 mm²

	0,5-25 mm²
	0,5-16 mm²
	4 mm²
	AWG 20-4
	16-18 mm
	KT 4 (0,8x4,0)

Type	Cat.No.	Qty.
NPP/PYK 16	450 419	25

Type	Cat.No.	Qty.

Type	Cat.No.	Qty.
UK 16/2	470 142	25
UK 16/3	470 143	20
UK 16/4	470 144	15
UK 16/5	470 145	10



8/3
1/B7
IP 20 / -
D_NS 12x10, DG 10/10, SLF-P1 W

30 pcs.

Color							
Color code is the last digit of the order number							
Blue	Green	Yellow	Red	Black	White	Orange	Brown
1	2	3	4	5	6	7	8

Practical Spring Clamp
Earth Terminals



PYK 1,5 MT



Cat No:

336 440



PYK 1,5 T



Cat No:

336 490


PYK 2,5 T



Cat No:

336 500

PYK 4 T



Cat No:

336 510



Electrical Ratings
CE (EN 60947-7-2)
UL
VDE (IEC 60947-7-2)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

End Plate

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
100 pcs.

Voltage, V ~	Current, A	Cross-Section
		1,5 mm²

0,34-2,5 mm²
0,34-1,5 mm²
0,5 mm²
AWG 22-14
9-10 mm
KT 1 (0,4x2,5)

Type	Cat.No.	Qty.
NPP/PYK 1,5 MT	446 632 T	100

8/3
1/A1-B1
IP 20 / PE
D_NS 4,2x6, DB 6/4, SLF-P1 W

Voltage, V ~	Current, A	Cross-Section
		1,5 mm²

0,34-2,5 mm²
0,34-1,5 mm²
0,5 mm²
AWG 22-14
9-10 mm
KT 1 (0,4x2,5)

Type	Cat.No.	Qty.
NPP/PYK 1,5 T	446 442 T	10

8/3
1/A1-B1
IP 20 / PE
D_NS 4,2x6, DB 6/4, SLF-P1 W

100 pcs.

Voltage, V ~	Current, A	Cross-Section
		2,5 mm²
		AWG 22-12
		2,5 mm²

800
0,34-4 mm²
0,34-2,5 mm²
0,5 mm²
AWG 22-12
9-10 mm
KT 1 (0,4x2,5)

Type	Cat.No.	Qty.
NPP/PYK 2,5 T	446 442 T	10

8/3
1/A3
IP 20 / PE
D_NS 5x10, SLF-P2 W , DB 10/5, DG 10/5, DG 10/5T, SLF-P1 W

50 pcs.

Voltage, V ~	Current, A	Cross-Section
		4 mm²
		AWG 22-10
		4 mm²

800
0,34-6 mm²
0,25-4 mm²
1 mm²
AWG 22-10
9-10 mm
KT 2 (0,5x3,0)

Type	Cat.No.	Qty.
NPP/PYK 4 T	446 452 T	10

8/3
1/A4
IP 20 / PE
D_NS 6x10, SLF-P2 W , DB 10/5, DG 10/5, DG 10/5T, SLF-P1 W

50 pcs.

Voltage, V ~	Current, A	Cross-Section
		4 mm²
		AWG 22-10
		4 mm²

800
0,34-6 mm²
0,25-4 mm²
1 mm²
AWG 22-10
9-10 mm
KT 2 (0,5x3,0)



Type	Cat.No.	Qty.
NPP/PYK 4 T	446 452 T	10

8/3
1/A4
IP 20 / PE
D_NS 6x10, SLF-P2 W , DB 10/5, DG 10/5, DG 10/5T, SLF-P1 W

50 pcs.

Practical Spring Clamp
Earth Terminals



PYK 6 T



Cat No:

336 520



PYK 10 T



Cat No:

336 530



PYK 16 T



Cat No:

336 640

PYK Test



Cat No:

498 559
498 550



Electrical Ratings
CE (EN 60947-7-2)
UL
VDE (IEC 60947-7-2)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

End Plate

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
60 pcs.

Voltage, V ~	Current, A	Cross-Section
600		6 mm² AWG 20-8

0,5-10 mm²
0,5-6 mm²
1,5 mm²
AWG 20-8
11-13 mm
KT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/PYK 6 T	446 462 T	10

8/3
1/A5
IP 20 / PE
D_NS 8x10, SLF-P2 W, DG 10/8, SLF-P1 W

Voltage, V ~	Current, A	Cross-Section
600		10 mm² AWG 20-6

0,5-16 mm²
0,5-10 mm²
4 mm²
AWG 20-6
13-15 mm
KT 4 (0,8x4,0)

Type	Cat.No.	Qty.
NPP/PYK 10 T	446 472 T	10

8/3
1/B6
IP 20 / PE
D_NS 10x10, SLF-P2 W, DG 10/10, SLF-P1 W

25 pcs.

Voltage, V ~	Current, A	Cross-Section

Type	Cat.No.	Qty.

--

Voltage, V ~	Current, A	Cross-Section
		16 mm²

0,5-25 mm²
0,5-16 mm²
4 mm²
AWG 20-4
16-18 mm
KT 4 (0,8x4,0)

Type	Cat.No.	Qty.
NPP/PYK 16 T	450 412 T	25

8/3
1/B7
IP 20 / PE
D_NS 12x10, DG 10/10, SLF-P1 W

30 pcs.

Voltage, V ~	Current, A	Cross-Section
250	17,5	1,5 mm²
300	15	AWG 22-14

0,34-2,5 mm²
0,34-1,5 mm²
0,5 mm²
AWG 22-14
9-10 mm
KT 1 (0,4x2,5)

Type	Cat.No.	Qty.
PYK TEST A	498 659	25

8/3
1/A1-B1
IP 20 / -

25 pcs.

Used for Terminals	
307 109	PYK 2,5
307 119	PYK 4
307 229	PYK 4 E
307 169	PYK 2,5 A
307 219	PYK 2,5 CCA
307 389	PYK 2,5 C
307439	PYK 2,5 E
304 200	AVK 2,5 RD
304 210	AVK 4 RD

PYK test terminals, which minimize the time needed for test and control connections, can be marked with Standard marking tags and thermal printer labels. PYK test terminals, being as a group together, Terminals can be used with PYK 2,5 terminals. When PYK Test A plates are added to Test terminals, the Terminals can be used with PYK 4 terminals.

PYKMR Series Mini
Terminals

PYKMR 2,5

Width: 5 mm




Cat No:

- 307 499
- 307 490

PYKM 2,5

Width: 5 mm




Cat No:

- 307 399
- 307 390

PYKM 2,5 T

Width: 5 mm



Cat No:

- 336 430



Electrical Ratings
CE (EN 60947-7-1 / EN 60947-7-2)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

End Plate

Grey
Grey
Yellow- Green
Yellow- Green

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
50 pcs.

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20	AWG 22-12

Type	Cat.No.	Qty.
NPP1 PYKMR 2,5	446 589	100
NPP2 PYKMR 2,5	446 599	100

Type	Cat.No.	Qty.
NPP1 PYKM 2,5	446 589	100
NPP2 PYKM 2,5	446 599	100

Type	Cat.No.	Qty.
NPP1 PYKM 2,5T	446 582 T	25
NPP2 PYKM 2,5T	446 592 T	25

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20	AWG 22-12

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20	AWG 22-12

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20	AWG 22-12

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20	AWG 22-12

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20	AWG 22-12

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20	AWG 22-12

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20	AWG 22-12

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20	AWG 22-12

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20	AWG 22-12

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20	AWG 22-12

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20	AWG 22-12


Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20	AWG 22-12

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20	AWG 22-12






Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20	AWG 22-12

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20	AWG 22-12

PYK Series Multilevel Rail Terminals




Double Deck Practical Spring Terminals are available in 2,5 - 4 mm cross section range. Double wiring density available without extension of mounting rails. Interconnection / shorting can be done at both layers. Group marking carrier is used to provide more visual marking in base layer. Special Marking solutions for each cross section can be provided by Thermal Printing and Plotter Labeling.



Multilevel Practical Spring Terminals make wiring more practical, reduce the installation costs and speed the wiring. Panels which exist switch lines & lightening, provide phase-neutral-Earth connection in one terminal. Are ideal for usage in industries where motors are working a lot, because of more practical wiring. Provide individual cross connections for each layer. Group marking carrier is used to provide more visual marking in base layer. Special Marking solutions for each cross section can be provided by Thermal Printing and Plotter Labeling.

Double - Deck
Practical
Spring Clamp
Line Type Terminals

PYK 2,5 - M2F



Cat No:

- 307 699
- 307 690



Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver


End Plate

Cross Connection

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity

PYK 2,5 - M2FT



Cat No:

- 307 709
- 307 700

Voltage, V ~	Current, A	Cross-Section
250	24	2,5 mm²

0,34-4 mm²
0,34-2,5 mm²
0,5 mm²
AWG 22-12
9-10 mm
KT 1 (0,4x2,5)


Type	Cat.No.	Qty.
NPP PYK PYK 2,5-M2FT	450 429	30

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

6/3
1/A3
IP 20 / -
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T, SLF-P1 W

30 pcs.

PYK 4 - 2 FN



Cat No:

- 307 579
- 307 570

Voltage, V ~	Current, A	Cross-Section
500	32	4 mm²

0,34-6 mm²
0,25-4 mm²
1 mm²
AWG 22-10
9-10 mm
KT 2 (0,5x3,0)

Type	Cat.No.	Qty.
NPP PYK 4-2 FN	446 669	25

Type	Cat.No.	Qty.
UK 4/2	476 232	25
UK 4/3	476 233	20
UK 4/4	476 234	15
UK 4/10	476 239	5

6/3
1/A4
IP 20 / -
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T, SLF-P1 W

25 pcs.

PYK 2,5 - 2 F



Cat No:

- 307 179
- 307 170

Voltage, V ~	Current, A	Cross-Section
500	24	2,5 mm²
300	20	AWG 22-12
500	21	

0,34-4 mm²
0,34-2,5 mm²
0,5 mm²
AWG 22-12
9-10 mm
KT 1 (0,4x2,5)


Type	Cat.No.	Qty.
NPP PYK 2,5-2 F	446 519	10

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

6/3
1/A3
IP 20 / -
D_NS 5x10, SLF-P2 W, DB 10/5, DG 10/5, DG, 10/5T, SLF-P1 W

40 pcs.

PYK 2,5 - 2 FK



Cat No:

- 307 239
- 307 230

Voltage, V ~	Current, A	Cross-Section
500	24	2,5 mm²
300	20	AWG 20-12

0,34-4 mm²
0,34-2,5 mm²
0,5 mm²
AWG 22-12
9-10 mm
KT 1 (0,4x2,5)

Type	Cat.No.	Qty.
NPP PYK 2,5-2 FK	446 519	10


Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

6/3
1/A3
IP 20 / -
D_NS 5x10, SLF-P2 W, DB 10/5, DG 10/5, DG 10/5T, SLF-P1 W

40 pcs.

Double - Deck
Practical
Spring Clamp
Terminals


PYK 2,5 - 2 FLD



Cat No:

- 307 349
- 307 340


PYK 2,5 - 2 FD A



Cat No:

- 307 369
- 307 360

PYK 2,5 - 2 FD B



Cat No:

- 307 379
- 307 370



Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Voltage, V ~	Current, A	Cross-Section
	24	2,5 mm²

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

0,34-4 mm²
0,34-2,5 mm²
0,5 mm²
AWG 22-12
9-10 mm
KT 1 (0,4x2,5)

Ordering Data

Type	Cat.No.	Qty.
24V DC	307 349	40
220V AC	307 359	40

Technical Data For Diode
Diode Voltage
Diode Current
Diod

Voltage, V ~	Current, A	Cross-Section
500	0,5	2,5 mm²

0,34-4 mm²
0,34-2,5 mm²
0,5 mm²
AWG 22-12
9-10 mm
KT 1 (0,4x2,5)

Type	Cat.No.	Qty.

1000 V
1 A
1 N 4007

End Plate

Type	Cat.No.	Qty.
NPP PYK 2,5-2 FLD	446 519	10

Cross Connection

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

6/3
1/A3
IP 20 / -
D_NS 5x10, SLF-P2 W, DB 10/5, DG 10/5, DG 10/5T, SLF-P1 W

Package Quantity
40 pcs.

40 pcs.

Type	Cat.No.	Qty.
NPP PYK 2,5-2 F	446 519	10

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

6/3
1/A3
IP 20 / -
D_NS 5x10, SLF-P2 W, DB 10/5, DG 10/5, DG 10/5T, SLF-P1 W

40 pcs.

Voltage, V ~	Current, A	Cross-Section

Type	Cat.No.	Qty.

Type	Cat.No.	Qty.

Type	Cat.No.	Qty.

Voltage, V ~	Current, A	Cross-Section
500	0,5	2,5 mm²

0,34-4 mm²
0,34-2,5 mm²
0,5 mm²
AWG 22-12
9-10 mm
KT 1 (0,4x2,5)

Type	Cat.No.	Qty.

1000 V
1 A
1 N 4007

Type	Cat.No.	Qty.
NPP PYK 2,5-2 F	446 519	10


Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

6/3
1/A3
IP 20 / -
D_NS 5x10, SLF-P2 W, DB 10/5, DG 10/5, DG 10/5T, SLF-P1 W

40 pcs.

Multilevel Practical
Spring Clamp
Terminals

PYK 2,5 - 3 F



Cat No:

- 307 199
- 307 190



Electrical Ratings
CE (EN 60947-7-1 / EN 60947-7-2)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver


End Plate

Cross Connection

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
30 pcs.

PYK 2,5 - 3 FK



Cat No:

- 307 559
- 307 550

Voltage, V ~	Current, A	Cross-Section
500	24	2,5 mm²
300	20	AWG 22-12
500	18	

0,34-4 mm²
0,34-2,5 mm²
0,5 mm²
AWG 22-12
9-10 mm
KT 1 (0,4x2,5)


Type	Cat.No.	Qty.
NPP PYK 2,5-3 FK	446 529	10

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

6/3
1/A3
IP 20 / -
D_NS 5x10, SLF-P2 W, DB 10/5, DG 10/5, DG 10/5T, SLF-P1 W

30 pcs.

PYK 2,5 - 2 FT



Cat No:

- 307 189
- 307 180

Voltage, V ~	Current, A	Cross-Section
500	24	2,5 mm²
300	20	AWG 22-12
500	21	

0,34-4 mm²
0,34-2,5 mm²
0,5 mm²
AWG 22-12
9-10 mm
KT 1 (0,4x2,5)


Type	Cat.No.	Qty.
NPP PYK 2,5-2 FT	446 529	10

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

6/3
1/A3
IP 20 / -
D_NS 5x10, SLF-P2 W, DB 10/5, DG 10/5, DG 10/5T, SLF-P1 W

30 pcs.

PYK 2,5 - 3 FT



Cat No:

- 307 209
- 307 200

Voltage, V ~	Current, A	Cross-Section
500	24	2,5 mm²
300	20	AWG 22-12
400	18	

0,34-4 mm²
0,34-2,5 mm²
0,5 mm²
AWG 22-12
9-10 mm
KT 1 (0,4x2,5)

Type	Cat.No.	Qty.
NPP PYK 2,5-3 FT	446 539	30

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5


6/3
1/A3
IP 20 / -
D_NS 5x10, SLF-P2 W, DB 10/5, DG 10/5, DG 10/5T, SLF-P1 W

30 pcs.




PYK Series Sensor / Fuse and Disconnect / Disconnect Terminals



Practical Spring Clamp Fuse Terminals has a sliding type hinged carrier that has a specially designed space for cartridge type glass fuse of size Ø 5x20 or Ø 5x25. Both sides of the terminals are closed and available for cross connection. Special Marking solutions can be provided by Plotter Labeling.




PYK series Disconnect Terminals enables to safely open-close the circuit , when the energy is on in the system. Can be marked with Thermal marking strip and cross-connected together with all other single-level terminals. Special Marking solutions can be provided by Thermal Printing and Plotter Labeling.



Practical Spring Terminals are making sensor connections, which are often used in industry, more practical and esthetic. All PYK series with single layer are available with marking strip printed on Thermal printer, using Klemark Software. Terminals can be used with NPN and PNP types of sensors. Special Marking solutions for each cross section can be provided by Thermal Printing and Plotter Labeling.

Practical Spring Clamp Sensor Terminals

PYK 3 S



Cat No:

307 409
 307 400

Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

End Plate


A 3D model of a grey, stepped rectangular block, representing the end plate. It has a flat top surface and a stepped profile on the right side.

Cross Connection

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity

PYK 3 SLD (NPN)



Cat No:

307 419
307 410

Voltage, V ~	Current, A	Cross-Section
24	24	2,5 mm ²

	0,34-4 mm ²
	0,34-2,5 mm ²
	0,5 mm ²
	AWG 22-12
	9-10 mm
	KT 1 (0,4x2,5)


Type	Cat.No.	Qty.
NPP PYK 3 S	446 609	10

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

8/3
1/A3
IP 20 / -
D_NS 5x10, SLF-P2 W, DB 10/5, DG 10/5, DG 10/5T

	20 pcs.

PYK 3 SLD (PNP)



Cat No:

307 429
307 420

Voltage, V ~	Current, A	Cross-Section
24	24	2,5 mm ²

	0,34-4 mm ²
	0,34-2,5 mm ²
	0,5 mm ²
	AWG 22-12
	9-10 mm
	KT 1 (0,4x2,5)

Type	Cat.No.	Qty.
NPP PYK 3 S	446 609	10

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5


8/3
1/A3
IP 20 / -
D_NS 5x10, SLF-P2 W, DB 10/5, DG 10/5, DG 10/5T

	20 pcs.

Practical Spring Clamp
Fuse and Disconnect
Terminals

PYK 2,5 A

Width: 5 mm




70,80

Cat No:

- 307 169
- 307 160

PYK 2,5 EA

Width: 5 mm




82,40

Cat No:

- 307 459
- 307 450

PYK 2,5 CCA

Width: 5 mm



93,90

Cat No:

- 307 219
- 307 210



Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

End Plate


Push-in Cross Connection


Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
50 pcs.

Voltage, V ~	Current, A	Cross-Section
400	20	2,5 mm²
300	16	AWG 22-12

0,34-4 mm²
0,34-2,5 mm²
0,5 mm²
AWG 22-12
9-10 mm
KT 1 (0,4x2,5)

Type	Cat.No.	Qty.
NPP/PYK 2,5 A	446 509	100

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

4/3
1/A3
IP 20 / -
D_NS 5x10, SLF-P2 W, DB 10/5, DG 10/5, DG 10/5T, SLF-P1 W

Voltage, V ~	Current, A	Cross-Section
400	16	2,5 mm²

0,34-4 mm²
0,34-2,5 mm²
0,5 mm²
AWG 22-12
9-10 mm
KT 1 (0,4x2,5)

Type	Cat.No.	Qty.
NPP/PYK 2,5 EA	446 629	100

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

4/3
1/A3
IP 20 / -
D_NS 5x10, SLF-P2 W, DB 10/5, DG 10/5, DG 10/5T, SLF-P1 W

60 pcs.

Voltage, V ~	Current, A	Cross-Section

Type	Cat.No.	Qty.

Type	Cat.No.	Qty.

--

Voltage, V ~	Current, A	Cross-Section
400	16	2,5 mm²
300	10	AWG 22-12

0,34-4 mm²
0,34-2,5 mm²
0,5 mm²
AWG 22-12
9-10 mm
KT 1 (0,4x2,5)

Type	Cat.No.	Qty.
NPP/PYK 2,5 CCA	446 549	100




Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

4/3
1/A3
IP 20 / -
D_NS 5x10, SLF-P2 W, DB 10/5, DG 10/5, DG 10/5T, SLF-P1 W

60 pcs.

PYK Series Multi input/output Terminals

PYK Series One Input - Two Output
Two Input - Two Output Terminals



PYK Series


One Input - Two Output

Two Input - Two Output

Terminals

PYK 1,5 ME

Width: 4,2 mm





63,60

Cat No:

- 307 039
- 307 030

PYK 1,5 MET

Width: 4,2 mm




63,60

Cat No:

- 336 460

PYK 1,5 MC

Width: 4,2 mm





75,10

Cat No:

- 307 029
- 307 020

PYK 1,5 MCT

Width: 4,2 mm



75,10

Cat No:

- 336 450



Electrical Ratings
CE (EN 60947-7-1 - EN 60947-7-2)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

End Plate



Push-in Cross Connection



Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
70 pcs.

Voltage, V ~	Current, A	Cross-Section
800	17,5	1,5 mm²

0,34-2,5 mm²
0,34-1,5 mm²
0,5 mm²
AWG 22-14
9-10 mm
KT 1 (0,4x2,5)

Type	Cat.No.	Qty.
NPP/PYK 1,5 ME	446 649	100

Type	Cat.No.	Qty.
UK 1,5/2	476 602	25
UK 1,5/3	476 603	20
UK 1,5/4	476 604	15
UK 1,5/10	476 609	5

8/3
1/A1-B1
IP 20 / -
D_NS 4,2x6, DB 6/4

70 pcs.

Voltage, V ~	Current, A	Cross-Section
		1,5 mm²

0,34-2,5 mm²
0,34-1,5 mm²
0,5 mm²
AWG 22-14
9-10 mm
KT 1 (0,4x2,5)

Type	Cat.No.	Qty.
NPP/PYK 1,5 MET	446 642T	100

Type	Cat.No.	Qty.

8/3
1/A1-B1
IP 20 / -
D_NS 4,2x6, DB 6/4

70 pcs.

Voltage, V ~	Current, A	Cross-Section

Type	Cat.No.	Qty.

Type	Cat.No.	Qty.

--

Voltage, V ~	Current, A	Cross-Section
800	17,5	1,5 mm²

0,34-2,5 mm²
0,34-1,5 mm²
0,5 mm²
AWG 22-14
9-10 mm
KT 1 (0,4x2,5)

Type	Cat.No.	Qty.
NPP/PYK 1,5 MC	446 659	100

Type	Cat.No.	Qty.
UK 1,5/2	476 602	25
UK 1,5/3	476 603	20
UK 1,5/4	476 604	15
UK 1,5/10	476 609	5

8/3
1/A1-B1
IP 20 / -
D_NS 4,2x6, DB 6/4

70 pcs.

Voltage, V ~	Current, A	Cross-Section
		1,5 mm²

0,34-2,5 mm²
0,34-1,5 mm²
0,5 mm²
AWG 22-14
9-10 mm
KT 1 (0,4x2,5)

Type	Cat.No.	Qty.
NPP/PYK 1,5 MCT	446 652T	100

Type	Cat.No.	Qty.

8/3
1/A1-B1
IP 20 / -
D_NS 4,2x6, DB 6/4

70 pcs.

PYK Series

One Input - Two Output

Two Input - Two Output

Terminals

PYK 2,5 E

Width: 5 mm




64,85

Cat No:

- 307 439
- 307 430

PYK 2,5 ET

Width: 5 mm



64,85

Cat No:

- 336 550

PYK 2,5 C

Width: 5 mm




76,40

Cat No:

- 307 389
- 307 380

PYK 2,5 CT

Width: 5 mm




76,40

Cat No:

- 336 540

PYK 4 E

Width: 6 mm



70,80

Cat No:

- 307 229
- 307 220



Electrical Ratings
CE (EN 60947-7-1 - EN 60947-7-2)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

End Plate

Test Terminal Block

Push-in Cross Connection

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
50 pcs.

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20	AWG 22-12

0,34-4 mm²
0,34-2,5 mm²
0,5 mm²
AWG 22-12
9-10 mm
KT 1 (0,4x2,5)

Type	Cat.No.	Qty.
NPP/PYK 2,5 E	446 619	10

Type	Cat.No.	Qty.
PYK TEST	498 559	25

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

8/3
1/A3
IP 20 / -
D_NS 5x10, SLF-P2 W, DB 10/5, DG 10/5, DG 10/5T, SLF-P1 W

50 pcs.

Voltage, V ~	Current, A	Cross-Section
		2,5 mm²
		AWG 22-12

0,34-4 mm²
0,34-2,5 mm²
0,5 mm²
AWG 22-12
9-10 mm
KT 1 (0,4x2,5)

Type	Cat.No.	Qty.
NPP/PYK 2,5 ET	446 612T	10

Type	Cat.No.	Qty.

8/3
1/A3
IP 20 / -
D_NS 5x10, SLF-P2 W, DB 10/5, DG 10/5, DG 10/5T, SLF-P1 W

50 pcs.

Voltage, V ~	Current, A	Cross-Section
		2,5 mm²
		AWG 22-12

0,34-4 mm²
0,34-2,5 mm²
0,5 mm²
AWG 22-12
9-10 mm
KT 1 (0,4x2,5)

Type	Cat.No.	Qty.

Type	Cat.No.	Qty.

8/3
1/A3
IP 20 / -
D_NS 5x10, SLF-P2 W, DB 10/5, DG 10/5, DG 10/5T, SLF-P1 W

50 pcs.

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20	AWG 22-12

0,34-4 mm²
0,34-2,5 mm²
0,5 mm²
AWG 22-12
9-10 mm
KT 1 (0,4x2,5)

Type	Cat.No.	Qty.
NPP/PYK 2,5 C	446 499	10

Type	Cat.No.	Qty.
PYK TEST	498 559	25

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

8/3
1/A3
IP 20 / -
D_NS 5x10, SLF-P2 W, DB 10/5, DG 10/5, DG 10/5T, SLF-P1 W

50 pcs.

Voltage, V ~	Current, A	Cross-Section
		2,5 mm²
		AWG 22-12

0,34-4 mm²
0,34-2,5 mm²
0,5 mm²
AWG 22-12
9-10 mm
KT 1 (0,4x2,5)

Type	Cat.No.	Qty.
NPP/PYK 2,5 CT	446 492T	10

Type	Cat.No.	Qty.

8/3
1/A3
IP 20 / -
D_NS 5x10, SLF-P2 W, DB 10/5, DG 10/5, DG 10/5T, SLF-P1 W

50 pcs.

Voltage, V ~	Current, A	Cross-Section
800	32	4 mm²
600	30	AWG 22-12
800	30	

0,34-6 mm²
0,25-4 mm²
1 mm²
AWG 22-10
9-10 mm
KT 2 (0,5x3,0)

Type	Cat.No.	Qty.
NPP/PYK 4 E	446 559	50

Type	Cat.No.	Qty.
PYK TEST	498 559	25
PYK TEST A	498 659	25

Type	Cat.No.	Qty.
UK 4/2	476 232	25
UK 4/3	476 233	20
UK 4/4	476 234	15
UK 4/10	476 239	5

8/3
1/A4
IP 20 / -
D_NS 6x10,SLF-P2 W, DB 10/6, DG 10/6, DG 10/6T, SLF-P1 W

50 pcs.

PYK Series
One input - Two Output
Two input - Two Output
Spring Clamp
Terminals




Electrical Ratings
CE (EN 60947-7-1 - EN 60947-7-2)
UL
VDE (IEC 60947-7-1)
CSA
ATEX
Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver
End Plate

Test Terminal Block

Push-in Cross Connection


Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix
Package Quantity



Cat No:

- 307 639
- 307 630


Voltage, V ~	Current, A	Cross-Section
1000	41	6 mm²
Type	Cat.No.	Qty.
NPP/PYK 6 E	446 689	25
Type	Cat.No.	Qty.
UK 6/2	476 242	25
UK 6/3	476 243	10
UK 6/4	476 244	15
UK 6/9	476 249	5
Type	Cat.No.	Qty.
8/3		
1/A5		
IP 20 / -		
D_NS 8x10, DG 10/8, DG 10/8T, SLF-P1 W		
45 pcs.		



Cat No:

- 336 620


Voltage, V ~	Current, A	Cross-Section
		6 mm²
Type	Cat.No.	Qty.
NPP/PYK 6 ET	446 682T	25
Type	Cat.No.	Qty.
Type	Cat.No.	Qty.
8/3		
1/A5		
IP 20 / -		
D_NS 8x10, DG 10/8, DG 10/8T, SLF-P1 W		
45 pcs.		



Cat No:

- 307 649
- 307 640

Voltage, V ~	Current, A	Cross-Section
1000	41	6 mm²
Type	Cat.No.	Qty.
NPP/PYK 6 C	446 699	25
Type	Cat.No.	Qty.
UK 6/2	476 242	25
UK 6/3	476 243	10
UK 6/4	476 244	15
UK 6/9	476 249	5
Type	Cat.No.	Qty.
8/3		
1/A5		
IP 20 / -		
D_NS 8x10, DG 10/8, DG 10/8T, SLF-P1 W		
35 pcs.		



Cat No:

- 336 630

Voltage, V ~	Current, A	Cross-Section
		6 mm²
Type	Cat.No.	Qty.
NPP/PYK 6 CT	446 692T	25
Type	Cat.No.	Qty.
Type	Cat.No.	Qty.
8/3		
1/A5		
IP 20 / -		
D_NS 8x10, DG 10/8, DG 10/8T, SLF-P1 W		
35 pcs.		




Cat No:


- 307 149
- 307 140

Voltage, V ~	Current, A	Cross-Section
800	57	10 mm²
Type	Cat.No.	Qty.
NPP/PYK 10E	446 709	25
Type	Cat.No.	Qty.
UK 10/2	476 252	25
UK 10/3	476 253	20
UK 10/4	476 254	15
UK 10/10	476 259	5
Type	Cat.No.	Qty.
8/3		
1/B7		
IP 20 / -		
D_NS 10x10, DG 10/10, SLF-P1 W		
50 pcs.		


YBK Series Spring Clamp Terminals






YBK Series Spring Clamp Terminals provide 2,5 10 mm² cross-section range. . Are suitable for usage with or without ferrules. So that to make connection, it is enough to release the spring with the help of screw-driver and then to push the cable into the terminal, Terminals accessories like End Plates and Cross Connections, make the mounting process faster like in Test Terminals. Special Marking solutions for each cross section can be provided by Plotter.




YBK Series Earth Terminals provides new design, which will satisfy customer tastes. YBK series provide non-corrosing contacts. The main difference between Spring Clamp Earth terminals and the Screw Connection Earth terminals is the automatic contact when the terminal blocks are attached on the DIN-rail, which makes wiring more practical and time-saving.



MYK Type Mini Terminals are available in 2,5 mm² cross-section. Can be mounted on MR 15x5,5 mm DIN-rail or directly on a flat surface. Earth Terminals, accessories, suitable for each usage, like End Plates and Cross Connections, make the mounting process faster. Marking solutions can be provided by Plotter. MYK series offer ideal solutions to projects which have narrow and limited space in panels, junction Boxes.



YBK Spring Clamp
Terminals





	Cat No:			Cat No:			Cat No:			Cat No:																																		
	306 229 306 220			306 239 306 230			306 249 306 240			306 259 306 250																																		
	Electrical Ratings			Voltage, V ~			Current, A			Cross-Section			Voltage, V ~			Current, A			Cross-Section			Voltage, V ~			Current, A			Cross-Section																
	CE (EN 60947-7-1)			750			24			2,5 mm²			750			32			4 mm²						750			41			6 mm²			750			57			10 mm²				
	UL			600			20			AWG 22-12			600			26			AWG 22-10						600			35			AWG 22-8			600			55			AWG 20-6				
VDE (IEC 60947-7-1)																																												
CSA																																												
ATEX																																												
Connection Data																																												
Conductor cross section solid (min.-max.)						0,08-4 mm²						0,08-6 mm²									0,2-10 mm²						0,2-16 mm²																	
Conductor cross section stranded (min.-max.)						0,08-2,5 mm²						0,08-4 mm²									0,2-6 mm²						0,2-10 mm²																	
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve						0,5 mm²						1 mm²									1,5 mm²						2,5 mm²																	
AWG Conductor						AWG 28-12						AWG 28-10									AWG 24-8						AWG 24-6																	
Insulation Stripping Length (min.-max.)						9-10 mm						10-12 mm									10-12 mm						11-13 mm																	
Screwdriver						KT 2 (0,5x3,0)						KT 3 (0,6x3,5)									KT 4 (0,8x4,0)						KT 4 (0,8x4,0)																	
End Plate			Type			Cat.No.			Qty.			Type			Cat.No.			Qty.			Type			Cat.No.			Qty.			Type			Cat.No.			Qty.								
			NPP/YBK 2,5			446 329			100			NPP/YBK 4			446 339			100						NPP/YBK 6			446 349			100			NPP/YBK 10			446 359			100					
Push-in Cross Connection			Type			Cat.No.			Qty.			Type			Cat.No.			Qty.			Type			Cat.No.			Qty.			Type			Cat.No.			Qty.								
			UK 2,5/2			476 222			25			UK 4/2			476 232			25						UK 6/2			476 242			25			UK 10/2			476 252			25					
			UK 2,5/3			476 223			20			UK 4/3			476 233			20						UK 6/3			476 243			20			UK 10/3			476 253			20					
			UK 2,5/4			476 224			15			UK 4/4			476 234			15						UK 6/4			476 244			15			UK 10/4			476 254			15					
			UK 2,5/10			476 229			5			UK 4/10			476 239			5						UK 6/10			476 249			5			UK 10/10			476 259			5					
Technical Data																																												
Rated Impulse Voltage / Pollution severity			8/3						8/3									8/3						8/3						8/3														
Insulation material group / Gauge pin code according to IEC 60947-1			1/A3						1/A4									1/A5						1/A6						1/A6														
Protection class / Protection conductor type			IP 20 / -						IP 20 / -									IP 20 / -						IP 20 / -						IP 20 / -														
Marking Tags (Dekafix)																																												
See pages 326-333 for a list of Dekafix			D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T						D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T									D_NS 8x10, DG 10/8						D_NS 10x10, DG 10/10																				
Package Quantity																																												
			100 pcs.						100 pcs.									100 pcs.						50 pcs.																				

Color							
Color code is the last digit of the order number							
Blue	Green	Yellow	Red	Black	White	Orange	Brown
1	2	3	4	5	6	7	8

Color							
Color code is the last digit of the order number							
Blue	Green	Yellow	Red	Black	White	Orange	Brown
1	2	3	4	5	6	7	8

YBK Spring Clamp
Earth Terminals


YBK 2,5 T



Cat No:

336 220



YBK 4 T



Cat No:

336 230



YBK 6 T



Cat No:

336 240

YBK 10 T



Cat No:

336 250



Electrical Ratings
CE (EN 60947-7-2)
UL
VDE (IEC 60947-7-2)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

End Plate

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity

Voltage, V ~	Current, A	Cross-Section
		2,5 mm²
		AWG 22-12

0,08-4 mm²
0,08-2,5 mm²
0,5 mm²
AWG 28-12
9-10 mm
KT 2 (0,5x3,0)

Type	Cat.No.	Qty.
NPP/YBK 2,5 T	446 322T	10

8/3
1/A3
IP 20 / PE
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T

50 pcs.

Voltage, V ~	Current, A	Cross-Section
		4 mm²
		AWG 22-10

0,08-6 mm²
0,08-4 mm²
1 mm²
AWG 28-10
10-12 mm
KT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/YBK 4 T	446 332T	10

8/3
1/A4
IP 20 / PE
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

50 pcs.

--

Voltage, V ~	Current, A	Cross-Section
		6 mm²
		AWG 22-8

0,2-10 mm²
0,2-6 mm²
1,5 mm²
AWG 24-8
10-12 mm
KT 4 (0,8x4,0)

Type	Cat.No.	Qty.
NPP/YBK 6 T	446 342T	10

8/3
1/A5
IP 20 / PE
D_NS 8x10, DG 10/8

40 pcs.

Voltage, V ~	Current, A	Cross-Section
		10 mm²
		AWG 20-6


0,2-16 mm²
0,2-10 mm²
2,5 mm²
AWG 24-6
11-13 mm
KT 4 (0,8x4,0)

Type	Cat.No.	Qty.
NPP/YBK 10 T	446 352T	10

8/3
1/A6
IP 20 / PE
D_NS 10x10, DG 10/10

30 pcs.

YBK Series Mini
Terminals





Cat No:

306 429

306 420



Cat No:

336 420

306 439

306 430

Cat No:

306 439

306 430


306 449

306 440

Cat No:


306 449

306 440

Electrical Ratings	Voltage, V ~	Current, A	Cross-Section	Voltage, V ~	Current, A	Cross-Section		Voltage, V ~	Current, A	Cross-Section	Voltage, V ~	Current, A	Cross-Section
CE (EN 60947-7-1 - EN 60947-7-2)	750	24	2,5 mm²			2,5 mm²		750	24	2,5 mm²	750	24	2,5 mm²
UL	600	20	AWG 22-12			AWG 22-12		600	20	AWG 22-12	600	20	AWG 22-12
VDE (IEC 60947-7-1)													
CSA													
ATEX	500	18						500	18		500	18	
Connection Data													
Conductor cross section solid (min.-max.)	0,08-4 mm²			0,08-4 mm²				0,08-4 mm²			0,08-4 mm²		
Conductor cross section stranded (min.-max.)	0,08-2,5 mm²			0,08-2,5 mm²				0,08-2,5 mm²			0,08-2,5 mm²		
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve	0,5 mm²			0,5 mm²				0,5 mm²			0,5 mm²		
AWG Conductor	AWG 28-12			AWG 28-12				AWG 28-12			AWG 28-12		
Insulation Stripping Length (min.-max.)	9-10 mm			9-10 mm				9-10 mm			9-10 mm		
Screwdriver	KT 2 (0,5x3,0)			KT 2 (0,5x3,0)				KT 2 (0,5x3,0)			KT 2 (0,5x3,0)		
End Plate	Type	Cat.No.	Qty.	Type	Cat.No.	Qty.		Type	Cat.No.	Qty.	Type	Cat.No.	Qty.
 	NPP 1 MYK	446 429	100	NPP 1 MYK 2,5 T	446 422T	100		NPP MYPD 1	495 079	100	NPP MYK 1	446 429	100
	NPP 2 MYK	446 439	100	NPP 2 MYK 2,5 T	446 432T	100		NPP MYPD 2	495 089	100	NPP MYK 2	446 439	100
Push-in Cross Connection	Type	Cat.No.	Qty.					Type	Cat.No.	Qty.	Type	Cat.No.	Qty.
 	UK 2,5/2	476 222	25					UK 2,5/2	476 222	25	UK 2,5/2	476 222	25
	UK 2,5/3	476 223	20					UK 2,5/3	476 223	20	UK 2,5/3	476 223	20
	UK 2,5/4	476 224	15					UK 2,5/4	476 224	15	UK 2,5/4	476 224	15
	UK 2,5/10	476 229	5					UK 2,5/10	476 229	5	UK 2,5/10	476 229	5
Technical Data													
Rated Impulse Voltage / Pollution severity	8/3			8/3				8/3			8/3		
Insulation material group / Gauge pin code according to IEC 60947-1	1/B3			1/B3				1/B3			1/B3		
Protection class / Protection conductor type	IP 20 / -			IP 20 / PE				IP 20 / -			IP 20 / -		
Marking Tags (Dekafix)													
See pages 326-333 for a list of Dekafix	DB 5			DB 5				DB 5			DB 5		
Package Quantity													
	50 pcs.			50 pcs.				100 pcs.			100 pcs.		



* For panel surface Mounting

* 3.5 mm (diameter) hole must be opened on panel surface.



YBK Series Mini
Terminals



MYK 2,5 C



Cat No:

- 306 479
- 306 470



MYPK 2,5 C



Cat No:

- 306 489
- 306 480



MYKR 2,5 C



Cat No:

- 306 499
- 306 490

MYKR 2,5



Cat No:

- 306 509
- 306 500



Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

End Plate

Push-in Cross Connection

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
100 pcs.

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²

0,08-4 mm²
0,08-2,5 mm²
0,5 mm²
AWG 28-12
9-10 mm
KT 2 (0,5x3,0)

Type	Cat.No.	Qty.
NPP 1 MYK 2,5C	446 429	100
NPP 2 MYK 2,5C	446 439	100

8/3
1/B3
IP 20 / -
DB 5

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²

0,08-4 mm²
0,08-2,5 mm²
0,5 mm²
AWG 28-12
9-10 mm
KT 2 (0,5x3,0)

Type	Cat.No.	Qty.
NPP MYPD 1	495 079	100
NPP MYPD 2	495 089	100

8/3
1/B3
IP 20 / -
DB 5

100 pcs.

* For panel surface mounting

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²

0,08-4 mm²
0,08-2,5 mm²
0,5 mm²
AWG 28-12
9-10 mm
KT 2 (0,5x3,0)

Type	Cat.No.	Qty.
NPP 1 MYK	446 429	100
NPP 2 MYK	446 439	100

8/3
1/B3
IP 20 / -
DB 5

100 pcs.

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²

0,08-4 mm²
0,08-2,5 mm²
0,5 mm²
AWG 28-12
9-10 mm
KT 2 (0,5x3,0)

Type	Cat.No.	Qty.
NPP 1 MYK	446 429	100
NPP 2 MYK	446 439	100

8/3
1/B3
IP 20 / -
DB 5

100 pcs.

Voltage, V ~	Current, A	Cross-Section
750	24	2,5 mm²

0,08-4 mm²
0,08-2,5 mm²
0,5 mm²
AWG 28-12
9-10 mm
KT 2 (0,5x3,0)


Type	Cat.No.	Qty.
NPP 1 MYK	446 429	100
NPP 2 MYK	446 439	100

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5



8/3
1/B3
IP 20 / -
DB 5

50 pcs.


YBK Series Double - Deck / Multilevel Terminals



YBK Series Spring Clamp Double Deck Rail Terminals are available in 2,5 - 4 mm² cross-section range. Double wiring density available without extension of mounting rails. Interconnection / shorting can be done at both levels. Special Marking solutions for each cross section can be provided by Plotter Labeling.




YBK Series Spring Clamp Multilevel Terminals make wiring more practical, reduce the installation costs and speed the wiring. Panels which exist switch lines & lightening, provide phase-neutral-Earth connection in one terminal. Are ideal for usage in industries where motors are working a lot, because of more practical wiring. Provide individual cross connections for each layer. Group marking carrier is used to provide more visual marking in base layer. Special Marking solutions for each cross section can be provided by Plotter Labeling.



Double - Deck Spring Clamp Terminals


YBK 2,5 - 2 F



Cat No:

- 316 109
- 316 100


YBK 2,5 - 2 FK



Cat No:

- 316 129
- 316 120


YBK 2,5 - 2 FD



Cat No:

- 316 219 / 229
- 316 210 / 220

YBK 2,5 - 2 FLD



Cat No:

- 316 319
- 316 310



Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Voltage, V ~	Current, A	Cross-Section
500	24	2,5 mm²
600	24	AWG 22-12

Voltage, V ~	Current, A	Cross-Section
500	24	2,5 mm²

Voltage, V ~	Current, A	Cross-Section
500	0,5	2,5 mm²

Voltage, V ~	Current, A	Cross-Section
	24	2,5 mm²

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

0,08-4 mm²
0,08-2,5 mm²
0,5 mm²
AWG 28-12
9-10 mm
KT 2 (0,5x3,0)

0,08-4 mm²
0,08-2,5 mm²
0,5 mm²
AWG 28-12
9-10 mm
KT 2 (0,5x3,0)

0,08-4 mm²
0,08-2,5 mm²
0,5 mm²
AWG 28-12
9-10 mm
KT 2 (0,5x3,0)

0,08-4 mm²
0,08-2,5 mm²
0,5 mm²
AWG 28-12
9-10 mm
KT 2 (0,5x3,0)

Ordering Data

Type	Cat.No.	Qty.
YBK 2,5-2 FD-A	316 219	30
YBK 2,5-2 FD-B	316 229	30

Type	Cat.No.	Qty.
YBK 2,5 FLD (24V AC)	316 319	30
YBK 2,5 FLD (24V DC)	316 329	30
YBK 2,5 FLD (48V AC)	316 419	30
YBK 2,5 FLD (48V DC)	316 429	30
YBK 2,5 FLD (110V AC)	316 619	30
YBK 2,5 FLD (110V DC)	316 629	30
YBK 2,5 FLD (220V AC)	316 719	30
YBK 2,5 FLD (220V DC)	316 729	30

Technical Data For Diode
Diode Reverse Voltage
Diode Current
Diod

1000 V
1 A
1 N 4007

1000 V
1 A
1 N 4007



Type	Cat.No.	Qty.
NPP YBK 2,5-2 F	446 299	10

Type	Cat.No.	Qty.
NPP YBK 2,5-2 F	446 299	10

Type	Cat.No.	Qty.
NPP YBK 2,5-2 F	446 299	10

Type	Cat.No.	Qty.
NPP YBK 2,5-2 F	446 299	10



Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5
Note: Only lower decks can be cross-connected		

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5
Note: Only lower decks can be cross-connected		

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5
Note: Only lower decks can be cross-connected		

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

8/3
1/A3
IP 20 / -
D_NS 5x6, DB 5, DG 6/5

8/3
1/A3
IP 20 / -
D_NS 5x6, DB 5, DG 6/5

8/3
1/A3
IP 20 / -
D_NS 5x6, DB 5, DG 6/5

8/3
1/A3
IP 20 / -
D_NS 5x6, DB 5, DG 6/5

Package Quantity
30 pcs.

30 pcs.

30 pcs.


--

30 pcs.

30 pcs.

Double - Deck Spring Clamp Terminals


YBK 4 - 2 F



Cat No:

- 318 109
- 318 100


YBK 4 - 2 FK



Cat No:

- 318 129
- 318 120


YBK 4 - 2 FD



Cat No:

- 318 219 / 229
- 318 210 / 220

YBK 4 - 2 FLD



Cat No:

- 318 319
- 318 310



Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Voltage, V ~	Current, A	Cross-Section
750	32	4 mm²
600	26	AWG 22-10

Voltage, V ~	Current, A	Cross-Section
750	32	4 mm²

Voltage, V ~	Current, A	Cross-Section
750	0,5	4 mm²

Voltage, V ~	Current, A	Cross-Section
	32	4 mm²

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

0,08-6 mm²
0,08-4 mm²
1 mm²
AWG 28-10
10-12 mm
KT 3 (0,6x3,5)

0,08-6 mm²
0,08-4 mm²
1 mm²
AWG 28-10
10-12 mm
KT 3 (0,6x3,5)

0,08-6 mm²
0,08-4 mm²
1 mm²
AWG 28-10
10-12 mm
KT 3 (0,6x3,5)

0,08-6 mm²
0,08-4 mm²
1 mm²
AWG 28-10
10-12 mm
KT 3 (0,6x3,5)

Ordering Data

Type	Cat.No.	Qty.
YBK 4-2 FLD (24V AC)	318 319	20
YBK 4-2 FLD (24V DC)	318 329	20
YBK 4-2 FLD (48V AC)	318 419	20
YBK 4-2 FLD (48V DC)	318 429	20
YBK 4-2 FLD (110V AC)	318 619	20
YBK 4-2 FLD (110V DC)	318 629	20
YBK 4-2 FLD (220V AC)	318 719	20
YBK 4-2 FLD (220V DC)	318 729	20

Technical Data For Diode
Diode Reverse Voltage
Diode Current
Diod

1000 V
1 A
1 N 4007

1000 V
1 A
1 N 4007



Type	Cat.No.	Qty.
NPP YBK 2,5-2 F	446 269	25

Type	Cat.No.	Qty.
NPP YBK 4-2 F	446 269	25

Type	Cat.No.	Qty.
NPP YBK 4-2 F	446 269	25

Type	Cat.No.	Qty.
NPP YBK 4-2 F	446 269	25



Type	Cat.No.	Qty.
UK 4/2	476 232	25
UK 4/3	476 233	20
UK 4/4	476 234	15
UK 4/10	476 239	5

Type	Cat.No.	Qty.
UK 4/2	476 232	25
UK 4/3	476 233	20
UK 4/4	476 234	15
UK 4/10	476 239	5
Note: Only lower decks can be cross-connected		

Type	Cat.No.	Qty.
UK 4/2	476 232	25
UK 4/3	476 233	20
UK 4/4	476 234	15
UK 4/10	476 239	5
Note: Only lower decks can be cross-connected		

Type	Cat.No.	Qty.
UK 4/2	476 232	25
UK 4/3	476 233	20
UK 4/4	476 234	15
UK 4/10	476 239	5
Note: Only lower decks can be cross-connected		

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

8/3
1/A4
IP 20 / -
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

8/3
1/A4
IP 20 / -
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

8/3
1/A4
IP 20 / -
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

8/3
1/A4
IP 20 / -
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

Package Quantity
50 pcs.

50 pcs.

20 pcs.


--

20 pcs.

20 pcs.

Spring Clamp
Multilevel Terminals


YBK 2,5 - 3 F



Cat No:

- 324 509
- 324 500


YBK 2,5 - 2 FT



Cat No:

- 324 809
- 324 800


YBK 2,5 - 3 FT



Cat No:

- 324 609
- 324 600


YBK 2,5 - 3 FLD (NPN)



Cat No:

- 324 739
- 324 730

YBK 2,5 - 3 FLD (PNP)



Cat No:

- 324 749
- 324 740



Electrical Ratings
CE (EN 60947-7-1 / EN 60947-7-2)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Voltage, V ~	Current, A	Cross-Section
500	24	2,5 mm²
600	20	AWG 22-12

Voltage, V ~	Current, A	Cross-Section
500	24	2,5 mm²
600	20	AWG 22-12

Voltage, V ~	Current, A	Cross-Section
500	24	2,5 mm²
600	20	AWG 22-12

Voltage, V ~	Current, A	Cross-Section
24	24	2,5 mm²

Voltage, V ~	Current, A	Cross-Section
24	24	2,5 mm²

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

0,08-4 mm²		
0,08-2,5 mm²		
0,5 mm²		
AWG 28-12		
9-10 mm		
KT 2 (0,5x3,0)		

0,08-4 mm²		
0,08-2,5 mm²		
0,5 mm²		
AWG 28-12		
9-10 mm		
KT 2 (0,5x3,0)		

0,08-4 mm²		
0,08-2,5 mm²		
0,5 mm²		
AWG 28-12		
9-10 mm		
KT 2 (0,5x3,0)		

0,08-4 mm²		
0,08-2,5 mm²		
0,5 mm²		
AWG 28-12		
9-10 mm		
KT 2 (0,5x3,0)		

0,08-4 mm²		
0,08-2,5 mm²		
0,5 mm²		
AWG 28-12		
9-10 mm		
KT 2 (0,5x3,0)		



Type	Cat.No.	Qty.
NPP YBK 2,5-3 F	446 249	10

Type	Cat.No.	Qty.
NPP YBK 2,5-2 T	446 299	10

Type	Cat.No.	Qty.
NPP YBK 2,5-3 FT	446 259	10

Type	Cat.No.	Qty.
NPP YBK 2,5-3 F	446 249	10

Type	Cat.No.	Qty.
NPP YBK 2,5-3 F	446 249	10

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

6/3
1/A3
IP 20 / -
D_NS 5x6, DB 5, DG 6/5

6/3
1/A3
IP 20 / -
D_NS 5x6, DB 5, DG 6/5

6/3
1/A3
IP 20 / -
D_NS 5x6, DB 5, DG 6/5

6/3
1/A3
IP 20 / -
D_NS 5x6, DB 5, DG 6/5

6/3
1/A3
IP 20 / -
D_NS 5x6, DB 5, DG 6/5

Package Quantity

30 pcs.

30 pcs.

20 pcs.


20 pcs.

20 pcs.



Sensor / Fuse / Disconnect Terminals




YBK Series Sensor Terminals are making sensor connections, which are often used in industry, more practical and esthetic. Provide individual cross connections for each layer, time saving in mounting process. Terminals can be used with NPN and PNP types of sensors. Special Marking solutions can be provided by Plotter Labeling.



Spring Clamp Fuse Terminals has a sliding type hinged carrier that has a specially designed space for cartridge type glass fuse of size Ø 5x20 or Ø 5x25 together with a spare one. Cross connection is available. Special Marking solutions can be provided by Plotter Labeling. LED alarm can be chosen, according to specified operating voltage of the product.




Spring Type Sensor Terminals

YBK 3 S

Cat No:

	324 709
	324 700


YBK 3 SLD (NPN)



Cat No:

324 719
324 710

YBK 3 SLD (PNP)



Cat No:

	324 729
	324 720



Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Voltage, V ~	Current, A	Cross-Section
500	24	2,5 mm²
500	24	AWG 22-12

Voltage, V ~	Current, A	Cross-Section
24	24	2,5 mm ²

Voltage, V ~	Current, A	Cross-Section
24	24	2,5 mm ²

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

0,08-4 mm ²
0,08-2,5 mm ²
0,5 mm ²
AWG 28-12
9-10 mm
KT 2 (0,5x3,0)

	0,08-4 mm ²
	0,08-2,5 mm ²
	0,5 mm ²
	AWG 28-12
	9-10 mm
	KT 2 (0,5x3,0)


	0,08-4 mm ²
	0,08-2,5 mm ²
	0,5 mm ²
	AWG 28-12
	9-10 mm
	KT 2 (0,5x3,0)

Type	Cat.No.	Qty.
NPP YBK 3 S	446 289	10

Type	Cat.No.	Qty.
NPP YBK 3 S	446 289	10

Type	Cat.No.	Qty.
NPP YBK 3 S	446 289	10

Push-in Cross Connection



Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group /
Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

6/3
1/A3
IP 20 / -
D_NS 5x6, DB 5, DG 6/5

6/3
1/A3
IP 20 / -
D_NS 5x6, DB 5, DG 6/5

6/3
1/A3
IP 20 / -
D_NS 5x6, DB 5, DG 6/5

Package Quantity

20 pcs.


20 pcs.

20 pcs.

Spring Clamp
Fuse and Disconnect
Terminals

YBK S

Width: 8 mm




Cat No:

- 355 119
- 325 110

YBK SB

Width: 8 mm




Cat No:

- 363 109
- 363 100

YBK SLD

Width: 8 mm




Cat No:

- 355 719
- 355 710

YBK 2,5 A

Width: 5 mm



Cat No:

- 353 209
- 353 200



Electrical Ratings
CE (EN 60947-7-1 / EN 60947-7-3)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

Ordering Data

End Plate


Push-in Cross Connection


Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Fuse / Fuse Type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity

Voltage, V ~	Current, A	Cross-Section
500	10	4 mm²
600	10	AWG 22-10

0,08-6 mm²
0,08-4 mm²
1 mm²
AWG 22-10
10-12 mm
KT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/YBK S	450 069	10

Type	Cat.No.	Qty.
UK 6/2	476 242	25
UK 6/3	476 243	20
UK 6/4	476 244	15
UK 6/10	476 249	5

6/3
1/A4
IP 20 / -
G/5x20 - 5x25 / Glass
D_NS 5x6, DB 5, DG 6/5

20 pcs.

Voltage, V ~	Current, A	Cross-Section
500	10	4 mm²
600	10	AWG 22-10

0,08-6 mm²
0,08-4 mm²
1 mm²
AWG 28-10
10-12 mm
KT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/YBK S	450 069	10

Type	Cat.No.	Qty.
UK 6/2	476 242	25
UK 6/3	476 243	20
UK 6/4	476 244	15
UK 6/10	476 249	5

6/3
1/A4
IP 20 / -
D_NS 5x6, DB 5, DG 6/5

20 pcs.

Voltage, V ~	Current, A	Cross-Section
	10	4 mm²
	10	AWG 22-10

0,08-6 mm²
0,08-4 mm²
1 mm²
AWG 28-10
10-12 mm
KT 3 (0,6x3,5)

Type	Cat.No.	Qty.
YBK SLD (24V AC)	355 719	20
YBK SLD (24V DC)	355 729	20
YBK SLD (48V AC)	355 739	20
YBK SLD (48V DC)	355 749	20
YBK SLD (110V AC)	355 759	20
YBK SLD (110V DC)	355 769	20
YBK SLD (220V AC)	355 779	20
YBK SLD (220V DC)	355 789	20

Type	Cat.No.	Qty.
NPP/YBK S	450 069	10

Type	Cat.No.	Qty.
UK 6/2	476 242	25
UK 6/3	476 243	20
UK 6/4	476 244	15
UK 6/10	476 249	5

6/3
1/A4
IP 20 / -
G/5x20 - 5x25 / Glass
D_NS 5x6, DB 5, DG 6/5

20 pcs.

Voltage, V ~	Current, A	Cross-Section
750	16	2,5 mm²
600	20	AWG 22-12

0,08-4 mm²
0,08-2,5 mm²
0,5 mm²
AWG 28-12
9-10 mm
KT 2 (0,5x3,0)

Type	Cat.No.	Qty.
NPP/YBK 2,5 A	450 219	10

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5


8/3
1/A3
IP 20 / -
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T

50 pcs.

Spring Clamp
Fuse and Disconnect
Terminals

YBK I

Width: 8 mm




Cat No:

- 355 129
- 355 120

YBK IB

Width: 8 mm




Cat No:

- 363 209
- 363 200

YBK ILD

Width: 8 mm



Cat No:

- 355 819
- 355 810



Electrical Ratings
CE (EN 60947-7-1/ EN 60947-7-3)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

Ordering Data

End Plate


Push-in Cross Connection


Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Fuse / Fuse Type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity

Voltage, V ~	Current, A	Cross-Section
500	10	4 mm²
600	10	AWG 22-10

0,08-6 mm²
0,08-4 mm²
1 mm²
AWG 28-10
10-12 mm
KT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/YBK S	450 069	10

Type	Cat.No.	Qty.
UK 6/2	476 242	25
UK 6/3	476 243	20
UK 6/4	476 244	15
UK 6/10	476 249	5

6/3
1/A4
IP 20 / -
G/6,35x31,75
D_NS 5x6, DB 5, DG 6/5

20 pcs.

Voltage, V ~	Current, A	Cross-Section
500	10	4 mm²
600	10	AWG 22-10

0,08-6 mm²
0,08-4 mm²
1 mm²
AWG 28-10
10-12 mm
KT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/YBK S	450 069	10

Type	Cat.No.	Qty.
UK 6/2	476 242	25
UK 6/3	476 243	20
UK 6/4	476 244	15
UK 6/10	476 249	5

6/3
1/A4
IP 20 / -
D_NS 5x6, DB 5, DG 6/5

20 pcs.

--

Voltage, V ~	Current, A	Cross-Section
	10	4 mm²
	10	AWG 22-10

0,08-6 mm²
0,08-4 mm²
1 mm²
AWG 28-10
10-12 mm
KT 3 (0,6x3,5)

Type	Cat.No.	Qty.
YBK ILD (24 VAC)	355 819	20
YBK ILD (24 VDC)	355 829	20
YBK ILD (48 VAC)	355 839	20
YBK ILD (48 VDC)	355 849	20
YBK ILD (110 VAC)	355 859	20
YBK ILD (110 VDC)	355 869	20
YBK ILD (220 VAC)	355 879	20
YBK ILD (220 VDC)	355 889	20

Type	Cat.No.	Qty.
NPP/YBK S	450 069	10

Type	Cat.No.	Qty.
UK 6/2	476 242	25
UK 6/3	476 243	20
UK 6/4	476 244	15
UK 6/10	476 249	5

6/3
1/A4
IP 20 / -
G/6,35x31,75
D_NS 5x6, DB 5, DG 6/5

20 pcs.

YBK Series Multi input/output Terminals





Spring Clamp one-level, multi input-output Terminals are suitable for usage in panels, with limited depth, where multilevel terminals cannot be used. Single-level terminals can be marked and cross-connected together with all other YBK series terminals; can be used together with test Terminals. Earth Terminals are available for same cross-sections and specifications. Special Marking solutions can be provided by Plotter Labeling. LED alarm can be chosen, according to specified operating voltage of the product.



One input - Two Output
Two input - Two Output
Spring Clamp
Terminals

YBK 2,5 E

Width: 5 mm



66,60

Cat No:


326 059

326 050


Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

End Plate

A 3D model of a rectangular plate with rounded ends and a central slot. It is shown from a perspective view, casting a shadow on the surface below it.

Push-in Cross Connection




Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group /
Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity

YBK 2,5 C

Width: 5 mm



81,40

Cat No:

326 109

326 100

Voltage, V ~	Current, A	Cross-Section
750	24	2,5 mm²
600	20	AWG 22-12

	0,08-4 mm ²
	0,08-2,5 mm ²
	0,5 mm ²
	AWG 28-12
	9-10 mm
	KT 2 (0,5x3,0)

Type	Cat.No.	Qty.
NPP/YBK 2,5 C	446 279	10


Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

8/3
1/A3
IP 20 / -
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T

	50 pcs.
--	---------

YBK 2,5 CX2

Width: 5 mm



81,40

Cat No:

326 209

326 200

Voltage, V ~	Current, A	Cross-Section
750	24	2,5 mm ²

	0,08-4 mm ²
	0,08-2,5 mm ²
	0,5 mm ²
	AWG 28-12
	9-10 mm
	KT 2 (0,5x3,0)

Type	Cat.No.	Qty.
NPP/YBK 2,5 C	446 279	25

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5


8/3
1/A3
IP 20 / -
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T

	50 pcs.

Two input - Two Output
Spring Clamp
Terminals

YBK 2,5 CD

Width: 5 mm




81,40

Cat No:

- 326 219
- 326 210

YBK 2,5 CLD

Width: 5 mm





81,40

Cat No:

- 326 319
- 326 310

YBK 2,5 CT

Width: 5 mm





81,40

Cat No:

- 336 100

YBK 2,5 ET

Width: 5 mm



66,60

Cat No:

- 336 110



Electrical Ratings
CE (EN 60947-7-1 - EN 60947-7-2)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Voltage, V ~	Current, A	Cross-Section
750	0,5	2,5 mm²

Voltage, V ~	Current, A	Cross-Section
24	24	2,5 mm²
	20	AWG 22-12

Voltage, V ~	Current, A	Cross-Section
		2,5 mm²
		AWG 22-12

Voltage, V ~	Current, A	Cross-Section
		2,5 mm²
		AWG 22-12

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

0,08-4 mm²
0,08-2,5 mm²
0,5 mm²
AWG 28-12
9-10 mm
KT2 (0,5x3,0)

0,08-4 mm²
0,08-2,5 mm²
0,5 mm²
AWG 28-12
9-10 mm
KT2 (0,5x3,0)

0,08-4 mm²
0,08-2,5 mm²
0,5 mm²
AWG 28-12
9-10 mm
KT2 (0,5x3,0)

0,08-4 mm²
0,08-2,5 mm²
0,5 mm²
AWG 28-12
9-10 mm
KT2 (0,5x3,0)

Ordering Data

Type	Cat.No.	Qty.
YBK 2,5 CLD (24V AC)	326 319	50
YBK 2,5 CLD (24V DC)	326 419	50
YBK 2,5 CLD (48V AC)	326 619	50
YBK 2,5 CLD (48V DC)	326 719	50
YBK 2,5 CLD (110V AC)	326 329	50
YBK 2,5 CLD (110V DC)	326 429	50
YBK 2,5 CLD (220V AC)	326 629	50
YBK 2,5 CLD (220V DC)	326 729	50

Technical Data For Diode
Diode Reverse Voltage
Diode Current
Diod

1000 V
1 A
1 N 4007

End Plate

Type	Cat.No.	Qty.
NPP/YBK 2,5 C	446 279	25

Type	Cat.No.	Qty.
NPP/YBK 2,5 C	446 279	25

Type	Cat.No.	Qty.
NPP/YBK 2,5 CT	446 272T	10

Type	Cat.No.	Qty.
NPP/YBK 2,5 E	446 212T	10

Cross Connection

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

Type	Cat.No.	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix
Package Quantity

8/3
1/A3
IP 20 / -
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T
50 pcs.

8/3
1/A3
IP 20 / -
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T
50 pcs.

8/3
1/A3
IP 20 / PE
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T
50 pcs.

8/3
1/A3
IP 20 / PE
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T
50 pcs.


“V0” Flammability Rating Product Range

Screw Type ‘V0’ Products

‘V0’ flammability rating Screw Terminal Blocks are ready in KLEMSAN Family for your prestigious projects! You can select the most suitable products from our premium ‘NM’ series as 108 products.

Complying EN 45545-2 European railway standard for fire safety classes R22-R23-R24-R26 for HL1 - HL2 - HL3 Hazard Levels.

Features	UL 94 V0	UL 94 V1	UL 94 V2
Self-extinguishing time after flame is applied to the sample (seconds).	≤ 10 sn	≤ 30 sn	≤ 30 sn
Total self-extinguishing time after 10 consecutive flame treatments.	≤ 50 sn	≤ 250 sn	≤ 250 sn
Is the sample burn completely?	No	No	No
Subject material which shouldn't ignite by dripping from the sample.	Cotton	Cotton	Paper




StoP Series Socket Type ‘V0’ Products

Klemsan StoP terminal blocks are highly recommended for LIFT / ELEVATOR INDUSTRY applications; also for RAILWAY TRANSPORTATION and MARINE INDUSTRIES as well.

Complying EN 45545-2 European railway standard for fire safety classes R22-R23-R24-R26 for HL1 - HL2 - HL3 Hazard Levels.

StoP series are compatible with SRD series. You can mount them in same rail side by side and you can use marking strip and push-in cross connection.




SRD Series Spring Type ‘V0’ Products

Brand new series spring clamp type terminal blocks are ready for your projects!

SRD Series are empowered terminal blocks compare with YBK series.


The thickness is 5,2 mm and the plastic bodies and rail legs are more ergonomic.

Complying EN 45545-2 European railway standard for fire safety classes R22-R23-R24-R26 for HL1 - HL2 - HL3 Hazard Levels.



AVK Series "V0" Terminals

AVK 2,5/NM



Cat No:

- 309 009
- 309 000

Electrical Ratings
CE (EN 60947-7-1)
UL - CuLus

Connection Data
Conductor cross section solid (min-max.)
Conductor cross section stranded (min-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min-max.)
Screwdriver


End Plate - Disconnect Plate
NPP/AVK 2,5-10/ NM
APP/AVK 2,5-10/ NM

Cross Connection
UK 2,5/2
UK 2,5/3
UK 2,5/4
UK 2,5/10

Comb Connector
TKO 2,5/2/NM
TKO 2,5/3/NM
TKO 2,5/4/NM
TKO 2,5/10/NM

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix
Package Quantity

AVK 4/NM



Cat No:

- 309 019
- 309 010

Electrical Ratings
750
600

Connection Data
Conductor cross section solid (min-max.)
Conductor cross section stranded (min-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min-max.)
Screwdriver


End Plate - Disconnect Plate
NPP/AVK 2,5-10/ NM
APP/AVK 2,5-10/ NM

Cross Connection
UK 4/2
UK 4/3
UK 4/4
UK 4/10
UK 4/20

Comb Connector
TKO 4/2/NM
TKO 4/3/NM
TKO 4/4/NM
TKO 4/10/NM

Technical Data
8/3
1/A4
IP 20 / -
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T
Package Quantity

AVK 6/NM



Cat No:

- 309 029
- 309 020

Electrical Ratings
630
600

Connection Data
Conductor cross section solid (min-max.)
Conductor cross section stranded (min-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min-max.)
Screwdriver


End Plate - Disconnect Plate
NPP/AVK 2,5-10/ NM
APP/AVK 2,5-10/ NM

Cross Connection
UK 6/2
UK 6/3
UK 6/4
UK 6/10

Comb Connector
TKO 6/2/NM
TKO 6/3/NM
TKO 6/4/NM
TKO 6/10/NM

Technical Data
8/3
1/B5
IP 20 / -
D_NS 8x10, DG 10/8
Package Quantity

AVK 10/NM



Cat No:

- 309 039
- 309 030

Electrical Ratings
630
600

Connection Data
Conductor cross section solid (min-max.)
Conductor cross section stranded (min-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min-max.)
Screwdriver


End Plate - Disconnect Plate
NPP/AVK 2,5-10/ NM
APP/AVK 2,5-10/ NM

Cross Connection
UK 10/2
UK 10/3
UK 10/4
UK 10/10

Comb Connector
TKO 10/2/NM
TKO 10/3/NM
TKO 10/4/NM
TKO 10/10/NM

Technical Data
8/3
1/B6
IP 20 / -
D_NS 10x10, DG 10/10
Package Quantity

AVK 16 RD/NM



Cat No:

- 309 059
- 309 050

Electrical Ratings
750
600

Connection Data
Conductor cross section solid (min-max.)
Conductor cross section stranded (min-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min-max.)
Screwdriver

End Plate - Disconnect Plate
NPP/AVK 16 RD/ NM
APP/AVK 16 RD/ NM


Cross Connection
UK 16/2
UK 16/3
UK 16/4
UK 16/10

Comb Connector
TKO 10/2/NM
TKO 10/3/NM
TKO 10/4/NM
TKO 10/10/NM

Technical Data
8/3
1/B7
IP 20 / -
D_NS 10x10, D_NS 12x10, DG 10x10
Package Quantity

AVK Series "V0" Terminals

AVK 35 RDS/NM



Cat No:

- 309 089
- 309 080

Electrical Ratings
CE (EN 60947-7-1)
UL - CuLus

Connection Data
Conductor cross section solid (min-max.)
Conductor cross section stranded (min-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min-max.)
Screwdriver

End Plate - Disconnect Plate


Cross Connection

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
50 pcs.

* Higher torque value compare to AVK 35 RD

AVK 4 A/NM



Cat No:

- 309 179
- 309 170

Voltage, V ~	Current, A	Cross-Section
500	20	4 mm²
300	16	AWG 26-10

Conductor cross section solid (min-max.)	0,2-6 mm²
Conductor cross section stranded (min-max.)	0,2-6 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)	0,5-2,5 mm²
AWG Conductor	AWG 24-10
Insulation Stripping Length (min.-max.)	9-10 mm
Torque (min-max.)	0,5-0,8 Nm
Screwdriver	IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/AVK 4 R-A/ NM	451 319	25


Type	Cat.No.	Qty.
UK 4/2/NM	470 312	25
UK 4/3/NM	470 313	20
UK 4/4/NM	470 314	15
UK 4/10/NM	470 319	5

Technical Data
8/3
1/A4
IP 20 / -
Marking Tags (Dekafix)
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T, SLF-P1 W

Package Quantity
50 pcs.

AVK RD Series "V0" Terminals

AVK 2,5 RD/NM



Cat No:

- 309 159
- 309 150

Electrical Ratings
CE (EN 60947-7-1)
UL - CuLus
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min-max.)
Conductor cross section stranded (min-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min-max.)
Screwdriver

End Plate - Disconnect Plate


Cross Connection

Comb Connector

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
100 pcs.

AVK 4 RD/NM



Cat No:

- 309 169
- 309 160

Voltage, V ~	Current, A	Cross-Section
750	32	4 mm²
600	30	AWG 26-10

Conductor cross section solid (min-max.)	0,2-6 mm²
Conductor cross section stranded (min-max.)	0,2-6 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)	0,5-2,5 mm²
AWG Conductor	AWG 24-10
Insulation Stripping Length (min.-max.)	9-10 mm
Torque (min-max.)	0,5-0,8 Nm
Screwdriver	IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/AVK 2,5-10/NM	451 069	100
APP/AVK 2,5-10/NM	464 059	25

Type	Cat.No.	Qty.
UK 4/2/NM	470 312	25
UK 4/3/NM	470 313	20
UK 4/4/NM	470 314	15
UK 4/10/NM	470 319	5

Type	Cat.No.	Qty.
TKO 4/2/NM	470 342	25
TKO 4/3/NM	470 343	20
TKO 4/4/NM	470 344	15
TKO 4/10/NM	470 349	5


Technical Data
8/3
1/A4
IP 20 / -
Marking Tags (Dekafix)
DB 10/5, DG 10/5, DG 10/5T

Package Quantity
100 pcs.

Color							
Color code is the last digit of the order number							
Blue	Green	Yellow	Red	Black	White	Orange	Brown
1	2	3	4	5	6	7	8

AVK T Series "V0"
Earth Terminals


AVK 2,5 / 4 TK/NM



Cat No:

341 010


AVK 6 TK/NM



Cat No:

341 020


AVK 10 TK/NM



Cat No:

341 030

AVK 16 T RD/NM



Cat No:

341 040



Electrical Ratings
CE (EN 60947-7-2)
UL - CuLus

Connection Data
Conductor cross section solid (min-max.)
Conductor cross section stranded (min-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min-max.)
Rail Tightening torque, (min-max.)
Screwdriver

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
50 pcs.

Voltage, V ~	Current, A	Cross-Section
		2,5-4 mm ²
		AWG 26-10

0,2-6 mm ²
0,2-6 mm ²
0,5-2,5 mm ²
AWG 24-10
9-10 mm
0,5-0,8 Nm
0,4-0,6 Nm
IKT 3 (0,6x3,5)

8/3
1/A4
IP 20 / PE
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

50 pcs.

Voltage, V ~	Current, A	Cross-Section
		6 mm ²
		AWG 26-8

0,2-10 mm ²
0,2-10 mm ²
0,5-4 mm ²
AWG 24-8
10-12 mm
0,8-1,2 Nm
0,6 -0,8 Nm
IKT 4 (0,8x4)

8/3
1/B5
IP 20 / PE
D_NS 8x10, DG 10/8

25 pcs.

Voltage, V ~	Current, A	Cross-Section
		10 mm ²
		AWG 16-6

0,5-16 mm ²
0,5-16 mm ²
0,5-6 mm ²
AWG 20-6
10-12 mm
1,2-1,8 Nm
0,8-1,0 Nm
IKT 4 (1,2x6,5)

8/3
1/B6
IP 20 / PE
D_NS 10x10, DG 10/10

25 pcs.

Voltage, V ~	Current, A	Cross-Section
		16 mm ²
		AWG 12-4


1,5-25 mm ²
1,5-25 mm ²
0,75-10 mm ²
AWG 16-4
12-14 mm
1,2-2,0 Nm
1,0-1,2 Nm
IKT 5 (1,2x6,5)

8/3
1/B7
IP 20 / PE
D_NS 10x10, D_NS 12x10, DG 10/10

50 pcs.

AVK T Series "V0"
Earth Terminals


AVK 35 T RDS/NM



Cat No:

341 060


AVK 2,5 T RD/NM



Cat No:

341 090

AVK 4 T RD/NM



Cat No:

341 100



Electrical Ratings
CE (EN 60947-7-2)
UL - CuLus

Connection Data
Conductor cross section solid (min-max.)
Conductor cross section stranded (min-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min-max.)
Rail Tightening torque, (min-max.)
Screwdriver

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity

Voltage, V ~	Current, A	Cross-Section
		35 mm²
		AWG 10-2

6-50 mm²
6-35 mm²
4-16 mm²
AWG 10-2
16-18 mm
4,0-6,0 Nm
1,2-1,5 Nm
IKT 6 (1,2x6,5)

8/3
1/B9
IP 20 / PE
D_NS 10x10, D_NS 14x10, DG 10/10

25 pcs.

Voltage, V ~	Current, A	Cross-Section
		2,5 mm²
		AWG 26-12

0,2-4 mm²
0,2-4 mm²
0,5-1,5 mm²
AWG 24-12
9-10 mm
0,4-0,6 Nm
IKT 3 (0,6x3,5)

8
1/A3
IP 20 / PE
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T

50 pcs.

--

Voltage, V ~	Current, A	Cross-Section
		4 mm²
		AWG 26-10


0,2-6 mm²
0,2-6 mm²
0,5-2,5 mm²
AWG 24-10
9-10 mm
0,5-0,8 Nm
IKT 3 (0,6x3,5)

8
1/A4
IP 20 / PE
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

50 pcs.

Screw Type "V0"
Double - Deck
Terminals


PIK 2,5 N/NM



Cat No:

- 309 189
- 309 180


PIK 2,5 RD/NM



Cat No:

- 309 429
- 309 420


PIK 2,5 NK/NM



Cat No:

- 309 199
- 309 190


PIK 2,5 RDK/NM



Cat No:

- 309 439
- 309 430


PIK 2,5 ND/NM



Cat No:

- 315 049
- 315 040

PIK 2,5 NLD/NM



Cat No:

- 309 229
- 309 220

Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min.-max.)
Screwdriver

Ordering Data

Technical Data For Diode
Diode Voltage
Diode Current
Diod

End Plate

Small Partition

Cross Connection

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity

Voltage, V ~	Current, A	Cross-Section
500	24	2,5 mm²
300	20	AWG 26-12

	0,2-4 mm²
	0,2-4 mm²
	0,5-1,5 mm²
	AWG 24-12
	9-10 mm
	0,4-0,6 Nm
	IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/PIK 2,5-4 N/NM	451 309	25

Type	Cat.No.	Qty.
AD 1	467 919	100

Type	Cat.No.	Qty.
UK 2,5/2	474 122	25
UK 2,5/3	474 123	20
UK 2,5/4	474 124	15
UK 2,5/10	474 129	5

Type	Cat.No.	Qty.
AD 1	467 919	100

Type	Cat.No.	Qty.
UK 2,5/2	474 122	25
UK 2,5/3	474 123	20
UK 2,5/4	474 124	15
UK 2,5/10	474 129	5

6/3
1/A3
IP 20 / -
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T

100 pcs.

Voltage, V ~	Current, A	Cross-Section
500	24	2,5 mm²
300	20	AWG 26-12

	0,2-4 mm²
	0,2-4 mm²
	0,5-1,5 mm²
	AWG 24-12
	9-10 mm
	0,4-0,6 Nm
	IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/PIK 2,5-4 N/NM	451 309	25

Type	Cat.No.	Qty.
AD 1	467 919	100

Type	Cat.No.	Qty.
UK 2,5/2	474 122	25
UK 2,5/3	474 123	20
UK 2,5/4	474 124	15
UK 2,5/10	474 129	5

Type	Cat.No.	Qty.
AD 1	467 919	100

Type	Cat.No.	Qty.
UK 2,5/2	474 122	25
UK 2,5/3	474 123	20
UK 2,5/4	474 124	15
UK 2,5/10	474 129	5

6/3
1/A3
IP 20 / -
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T

100 pcs.

Voltage, V ~	Current, A	Cross-Section
500	24	2,5 mm²
300	20	AWG 26-12

	0,2-4 mm²
	0,2-4 mm²
	0,5-1,5 mm²
	AWG 24-12
	9-10 mm
	0,4-0,6 Nm
	IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/PIK 2,5-4 N/NM	451 309	25

Type	Cat.No.	Qty.
AD 1	467 919	100

Type	Cat.No.	Qty.
UK 2,5/2	474 122	25
UK 2,5/3	474 123	20
UK 2,5/4	474 124	15
UK 2,5/10	474 129	5

Type	Cat.No.	Qty.
AD 1	467 919	100

Type	Cat.No.	Qty.
UK 2,5/2	474 122	25
UK 2,5/3	474 123	20
UK 2,5/4	474 124	15
UK 2,5/10	474 129	5

6/3
1/A3
IP 20 / -
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T

20 pcs.

Voltage, V ~	Current, A	Cross-Section
500	24	2,5 mm²
300	20	AWG 26-12

	0,2-4 mm²
	0,2-4 mm²
	0,5-1,5 mm²
	AWG 24-12
	9-10 mm
	0,4-0,6 Nm
	IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/PIK 2,5-4 N/NM	451 309	25

Type	Cat.No.	Qty.
AD 1	467 919	100

Type	Cat.No.	Qty.
UK 2,5/2	474 122	25
UK 2,5/3	474 123	20
UK 2,5/4	474 124	15
UK 2,5/10	474 129	5

Type	Cat.No.	Qty.
AD 1	467 919	100

Type	Cat.No.	Qty.
UK 2,5/2	474 122	25
UK 2,5/3	474 123	20
UK 2,5/4	474 124	15
UK 2,5/10	474 129	5

Note: Only lower decks can be cross-connected

6/3
1/A3
IP 20 / -
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T

20 pcs.

Voltage, V ~	Current, A	Cross-Section
500	24	2,5 mm²
300	20	AWG 26-12

	0,2-4 mm²
	0,2-4 mm²
	0,5-1,5 mm²
	AWG 24-12
	9-10 mm
	0,4-0,6 Nm
	IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/PIK 2,5-4 N/NM	451 309	25

Type	Cat.No.	Qty.
AD 1	467 919	100

Type	Cat.No.	Qty.
UK 2,5/2	474 122	25
UK 2,5/3	474 123	20
UK 2,5/4	474 124	15
UK 2,5/10	474 129	5

Type	Cat.No.	Qty.
AD 1	467 919	100

Type	Cat.No.	Qty.
UK 2,5/2	474 122	25
UK 2,5/3	474 123	20
UK 2,5/4	474 124	15
UK 2,5/10	474 129	5

Note: Only lower decks can be cross-connected

6/3
1/A3
IP 20 / -
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T

100 pcs.

Voltage, V ~	Current, A	Cross-Section
500	0,5	2,5 mm²
300	20	AWG 26-12

	0,2-4 mm²
	0,2-4 mm²
	0,5-1,5 mm²
	AWG 24-12
	9-10 mm
	0,4-0,6 Nm
	IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
PIK 2,5 ND A/NM	315 049	20
PIK 2,5 ND B/NM	315 059	20

Type	Cat.No.	Qty.
AD 1	467 919	100

Type	Cat.No.	Qty.
UK 2,5/2	474 122	25
UK 2,5/3	474 123	20
UK 2,5/4	474 124	15
UK 2,5/10	474 129	5

Type	Cat.No.	Qty.
AD 1	467 919	100

Type	Cat.No.	Qty.
UK 2,5/2	474 122	25
UK 2,5/3	474 123	20
UK 2,5/4	474 124	15
UK 2,5/10	474 129	5

Note: Only lower decks can be cross-connected

6/3
1/A3
IP 20 / -
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T

20 pcs.

Voltage, V ~	Current, A	Cross-Section
	24	2,5 mm²
	20	AWG 26-12

	0,2-4 mm²
	0,2-4 mm²
	0,5-1,5 mm²
	AWG 24-12
	9-10 mm
	0,4-0,6 Nm
	IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
PIK 2,5 NLD/NM (24AC)	309 229	20
PIK 2,5 NLD/NM (24DC)	309 239	20
PIK 2,5 NLD/NM (48AC)	309 249	20
PIK 2,5 NLD/NM (48DC)	309 259	20
PIK 2,5 NLD/NM (110AC)	309 269	20
PIK 2,5 NLD/NM (110DC)	309 279	20
PIK 2,5 NLD/NM (220AC)	309 289	20
PIK 2,5 NLD/NM (220DC)	309 299	20

Type	Cat.No.	Qty.
AD 1	467 919	100

Type	Cat.No.	Qty.
UK 2,5/2	474 122	25
UK 2,5/3	474 123	20
UK 2,5/4	474 124	15
UK 2,5/10	474 129	5

Type	Cat.No.	Qty.
AD 1	467 919	100

Type	Cat.No.	Qty.
UK 2,5/2	474 122	25
UK 2,5/3	474 123	20
UK 2,5/4	474 124	15
UK 2,5/10	474 129	5


Note: Only lower decks can be cross-connected

6/3
1/A3
IP 20 / -
D_NS 5x10, DB 10/5, DG 10/5, DG 10/5T

20 pcs.

Screw Type "V0"
Multilevel
Terminals


PUK 3/NM



Cat No:

- 309 479
- 309 470


PUK 2 T/NM



Cat No:

- 309 469
- 309 460

PUK 3 T/NM



Cat No:

- 309 489
- 309 480



Electrical Ratings
CE (EN 60947-7-1 - EN 60947-7-2)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Voltage, V ~	Current, A	Cross-Section
440	24	2,5 mm²
600	24	AWG 24-12

Voltage, V ~	Current, A	Cross-Section
440	24	2,5 mm²
600	24	AWG 24-12

Voltage, V ~	Current, A	Cross-Section
440	24	2,5 mm²
600	24	AWG 24-12

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min.-max.)
Screwdriver

0,2-4 mm²
0,2-4 mm²
0,5-1,5 mm²
AWG 24-12
7-8 mm
0,4-0,6 Nm
IKT 3 (0,6x3,5)

0,2-4 mm²
0,2-4 mm²
0,5-1,5 mm²
AWG 24-12
7-8 mm
0,4-0,6 Nm
IKT 3 (0,6x3,5)

0,2-4 mm²
0,2-4 mm²
0,5-1,5 mm²
AWG 24-12
7-8 mm
0,4-0,6 Nm
IKT 3 (0,6x3,5)



Type	Cat.No.	Qty.
NPP/PUK 3/NM	351 339	10

Type	Cat.No.	Qty.
NPP/PUK 2 T/NM	451 329	10

Type	Cat.No.	Qty.
NPP/PUK 3 T/NM	351 349	10



Type	Cat.No.	Qty.
UK 2,5/2	480 132	25
UK 2,5/3	480 133	20
UK 2,5/4	480 134	15
UK 2,5/10	480 139	5
UK 2,5/35	480 140	5

Type	Cat.No.	Qty.
UK 2,5/2	480 132	25
UK 2,5/3	480 133	20
UK 2,5/4	480 134	15
UK 2,5/10	480 139	5
UK 2,5/35	480 140	5

Type	Cat.No.	Qty.
UK 2,5/2	480 132	25
UK 2,5/3	480 133	20
UK 2,5/4	480 134	15
UK 2,5/10	480 139	5
Note: Only upper decks can be cross-connected		

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

6/3
1/A3
IP 20 / -
DB 5

6/3
1/A3
IP 20 / PE
DB 5

6/3
1/A3
IP 20 / PE
DB 5

Package Quantity

20 pcs.


20 pcs.

--

20 pcs.

Screw Type "V0"
Sensor Terminals


PUK 3 S/NM



Cat No:

- 309 499
- 309 490


PUK 3 SLD (NPN)/NM



Cat No:

- 309 509
- 309 500

PUK 3 SLD (PNP)/NM



Cat No:

- 309 519
- 309 510



Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min.-max.)
Screwdriver

End Plate


Cross Connection


Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
20 pcs.

Voltage, V ~	Current, A	Cross-Section
500	24	2,5 mm²
300	20	AWG 24-12

0,2-4 mm²
0,2-4 mm²
0,5-1,5 mm²
AWG 24-12
7-8 mm
0,4-0,6 Nm
IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/PUK 3 S/NM	351 359	10

Type	Cat.No.	Qty.
UK 2,5/2	480 132	25
UK 2,5/3	480 133	20
UK 2,5/4	480 134	15
UK 2,5/10	480 139	5
UK 2,5/35	480 140	5

6/3
1/A3
IP 20 / -
DB 5

20 pcs.

Voltage, V ~	Current, A	Cross-Section
24	24	2,5 mm²
300	20	AWG 24-12

0,2-4 mm²
0,2-4 mm²
0,5-1,5 mm²
AWG 24-12
7-8 mm
0,4-0,6 Nm
IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/PUK 3 S/NM	351 359	10

Type	Cat.No.	Qty.
UK 2,5/2	480 132	25
UK 2,5/3	480 133	20
UK 2,5/4	480 134	15
UK 2,5/10	480 139	5
UK 2,5/35	480 140	5

6/3
1/A3
IP 20 / -
DB 5

20 pcs.

--

Voltage, V ~	Current, A	Cross-Section
24	24	2,5 mm²
300	20	AWG 24-12

0,2-4 mm²
0,2-4 mm²
0,5-1,5 mm²
AWG 24-12
7-8 mm
0,4-0,6 Nm
IKT 3 (0,6x3,5)

Type	Cat.No.	Qty.
NPP/PUK 3 S/NM	351 359	10


Type	Cat.No.	Qty.
UK 2,5/2	480 132	25
UK 2,5/3	480 133	20
UK 2,5/4	480 134	15
UK 2,5/10	480 139	5
UK 2,5/35	480 140	5

6/3
1/A3
IP 20 / PE
DB 5

20 pcs.

WGO Series "V0"
Test / Disconnect
Terminals

WGO 3/NM



Cat No:

- 309 569
- 309 560



Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min.-max.)
Screwdriver

Ordering Data
Without Socket - Beige / Grey
One Socket - Beige / Grey
Double Socket - Beige / Grey
One Test Socket - Beige / Grey
Double Test Socket - Beige / Grey

End Plate

Cross Connection

Test Plug
suitable for test socket types

Comb Connector

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
50 pcs.

Voltage, V ~	Current, A	Cross-Section
400	41	6 mm²
300	43	AWG 20-8

	0,2-10 mm²
	0,2-10 mm²
	0,5-4 mm²
	AWG 24-8
	10-12 mm
	0,8-1,2 Nm
	IKT 4 (0,8x4,0)

Type	Cat.No.	Qty.
WGO 3/NM	309 529 - 520	50
WGO 3/NM	309 539 - 530	50
WGO 3/NM	309 549 - 540	50
WGO 3/NM	309 559 - 550	50
WGO 3/NM	309 569 - 560	50

Type	Cat.No.	Qty.
NPP/WGO 3/NM	351 369	25


Type	Cat.No.	Qty.
IZUK 6/2/NM	470 372	10
IZUK 6/3/NM	470 373	10
IZUK 6/4/NM	470 374	10
IZUK 6/6/NM	470 376	10
IZUK 6/10/NM	470 379	5
WGO UAA	498 300	1

Type	Cat.No.	Qty.
TF (Ø4)	493 050	10

Type	Cat.No.	Qty.
TKO 6/2/NM	470 352	25
TKO 6/3/NM	470 353	20
TKO 6/4/NM	470 354	15
TKO 6/10/NM	470 359	5

6/3
1/B5
IP 20 / -
D_NS 8x10, DG 10/8

WGO 4/NM



Cat No:

- 309 589
- 309 580

Voltage, V ~	Current, A	Cross-Section
1000	41	6 mm²
300	48	AWG 26-8

	0,2-10 mm²
	0,2-10 mm²
	0,5-4 mm²
	AWG 24-8
	10-12 mm
	0,8-1,0 Nm
	IKT 4 (0,8x4,0)

Type	Cat.No.	Qty.
WGO 4/NM	309 579 - 570	50

Type	Cat.No.	Qty.

Type	Cat.No.	Qty.
IZUK 6/2/NM	470 372	10
IZUK 6/3/NM	470 373	10
IZUK 6/4/NM	470 374	10
IZUK 6/6/NM	470 376	10
IZUK 6/10/NM	470 379	5

Type	Cat.No.	Qty.
TF (Ø4)	493 050	10


Type	Cat.No.	Qty.
UK 6/2/NM	470 322	25
UK 6/3/NM	470 323	20
UK 6/4/NM	470 324	15
UK 6/10/NM	470 329	5

6/3
1/B5
IP 20 / -
D_NS 8x10, DG 10/8, SLF-P1 W

50 pcs.

WGO 6 Series "V0"
Test / Disconnect
Terminals

new WGO 6/NM



Cat No:

- 309 609
- 309 600



Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
AWG Conductor
Torque
Hole Diameter
Bolt Diameter
Screwdriver

Cross Connection

Plastic Lock
Grey Orange

Coding Plastic
Orange Blue Green Yellow Red Black

Test Plug

Cross Connection Holder

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
50 pcs.

Voltage, V ~	Current, A	Cross-Section
1000	41	6 mm²
600	50	AWG 24-8

	0,2-10 mm²
	0,2-10 mm²
	AWG 24-8
	0,8-1,0 Nm
	10 mm
	B5
	IKT 4 (0,8x4)

Type	Cat.No.	Qty.
CS 6/2	470 122	25
CS 6/3	470 123	20
CS 6/4	470 124	15
CS 6/5	470 125	10
CS 6/10	470 129	5
SCS 6/2	470 172	25
SCS 6/3	470 173	20
SCS 6/4	470 174	15

Type	Cat.No.	Qty.
WGO 6_PK	469 079	50
WGO 6_PK	469 077	50

Type	Cat.No.	Qty.
WGO 6_KP	469 067	50
WGO 6_KP	469 061	50
WGO 6_KP	469 062	50
WGO 6_KP	469 063	50
WGO 6_KP	469 064	50
WGO 6_KP	469 065	50


Type	Cat.No.	Qty.
TFØ4	493 050	10

Type	Cat.No.	Qty.
ATCS 6	499 559	20

6/3
1/NA
IP 20 / -
D-NS 8x10, DG 10/8, SLF-P1 W

50 pcs.

new WGO D6/NM



Cat No:

- 309 619
- 309 610

Voltage, V ~	Current, A	Cross-Section
1000	41	6 mm²
600	50	AWG 24-8

	0,2-10 mm²
	0,2-10 mm²
	AWG 24-8
	0,8-1,0 Nm
	10 mm
	B5
	IKT 4 (0,8x4)

Type	Cat.No.	Qty.
CS 6/2	470 122	25
CS 6/3	470 123	20
CS 6/4	470 124	15
CS 6/5	470 125	10
CS 6/10	470 129	5
SCS 6/2	470 172	25
SCS 6/3	470 173	20
SCS 6/4	470 174	15

Type	Cat.No.	Qty.

Type	Cat.No.	Qty.
WGO 6_KP	469 067	50
WGO 6_KP	469 061	50
WGO 6_KP	469 062	50
WGO 6_KP	469 063	50
WGO 6_KP	469 064	50
WGO 6_KP	469 065	50

Type	Cat.No.	Qty.
TFØ4	493 050	10



Type	Cat.No.	Qty.
ATCS 6	499 559	20

6/3
1/NA
IP 20 / -
D-NS 8x10, DG 10/8, SLF-P1 W

50 pcs.

WGO PB Series "V0"
Test / Disconnect
Terminals

WGO PB 6/NM



Cat No:

- 308 069
- 308 060

Table with 1 column: Electrical Ratings. Rows include CE (EN 60947-7-1), UL, VDE (IEC 60947-7-1), CSA, and ATEX.

Table with 2 columns: Connection Data. Rows include Conductor cross section solid (min.-max.), Conductor cross section stranded (min.-max.), AWG Conductor, Torque, Hole Diameter, Bolt Diameter, and Screwdriver.





Table with 2 columns: Comb Connector/Ring Type. Includes images of the connectors and their specifications.

Table with 1 column: Test Plug. Includes image and specifications.

Table with 2 columns: Technical Data. Rows include Rated Impulse Voltage / Pollution severity, Insulation material group / Gauge pin code according to IEC 60947-1, Protection class / Protection conductor type, Marking Tags (Dekafix), and See pages 326-333 for a list of Dekafix.

Table with 1 column: Package Quantity. Row shows 25 pcs.

WGO PBD 6/NM



Cat No:

- 308 079
- 308 070

Table with 1 column: Electrical Ratings. Rows include CE (EN 60947-7-3), UL, VDE (IEC 60947-7-1), CSA, and ATEX.

Table with 2 columns: Connection Data. Rows include Conductor cross section solid (min.-max.), Conductor cross section stranded (min.-max.), AWG Conductor, Torque, Hole Diameter, Bolt Diameter, and Screwdriver.

Table with 6 columns: End Plate. Rows include NPP/WGO PB 6 and APP/WGO PB 6 with Cat.No. and Qty.

Table with 6 columns: Comb Connector/Ring Type. Rows include TKO PB 6/2, TKO PB 6/3, TKO PB 6/4, TKO PB 6/7, and TKO PB 6/10 with Cat.No. and Qty.



Table with 1 column: Test Plug. Includes image and specifications.

Table with 2 columns: Technical Data. Rows include Rated Impulse Voltage / Pollution severity, Insulation material group / Gauge pin code according to IEC 60947-1, Protection class / Protection conductor type, Marking Tags (Dekafix), and See pages 326-333 for a list of Dekafix.

Table with 1 column: Package Quantity. Row shows 25 pcs.

Screw Type "V0"
Fuse Terminals

ASK 5/NM



Cat No:

- 315 009

Table with 1 column: Electrical Ratings. Rows include CE (EN 60947-7-3), UL, VDE (IEC 60947-7-1), CSA, and ATEX.

Table with 2 columns: Connection Data. Rows include Conductor cross section solid (min.-max.), Conductor cross section stranded (min.-max.), 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.), AWG Conductor, Insulation Stripping Length (min.-max.), Torque (min.-max.), and Screwdriver.


Table with 1 column: Ordering Data. Includes image and specifications.

Table with 2 columns: Push-in Cross Connection. Includes image and specifications.

Table with 2 columns: Technical Data. Rows include Rated Impulse Voltage / Pollution severity, Insulation material group / Gauge pin code according to IEC 60947-1, Protection class / Protection conductor type, Fuse / Fuse Type, Marking Tags (Dekafix), and See pages 326-333 for a list of Dekafix.

Table with 1 column: Package Quantity. Row shows 50 pcs.

ASK 5 LD/NM



Cat No:

- 315 019

Table with 1 column: Electrical Ratings. Rows include CE (EN 60947-7-3), UL, VDE (IEC 60947-7-1), CSA, and ATEX.

Table with 2 columns: Connection Data. Rows include Conductor cross section solid (min.-max.), Conductor cross section stranded (min.-max.), 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.), AWG Conductor, Insulation Stripping Length (min.-max.), Torque (min.-max.), and Screwdriver.

Table with 6 columns: Ordering Data. Rows include ASK 5 LD/NM 24V AC/DC, ASK 5 LD /NM 110V AC/DC, and ASK 5 LD /NM 220V AC/DC with Cat.No. and Qty.


Table with 6 columns: Push-in Cross Connection. Rows include UK 6/2/NM, UK 6/3/NM, UK 6/4/NM, and UK 6/10/NM with Cat.No. and Qty.

Table with 2 columns: Technical Data. Rows include Rated Impulse Voltage / Pollution severity, Insulation material group / Gauge pin code according to IEC 60947-1, Protection class / Protection conductor type, Fuse / Fuse Type, Marking Tags (Dekafix), and See pages 326-333 for a list of Dekafix.

Table with 1 column: Package Quantity. Row shows 50 pcs.

PB Series "V0"
Feed Through and
Earth Terminals


PB 2,5/NM



Cat No:

308 029


PB 2,5K/NM



Cat No:

308 039


PB 2,5T/NM



Cat No:

337 010


PB 6/NM



Cat No:

308 009

PB 6K/NM



Cat No:

308 019



Electrical Ratings
CE (EN 60947-7-1 / EN 60947-7-2)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20/15	AWG 26-14
600	20/15	AWG 26-14

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20/15	AWG 26-14
600	20/15	AWG 26-14

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²
600	20/15	AWG 26-14
600	20/15	AWG 26-14

Voltage, V ~	Current, A	Cross-Section
800	41	6 mm²
600	45	AWG 22-8
600	45	AWG 22-8

Voltage, V ~	Current, A	Cross-Section
800	41	6 mm²
600	45	AWG 22-8
600	45	AWG 22-8

Voltage, V ~	Current, A	Cross-Section
800	41	6 mm²
600	45	AWG 22-8
600	45	AWG 22-8

Connection Data
Conductor cross section solid (min-max.)
Conductor cross section stranded (min.-max.)
AWG Conductor
Torque (min-max.)
Hole Diameter
Bolt Diameter
Screwdriver
Rail Tightening torque, min-max.

Type	Cat.No.	Qty.
NPP/PB 2,5/NM	451 029	25
APP/PB 2,5-6/NM	464 009	25

Type	Cat.No.	Qty.
NPP/PB 2,5/NM	451 029	25
APP/PB 2,5-6/NM	464 009	25

Type	Cat.No.	Qty.
NPP/PB 2,5/NM	451 029	25
APP/PB 2,5-6/NM	464 009	25

Type	Cat.No.	Qty.
NPP / PB 6/NM	451 019	25
APP / PB 2,5-6/NM	464 009	25

Type	Cat.No.	Qty.
NPP / PB 6/NM	451 019	25
APP / PB 2,5-6/NM	464 009	25

Type	Cat.No.	Qty.
NPP / PB 6/NM	451 019	25
APP / PB 2,5-6/NM	464 009	25

End Plate - Disconnect Plate
TKO PB 2,5/2
TKO PB 2,5/3
TKO PB 2,5/4
TKO PB 2,5/7
TKO PB 2,5/10

Type	Cat.No.	Qty.
TKO PB 2,5/2	479 012	25
TKO PB 2,5/3	479 013	20
TKO PB 2,5/4	479 014	15
TKO PB 2,5/7	479 017	5
TKO PB 2,5/10	479 019	5

Type	Cat.No.	Qty.
TKO PB 2,5/2	479 012	25
TKO PB 2,5/3	479 013	20
TKO PB 2,5/4	479 014	15
TKO PB 2,5/7	479 017	5
TKO PB 2,5/10	479 019	5

Type	Cat.No.	Qty.
TKO PB 2,5/2	479 012	25
TKO PB 2,5/3	479 013	20
TKO PB 2,5/4	479 014	15
TKO PB 2,5/7	479 017	5
TKO PB 2,5/10	479 019	5

Type	Cat.No.	Qty.
TKO- PB 6/2	479 002	25
TKO- PB 6/3	479 003	20
TKO- PB 6/4	479 004	15
TKO- PB 6/7	479 007	5
TKO- PB 6/10	479 009	5

Type	Cat.No.	Qty.
TKO- PB 6/2	479 002	25
TKO- PB 6/3	479 003	20
TKO- PB 6/4	479 004	15
TKO- PB 6/7	479 007	5
TKO- PB 6/10	479 009	5

Type	Cat.No.	Qty.
TKO- PB 6/2	479 002	25
TKO- PB 6/3	479 003	20
TKO- PB 6/4	479 004	15
TKO- PB 6/7	479 007	5
TKO- PB 6/10	479 009	5

Cross Connection
TF (Ø2,3)

Type	Cat.No.	Qty.
TF (Ø2,3)	493 023	5

Type	Cat.No.	Qty.
TF (Ø2,3)	493 023	5

Type	Cat.No.	Qty.
TF (Ø2,3)	493 023	5

Type	Cat.No.	Qty.
TF (Ø2,3)	493 023	5

Type	Cat.No.	Qty.
TF (Ø2,3)	493 023	5

Type	Cat.No.	Qty.
TF (Ø2,3)	493 023	5

Test Plug
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

Type	Cat.No.	Qty.
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T		

Type	Cat.No.	Qty.
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T		

Type	Cat.No.	Qty.
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T		

Type	Cat.No.	Qty.
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T		

Type	Cat.No.	Qty.
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T		

Type	Cat.No.	Qty.
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T		

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

8/3
1/NA
IP 20 / -
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

8/3
1/NA
IP 20 / -
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

8/3
1/NA
IP 20 / PE
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

8/3
1/NA
IP 20 / PE
D_NS 6x10, DB 10/6, DG 10/6, DG 10/6T

8/3
1/NA
IP 20 / -
DN_S 8x10, DG 10/8

8/3
1/NA
IP 20 / -
DN_S 8x10, DG 10/8

Package Quantity
45 pcs.

Package Quantity
45 pcs.

Package Quantity
45 pcs.

Package Quantity
45 pcs.


Package Quantity
45 pcs.

Package Quantity
40 pcs.

Package Quantity
40 pcs.

PB Series "V0"
Feed Through and
Earth Terminals


PB 6 T/NM



Cat No:

337 000


PB 25/NM (M5)



Cat No:

308 049

PB 25/NM (M6)



Cat No:

308 059



Electrical Ratings
CE (EN 60947-7-1 / EN 60947-7-2)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
AWG Conductor
Torque (min.-max.)
Hole Diameter
Bolt Diameter
Screwdriver
Rail Tightening torque, min.-max.

End Plate - Disconnect Plate

Comb Connector

Cross Connection

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix
Package Quantity

Voltage, V ~	Current, A	Cross-Section
		6 mm²
		AWG 22-8
		AWG 22-8

0,5-6 mm²
0,5-6 mm²
AWG 22-8
0,8-1,2 Nm
4 mm
4,0 mm
IKT 5 (1,0x5,5)
0,6-08 Nm

Type	Cat.No.	Qty.
NPP PB 25/NM	451 039	25
APP PB 25/NM	464 019	25

Type	Cat.No.	Qty.

Type	Cat.No.	Qty.
TKO PB 25/2	479 022	25

8/3
1/NA
IP 20 / PE
D_NS 8x10, DG 10/8
40 pcs.

Voltage, V ~	Current, A	Cross-Section
800	101	25 mm²
600	115/85	AWG 26-4
600	115/85	AWG 26-4

1,5-25 mm²
1,5-25 mm²
AWG 26-4
3-3,5 Nm
5,2 mm
5,0 mm
IKT 5 (1,0x5,5)

Type	Cat.No.	Qty.
NPP PB 25/NM	451 039	25
APP PB 25/NM	464 019	25

Type	Cat.No.	Qty.

Type	Cat.No.	Qty.
TKO PB 25/2	479 022	25

8/3
1/NA
IP 20 / PE
D_NS 10x10, DG 10/10
10 pcs.

Voltage, V ~	Current, A	Cross-Section

1,5-25 mm²
1,5-25 mm²
AWG 16-4
3,2-3,7 Nm
6,2 mm
6,0 mm
IKT 5 (1,0x5,5)

Type	Cat.No.	Qty.
NPP PB 25/NM	451 039	25
APP PB 25/NM	464 019	25

Type	Cat.No.	Qty.

Type	Cat.No.	Qty.
TKO PB 25/2	479 022	25

8/3
1/NA
IP 20 / PE
D_NS 10x10, DG 10/10
10 pcs.

Voltage, V ~	Current, A	Cross-Section
800	101	25 mm²
600	115/85	AWG 26-4
600	115/85	AWG 26-4

1,5-25 mm²
1,5-25 mm²
AWG 16-4
3,2-3,7 Nm
6,2 mm
6,0 mm
IKT 5 (1,0x5,5)

Type	Cat.No.	Qty.
NPP PB 25/NM	451 039	25
APP PB 25/NM	464 019	25

Type	Cat.No.	Qty.

Type	Cat.No.	Qty.
TKO PB 25/2	479 022	25

8/3
1/NA
IP 20 / PE
D_NS 10x10, DG 10/10
10 pcs.