


IBK type clamping yokes are designed with yellow - green insulation Widths to emphasise the protection function. They Terminals can be used with DB 5 marking tag.

**IBK 4**  
525 381



**IBK 10**  
525 382




**IBK 35**  
525 383



<b>Electrical Ratings</b>				
Cross-Sec.	4 mm <sup>2</sup>	10 mm <sup>2</sup>	35 mm <sup>2</sup>	
Insulation Stripping Length (min.-max.)	16 mm	19 mm	19 mm	
Fixing Screw	M 3	M 4	M 6	
Busbar Dimensions	10 x 3	10 x 3	10 x 3	
Isolation Width	Yellow-Green	Yellow-Green	Yellow-Green	
Torque	0,5 Nm	1,2 Nm	2,8 Nm	
<b>Qty.</b>				
	100	100	50	
<b>Connection Data</b>				
Solid Strand	0,5 ... 6 mm <sup>2</sup>	1,5 ... 10 mm <sup>2</sup>	16 ... 50 mm <sup>2</sup>	
Fine Strand,	0,5 ... 4 mm <sup>2</sup>	2,5 ... 10 mm <sup>2</sup>	16 ... 35 mm <sup>2</sup>	
AWG Conductor	20 ... 10	14 ... 6	4 ... 1	
<b>Dimensions</b>				
	a	14,1	19,9	8,8
	b	18,8	18,8	31,7
	c	6,4	8,5	14,1

**BKN 4**  
525 410



**BKN 16**  
525 420



**BKN 35**  
525 430



<b>Electrical Ratings</b>				
Cross-Sec.	4 mm <sup>2</sup>	16 mm <sup>2</sup>	35 mm <sup>2</sup>	
Insulation Stripping Length (min.-max.)	16 mm	16 mm	16 mm	
Fixing Screw	M 4	M 5	M 6	
Busbar Dimensions	10 x 3 / 12 x 3	10 x 3 / 12 x 3	10 x 3 / 12 x 3	
Isolation Width	-	-	-	
Torque	1,5 - 1,8 Nm	2,5 - 3 Nm	3,2 - 3,7 Nm	
<b>Qty.</b>				
	50	50	50	
<b>Connection Data</b>				
Solid Strand	0,5 ... 6 mm <sup>2</sup>	1,5 ... 16 mm <sup>2</sup>	2,5 ... 35 mm <sup>2</sup>	
Fine Strand,	0,5 ... 4 mm <sup>2</sup>	1,5 ... 16 mm <sup>2</sup>	2,5 ... 35 mm <sup>2</sup>	
AWG Conductor	20 ... 10	16 ... 6	14 ... 2	
<b>Dimensions</b>				
	a	18	18	18
	b	7	10	14