





Technical Specifications

Made in South Africa  **EZI CANAL**
electrical cable ducting

Slotted trunking (wide slot)



www.em.co.za

| type | dimensions (mm) | | colour | material | description | slot width (mm) | finger width (mm) | standard length (2 m) | carton qty (length) |
|-------------------|-----------------|--------|--------|----------|-------------------------------|-----------------|-------------------|-----------------------|---------------------|
| | width | height | | | | | | | |
| TSL040060W | 40 | 60 | grey | PVC | Wide slotted cable trunking | 8 | 12 | 2 | 28 |
| TSL060060W | 60 | 60 | grey | PVC | Wide slotted cable trunking | 8 | 12 | 2 | 18 |
| TSL080060W | 80 | 60 | grey | PVC | Wide slotted cable trunking | 8 | 12 | 2 | 14 |
| TSL100060W | 100 | 60 | grey | PVC | Wide slotted cable trunking | 8 | 12 | 2 | 12 |
| TSL040080W | 40 | 80 | grey | PVC | Wide slotted cable trunking | 8 | 12 | 2 | 20 |
| TSL060080W | 60 | 80 | grey | PVC | Wide slotted cable trunking | 8 | 12 | 2 | 12 |
| TSL080080W | 80 | 80 | grey | PVC | Wide slotted cable trunking | 8 | 12 | 2 | 8 |
| TSL100080W | 100 | 80 | grey | PVC | Wide slotted cable trunking | 8 | 12 | 2 | 8 |
| TSL040100N | 40 | 100 | grey | PVC | Narrow slotted cable trunking | 4 | 6 | 2 | 16 |
| TSL060100N | 60 | 100 | grey | PVC | Narrow slotted cable trunking | 4 | 6 | 2 | 12 |
| TSL080100N | 80 | 100 | grey | PVC | Narrow slotted cable trunking | 4 | 6 | 2 | 8 |
| TSL100100N | 100 | 100 | grey | PVC | Narrow slotted cable trunking | 4 | 6 | 2 | 8 |

Technical information:

Manufactured from high-impact, self-extinguishing, warp-proof rigid PVC material providing a shock proof insulated protection solution resistant to acids, oils and grease. Used for general purpose control panel wiring to provide improved aesthetics and a neater wire management solution in high density control panels.

- Operating temperature : -5°C to 60°C
- Colour: RAL 7030 Grey
- UL94 flammability rating V-0 for excellent flame retardation.
- Double score-line permits finger/slot or complete sidewall removal
- Simple open/close cover design for easy access to wiring in control panel
- Coining process for burr-free edges to protect hands and wiring from abrasion
- Restricted slot design retains wire within slot for fast, easy wire installation or removal
- Duct and cover form a flush sidewall to provide increased capacity and improved appearance



Systematic wiring that can be re-routed easily



Enhances aesthetics and clarity



Provides complete electrical insulation



Ideal for building applications



Quick and easy to install

Part number breakdown:

